



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: 12002 BASE COAT REDUCER (FAST)**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 12002 BASE COAT REDUCER (FAST)

Recommended use and restrictions on .. Paints.  
use

Chemical family..... Hydrocarbons.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritant 2. Acute Toxicity 4. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system). Carcinogenicity — Category 2. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 This product contains ingredients that are suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys through prolonged or repeated contact.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P260 Do not breathe the mist, vapours, or spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area.

Response ..... P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 - For specific treatment see section 4 on this SDS.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note ..... This product mixture has been classified based on its ingredients.

**PRODUCT: 12002 BASE COAT REDUCER (FAST)****SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS | CAS #    | WT. % |
|----------------------------|----------|-------|
| Ethyl Acetate              | 141-78-6 | 45-55 |
| Toluene                    | 108-88-3 | 10-20 |
| Methyl Ethyl Ketone        | 78-93-3  | 10-20 |
| n-Butyl Acetate            | 123-86-4 | 7-13  |
| Methyl Isobutyl Ketone     | 108-10-1 | 5-10  |

**SECTION 04: FIRST-AID MEASURES**

|                             |  |
|-----------------------------|--|
| Eye contact.....            | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.  |
| Skin contact.....           | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.   |
| Inhalation.....             | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.  |
| Ingestion.....              | If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.            |
| Additional information..... | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

**SECTION 05: FIRE-FIGHTING MEASURES**

|  |   |
|--|---|
| Suitable and unsuitable extinguishing media  | "Alcohol" foam, CO <sub>2</sub> , dry chemical. Do not use water in a jet.  |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO <sub>2</sub> ). Toxic vapours may be evolved upon exposure to heat or open flame.  |
| Special protective equipment and precautions for fire-fighters   | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. |

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

|                 |   |
|-----------------|---|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Evacuate all non-essential personnel. Avoid all personal contact. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|---|

**SECTION 07: HANDLING AND STORAGE**

|  |   |
|--|---|
| Precautions for safe handling.....                           | Keep away from heat, sparks, and open flame. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.  |

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS   | TWA     | ACGIH TLV<br>STEL | PEL     | OSHA PEL<br>STEL | REL     | NIOSH |
|---------------|---------|-------------------|---------|------------------|---------|-------|
| Ethyl Acetate | 400 ppm | Not established   | 400 ppm | Not established  | 400 ppm |       |

**PRODUCT: 12002 BASE COAT REDUCER (FAST)****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS            | ACGIH TLV                                    |                 | PEL     | OSHA PEL           |      | REL                    | NIOSH |
|------------------------|--|-----------------|---------|--------------------|------|------------------------|-------|
|                        | TWA  | STEL            |         | STEL               | STEL |                        |       |
| Toluene                | CA ON: 400 ppm (TWA)<br>20 ppm               | Not established | 200 ppm | 500 ppm 10 minutes |      | 100 ppm / STEL 150 ppm |       |
| Methyl Ethyl Ketone    | CA ON: TWA: 20 ppm<br>200 ppm                | 300 ppm         | 200 ppm | Not established    |      | 200 ppm TWA            |       |
| n-Butyl Acetate        | CA ON: 200ppm (TWA), 300ppm (STEL)<br>50 ppm | 150 ppm         | 150 ppm | 200 ppm            |      | 150 ppm / STEL 200 ppm |       |
| Methyl Isobutyl Ketone | CA ON: 50ppm (TWA), 150ppm (STEL)<br>50 ppm  | 75 ppm          | 100 ppm | Not established    |      | 50 ppm / STEL 75 ppm   |       |
|                        | ON: 20 ppm (TWA), 75 ppm (STEL)              |                 |         |                    |      |                        |       |

**Personal Protective Equipment**

|                                       |  |
|---------------------------------------|--|
| Eye/type.....                         | Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.  |
| Respiratory/type.....                 | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.  |
| Gloves/ type.....                     | Chemical resistant gloves.   |
| Clothing/type.....                    | Wear adequate protective clothes.  |
| Footwear/type.....                    | Safety boots per local regulations.  |
| Other/type.....                       | Emergency showers and eye wash stations should be available.   |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Ventilation system must be designed vapor and explosion proof for handling solvent vapors. |

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

|  |                            |
|--|----------------------------|
| Appearance/Physical state.....                     | Liquid.                    |
| Odour.....   | Solvent odour.             |
| Odour threshold (ppm).....                         | Not available.             |
| Vapour pressure (mm Hg).....                       | Not available.             |
| Vapour density (air=1).....                        | >1.                        |
| pH.....  | Not applicable.            |
| Relative Density (Specific Gravity).....           | 7.26 lbs/USG; 0.870.       |
| Melting / Freezing point (deg C).....              | Not available.             |
| Solubility.....                                    | Slightly soluble in water. |
| Initial boiling point / boiling range (deg C)..... | > 77.                      |
| Evaporation rate.....                              | Not available.             |
| Flash point (deg C), method.....                   | -9 °C. (estimated).        |
| Auto ignition temperature (deg C).....             | > 390.                     |
| Upper flammable limit (% vol).....                 | 12.6.                      |
| Lower flammable limit (% vol).....                 | 1.0.                       |
| Partition coefficient — n-octanol/water.....       | Not available.             |
| % Volatile by volume.....                          | 100.                       |
| VOC (less water).....                              | 7.26 lb/usg.               |
| Viscosity.....                                     | 13.2", Zahn #2.            |

**SECTION 10: STABILITY AND REACTIVITY**

|   |  |
|---|--|
| Chemical stability.....   | Stable at normal temperatures and pressures.   |
| Reactivity .....  | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions.....                                   | Will not occur under normal temperature and pressure.  |
| Conditions to avoid, including static discharge, shock or vibration ..... | Keep away from heat. Incompatible with strong oxidizers.   |
| Hazardous decomposition products.....                                     | Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.                               |

**PRODUCT: 12002 BASE COAT REDUCER (FAST)****SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS                             | LC50   | LD50   |
|---|--|--|
| Ethyl Acetate                           | 16,000 ppm 6 hours rat   | 5,600 mg/kg (rat oral )  |
| Toluene                                 | 8000ppm (rat inhalation)<br>400ppm mouse (inhalation 24hr)   | 5,000 mg/kg (rat ora);<br>12,124 mg/kg (rabbit dermal )                              |
| Methyl Ethyl Ketone                     | >5,000 ppm (6 hours, rat),<br>11000 ppm (45 minutes, mouse)  | 3,400 mg/kg (rat, oral),<br>>8000 mg/kg (rabbit, dermal),<br>670 mg/kg (mouse, oral) |
| n-Butyl Acetate                         | >33 mg/L vapour, 5.2 mg/L<br>(rat) dust/mist   | 10760 mg/kg (rat, oral)<br>14112 mg/kg (rabbit, dermal)                              |
| Methyl Isobutyl Ketone                  | 8.2 - 16.4 mg/L 4 hours rat  | 2080 mg/kg (rat oral)<br>>16,000 mg/kg (rabbit dermal)                               |
| Route of exposure.....                  | Eye contact. Skin contact. Inhalation.   |  |
| Effects of acute exposure.....          | The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation.   |  |
| Skin contact.....                       | Can cause moderate irritation, defatting and dermatitis.   |  |
| Skin absorption.....                    | Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.  |  |
| Eye contact.....                        | Can cause redness, irritation, tissue destruction.   |  |
| Inhalation (acute).....                 | Solvent vapours may be irritating to the eyes, nose and throat, resulting in redness, burning and itching of eyes, dryness of the throat and tightness in the chest. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects.  |  |
| Inhalation (chronic).....               | Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation. |  |
| Ingestion.....                          | Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.   |  |
| Effects of chronic exposure.....        | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. May cause skin defatting and dermatitis.  |  |
| Sensitizing capability of material..... | None reported.   |  |
| Carcinogenicity of material.....        | Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B).   |  |
| Reproductive effects.....               | Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. In one study, Methyl Ethyl Ketone has been found to cause embryol toxicity in large concentrations.  |  |

**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.  
Persistence and degradability..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging Empty containers must be handled with care due to product residue. This material and its container must be disposed of as hazardous waste. Avoid release to the environment.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.  
DOT Classification (Road)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.  
IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity.  
IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity.  
Marine Pollutant..... No.  
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**PRODUCT: 12002 BASE COAT REDUCER (FAST)****SECTION 15: REGULATORY INFORMATION**

|  |   |
|--|---|
| WHMIS 1988 classification.....                     | B2, D2A, D2B.   |
| CEPA status.....                                   | On Domestic Substances List (DSL).  |
| TSCA inventory status.....                         | All components are listed.  |
| OSHA.....  | This product is considered hazardous under the OSHA Hazard Communication Standard.  |
| SARA Title III                                     |   |
| Section 302 - extremely hazardous substances ..... | None.   |
| Section 311/312 - hazard categories.....           | Immediate health, delayed health, fire hazard.  |
| Section 313.....                                   | Methyl Ethyl Ketone. Methyl Isobutyl Ketone. Toluene.   |
| EPA hazardous air pollutants (HAPS) 40CFR63 .....  | Benzene. Cumene. Methyl Isobutyl Ketone. Toluene.   |
| California Proposition 65.....                     | *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. *WARNING: This product contains a chemical known to the State of California to cause cancer. |

**SECTION 16: OTHER INFORMATION**

|   |   |
|---|---|
| Prepared by: .....                                      | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.  |
| Telephone number:.....                                  | (800) 387-7981.   |
| Disclaimer:.....  | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:.....                                       | 2022-11-30.   |
| Date of the latest revision of the safety data sheet .. | 2017-09-22  |