

Fast drying, Acrylic Clearcoat is formulated for use over car, truck, van and SUV small spot and panel repairs. This ready-to-use product will provide a durable, high gloss finish to protect your paint. Exceptional for use on replacement parts, door jambs, hood and truck jambs and cut-ins. UV resistant formula ensures durability and helps protect color and gloss from damage caused by the sun's rays.

PRODUCT**SIZE****12100**

14.9 oz (423 g) Aerosol

12330

12 oz (340 g) Aerosol

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

ADVANTAGES:

- Provides durable, high gloss finish
- UV resistant

SURFACE PREPARATION:

Wash the area to be painted with soap and water. When applying over existing clearcoat, wet sand the clear with 600 grit or finer paper. Clean cured finishes with 19180 Prime Wash Wax & Grease Remover (Mild), clean plastic surfaces with 19040 Plastic Parts Cleaner. When applying over basecoat, allow the basecoat to flash for 1 hour or as per manufacturer's instructions.

DIRECTIONS FOR USE:

1. Shake can for 1 minute after mixing ball moves freely and repeat shaking for 10 seconds after each minute of use. **Note:** Insufficient mixing may cause permanent plugging of the spray head.
2. Apply to clean, dry and properly prepared surfaces.
3. Hold can approximately 8-10" (20-25 cm) from surface, spraying evenly.
4. Two thin coats are recommended rather than one heavy coat. Allow 5 minutes flash time between coats.
5. When finished, turn can upside down and spray about 3 seconds to clean out valve and spray head.

Caution: Test the compatibility of this product with your paint system. Do not use in temperatures below 60°F (16°C). Use below these temperatures will affect dry times and performance. For best results, use when temperature of the can and surface is between 68°F to 75°F (20°C to 24°C).

INCLUDES 2 SPRAYHEADS:

- White sprayhead provides a 6½ width fan spray.
- Red sprayhead provides a 2½ width fan spray.

**TECHNICAL DATA:**

	12100, 12330
Physical State:	Aerosol
Color:	Clear
Odour:	Solvent odour
Solubility:	Slightly soluble in water
Flash Point:	-18°C (-0.40°F)(estimate for liquid)
Auto ignition temperature:	>370°C (698°F)(liquid)
VOC:	2.38 lb/usg - 285 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.