



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 12560 SUPER EXPRESS CLEAR 3.5 VOC

SECTION 01: Chemical product and company identification

Manufactured for..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product name..... 12560 SUPER EXPRESS CLEAR 3.5 VOC

Recommended use and restrictions on use.. Paints. This product should not be used for any other purpose other than the ones described in this section.

Chemical family..... Polyacrylate.

HMIS..... H: 2 F: 3 R: 0.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300. .

SECTION 02: Hazards identification



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Sensitizer 1. Eye Irritant 2A. Specific Target Organ Toxicity — Single Exposure — 3. (narcotic effects). (respiratory system). Carcinogenicity — 2. Reproductive 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 This product contains ingredients that are suspected of causing cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P280 Wear protective gloves and eye protection. P264 Wash thoroughly after handling. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P272 Contaminated work clothing should not be allowed out of the workplace. P271 Use only outdoors or in a well ventilated area.

Response P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P302 + P352 - If on skin: wash with plenty of water. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 - For specific treatment see section 4 on this SDS.

Storage..... P405 Store locked up. P403 + P233 Store in a well ventilated area. Keep container tightly closed. P235 Keep cool.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

PRODUCT: 12560 SUPER EXPRESS CLEAR 3.5 VOC**SECTION 03: Composition/Information on Ingredients**

HAZARDOUS INGREDIENTS	CAS #	WT. %
N-Butyl Acetate	123-86-4	5-17
Acetone	67-64-1	7-13
Ethyl Acetate	141-78-6	7-13
Methyl Isobutyl Ketone	108-10-1	7-13
Propylene Glycol Monomethyl Ether Acetate	108-65-6	5-10
4-Chlorobenzotrifluoride	98-56-6	1-5
Xylene	1330-20-7	<0.5
Bis (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate	41556-26-7	<0.2

SECTION 04: First aid measures

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed.....	Harmful if swallowed, in contact with skin or if inhaled. Causes serious eye irritation. Can cause skin sensitization. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause respiratory irritation.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: Fire fighting measures

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. Do not use water in a jet.
Hazardous combustion products.....	Oxides of carbon (CO, CO ₂). Hydrocarbon fumes and smoke.
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Pick up waste material and place in an appropriate container for disposal. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 07: Handling and storage

Handling procedures.....	Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: Exposure controls / personal protection

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH

PRODUCT: 12560 SUPER EXPRESS CLEAR 3.5 VOC**SECTION 08: Exposure controls / personal protection**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
N-Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm
Acetone	500 ppm	750 ppm	1,000 ppm	Not established	250 ppm
Ethyl Acetate	400 ppm	Not established	400 ppm	Not established	400 ppm
Methyl Isobutyl Ketone	50 ppm	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm
Propylene Glycol Monomethyl Ether Acetate	Not established	Not established	Not established	Not established	Not established
4-Chlorobenzotrifluoride	Not established	Not established	Not established	Not established	Not established
Xylene	50 ppm	150 ppm	100 ppm TWA	Not established	Not established
Bis (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate	Not established	Not established	Not established	Not established	Not established
Protective equipment	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Chemical safety goggles and full faceshield if a splash hazard exists.				
Respiratory/type.....	Chemical resistant gloves.				
Eye/type.....	Wear adequate protective clothes.				
Gloves/ type.....	Safety boots per local regulations.				
Clothing/type.....	Emergency showers and eye wash stations should be available.				
Footwear/type.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .				
Other/type.....					
Appropriate engineering controls.....					

SECTION 09: Physical and chemical properties

Physical state.....	Liquid.
Colour.....	Clear.
Odour.....	Characteristic odour. Solvent odour.
Odour threshold (ppm).....	n-butyl acetate: 0.3 ppm.
Relative Density (Specific Gravity).....	8.2 lb/usg - 0.98 g/mL.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Melting / Freezing point (deg C).....	< -33 C.
Solubility.....	Negligible.
Initial boiling point / boiling range (deg C).....	> 56°C.
Evaporation rate.....	Moderate.
Flash point (deg C), method.....	-18°C. (estimate; lowest flash point ingredient).
Auto ignition temperature (deg C).....	> 300.
Upper flammable limit (% vol).....	12.6.
Lower flammable limit (% vol).....	0.9.
Coefficient of water/oil distribution.....	Not available.
VOC.....	3.58 lb/usg - 429 g/L.
% Volatile by volume.....	66.9.
Viscosity.....	15 sec Zahn #2 .

SECTION 10: Stability and reactivity

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Possibility of hazardous reactions.....	Will not occur under normal temperature and pressure.
Conditions to avoid.....	Keep away from heat. Incompatible with strong oxidizers. Acids. Bases. Halogens.
Hazardous decomposition products.....	Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.

PRODUCT: 12560 SUPER EXPRESS CLEAR 3.5 VOC**SECTION 11: Toxicological information**

INGREDIENTS	LC50	LD50
N-Butyl Acetate	>29.2 mg/L 4 hour rat aerosol 4 hour rat	>3200 mg/kg rat oral >5000 mg/kg rabbit dermal
Acetone	50,100 mg/m ³ 8 hours rat inhalation	5,800 mg/kg rat oral
Ethyl Acetate	16,000 ppm 6 hours rat	5,600 mg/kg rat oral
Methyl Isobutyl Ketone	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal
Propylene Glycol Monomethyl Ether Acetate	Not Available	8,532 mg/kg (rat oral) >5,000 mg/kg (rabbit dermal)
4-Chlorobenzotrifluoride	4479 ppm	>6,800 mg/kg rat oral; >2,700 mg/kg rabbit dermal
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Bis (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate	Not Available	2369-3920 mg/kg oral rat >2000 mg/kg dermal rabbit
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Contains an ingredient which caused reproductive effects in rats after repeated application of large amounts to skin. These effects have not been reported in humans. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Skin contact.....	May cause sensitization by skin contact. Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Solvent vapours may be irritating to the eyes, nose and throat, resulting in redness, burning and itching of eyes, dryness of the throat and tightness in the chest. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation.	
Ingestion.....	May be harmful or fatal if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Carcinogenicity of material.....	Methyl isobutyl ketone is known to the state of California to cause cancer and developmental effects. Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B).	
Reproductive effects.....	High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. Methyl Isobutyl Ketone is known by the State of California to cause adverse fetal developmental effects.	
Sensitizing capability of material.....	May cause sensitization by skin contact.	

SECTION 12: Ecological information

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not available.

SECTION 13: Disposal considerations

Waste disposal.....	Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---------------------	-----------------------------------------------------------------------------------------------------

PRODUCT: 12560 SUPER EXPRESS CLEAR 3.5 VOC

SECTION 14: Transport information

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.

DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.

IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.

IMDG Classification (Marine)..... UN1263 - PAINT- Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity.

Marine Pollutant..... Potential marine pollutant.

Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status..... On Domestic Substances List (DSL).

TSCA inventory status..... Not determined.

OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.

SARA Title III
Section 302 - extremely hazardous substances None.

Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.

Section 313..... Methyl Isobutyl Ketone.

EPA hazardous air pollutants (HAPS) Methyl Isobutyl Ketone. Toluene. Xylene.

40CFR63

California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.

Telephone number:..... (800) 387-7981.

Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Preparation date: NOV 28/2017