



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM

Recommended use and restrictions on .. Paints. No restrictions on use known.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 3. Skin Sensitizer — Category 1. Respiratory Sensitizer — Category 1. Aspiration Toxicity 1. Eye Irritation — Category 2A. Skin Irritation — Category 2. Acute Toxicity (Inhalation) — Category 4. Acute Toxicity (Oral) — Category 4. Acute Toxicity (Dermal) — Category 4. Specific Target Organ Toxicity — Single Exposure — Category 3. (central nervous system). (respiratory system). Specific Target Organ Toxicity — Repeated Exposure — Category 2. (liver, kidney, central nervous system).

Signal Word..... DANGER.

Hazard Description..... H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection. P284 In case of inadequate ventilation wear respiratory protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P301 + P312 If swallowed call a poison control centre. P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P330 Rinse mouth. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P342 + P311 If experiencing respiratory symptoms; call poison center or doctor. P362 + P364 - Take off contaminated clothing and wash before reuse. P337 + P313 - If eye irritation persists get medical attention. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.

Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

PRODUCT: 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM**SECTION 02: HAZARD IDENTIFICATION**

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
 Other hazards..... None known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Butyl Acetate	123-86-4	30-60
Hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	10-30
Xylene	1330-20-7	15-40
Ethylbenzene	100-41-4	10-30
Cumene	98-82-8	0.1-1

<<The actual concentration(s) withheld as a trade secret>> .

Ethyl Benzene & Cumene are in the product which present a health or environmental hazard. *NOTE*

SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention immediately.
 Skin contact..... Wash using plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists, seek medical attention.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
 Ingestion..... If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. Drink plenty of water. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
 Most important symptoms and effects, May cause an allergic skin reaction. Difficulty breathing. Dermatitis. Rash.
 whether acute or delayed
 Additional information..... Treat victims symptomatically. Symptoms may be delayed. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable extinguishing media..... Water spray. Alcohol resistant foam. Carbon dioxide. Dry chemical. Foam. Water fog.
 Unsuitable extinguishing media..... Do not use solid water streams or water jet.
 Specific hazards arising from the Do not allow run-off from fire fighting to enter drains or water courses. Oxides of carbon
 hazardous product, such as the nature of (CO, CO2). Unburned hydrocarbons.
 any hazardous combustion products
 Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective
 precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective Avoid breathing vapours. Avoid skin and eye contact with vapors. Ensure adequate
 equipment and emergency procedures ventilation. Remove all sources of ignition. Ventilate area. Vapours can accumulate in low areas. Vapors can form explosive mixture in air. Do not touch spilled material.
 Environmental precautions..... Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.
 Methods and materials for containment Dike area to contain the spill, prevent runoff from going into drains, absorb residual
 and cleaning up material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste. Soak up with inert material. Keep in suitable container for disposal. Clean up any residual material with absorbent and dispose of as hazardous waste.

SECTION 07: HANDLING AND STORAGE

PRODUCT: 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. Electrostatic charges may be generated during pumping. Ensure that equipment is properly bonded and grounded during filling and transferring as product may become electrostatically charged. Avoid all skin contact. Handle with care. Avoid breathing vapours or mist. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Employees should wash hands and face before eating or drinking. Avoid smoking, drinking or eating in use area. Dispose of rinse water according to local, Provincial and Federal guidelines. Handle in accordance with good industrial hygiene and safety practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from incompatible materials. Store away from sunlight. Store at ambient temperatures.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm vacated	150 ppm - STEL 200 ppm
	CA ON: 50ppm (TWA), 150 ppm (STEL)				
Hexane, 1,6-diisocyanato- homopolymer	Not available	Not available	Not available	Not available	Not available
	Supplier OEL: 0.5mg/m3 (TWA)				
Xylene	50 ppm	150 ppm	100 ppm TWA	Not available	Not available
	CA ON: 100ppm (TWA); 150ppm (STEL)				
Ethylbenzene	100 ppm	125 ppm	100 ppm	Not established	100 ppm / STEL 125 ppm
	CA ON: 20ppm (TWA)				
Cumene	TWA 50 ppm 5 mg/m3	Not available	TWA 50 ppm	Not available	TWA 50 ppm
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.				
Personal Protective Equipment					
Eye/type.....	Chemical safety goggles and full faceshield if a splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.				
Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. Consult your personal protective equipment supplier for additional recommendations.				
Clothing/type.....	Wear adequate protective clothes. Consult your personal protective equipment supplier for additional recommendations.				
Footwear/type.....	Safety boots per local regulations. Consult your personal protective equipment supplier for additional recommendations.				
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Consult your personal protective equipment supplier for additional recommendations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	Not available.
Odour.....	Not available.
Odour threshold (ppm).....	Not available.
pH.....	Not available.
Melting / Freezing point (deg C).....	Not available.
Initial boiling point / boiling range (deg C).	Not available.
Flash point (deg C), method.....	Not available.
Evaporation rate.....	Not available.
Flammability (solids and gases).....	Not applicable.

PRODUCT: 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Upper flammable limit (% vol).....	Not available.
Lower flammable limit (% vol).....	Not available.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	Not available.
Relative Density (Specific Gravity).....	Not available.
Pounds / USG.....	7.72. lbs/GAL.
Solubility.....	Not available.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	Not available.
Decomposition temperature.....	Not available.
Viscosity.....	Not available.
% Volatile by volume.....	79.76.
% Volume Volatile exempt.....	0.00.
VOC LBS/GAL less water.....	5.76.
LBS VOC/GAL solids.....	28.4.
VOC LBS/GAL less exempt volatiles.....	5.76.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Not reactive under normal conditions of use.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Vapours may form explosive mixture with air.
Conditions to avoid, including static	Avoid heat, spark, open flames.
discharge, shock or vibration	
Incompatible materials.....	Strong oxidizing agents, acids, bases. Aldehydes. Reducing agents. Amines. Halogenated compounds. Metals. Peroxides. Nitrogen oxides.
Hazardous decomposition products.....	Oxides of carbon (CO,CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Butyl Acetate	390 ppm (4 hr)	10768 mg/kg oral rat 17600 mg/kg dermal rabbit
Hexane, 1,6-diisocyanato-, homopolymer	4.63 mg/L rat 4 hours	>5,000 mg/kg oral rat >5,000 mg/kg dermal rabbit
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Ethylbenzene	No data	3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal
Cumene	Not available	Not available
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May cause eye irritation.	
Effects of chronic exposure.....	Not available.	
Aspiration Hazard.....	May be fatal if aspirated into the airways.	
Serious eye damage/eye irritation.....	Irritating to the eyes.	
Skin corrosion/irritation.....	Causes skin irritation.	
Respiratory or Skin Sensitization.....	This product may cause skin sensitization. May cause allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. .	
Carcinogenicity.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.	
Reproductive effects.....	No component of this product present at levels greater than or equal to 0.1% .	
Mutagenicity.....	No component of this product present at levels greater than or equal to 0.1% .	
STOT-SE.....	Target organs:. Central nervous system.	
STOT-RE.....	Target organs:. Central nervous system. Kidney. Liver.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	May be dangerous for the environment. .
Bioaccumulative potential.....	Not available as a product.
Mobility in soil.....	Not available as a product.
Persistence and degradability.....	Not available as a product.
Other adverse effects.....	Not available.

PRODUCT: 12582 PRODUCTION CLEAR ACTIVATOR 2:1 MEDIUM**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

UN number..... UN1263.
 Shipping name..... Paint Related Material.
 Class..... 3.
 Packaging group..... II.
 Exemptions..... This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
 DOT Classification (Road)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... Potential marine pollutant.
 Proof of Classification..... This product has been classified in accordance with DOT and Canada's Part 2 of the Transportation of Dangerous Goods regulations.

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 Categorization of the DSL..... Some components met the criteria under subsection 73(1) of CEPA during categorization of the DSL. Please check to see if this affects your company. (CAS # 123-86-4). (CAS # 28182-81-2). (CAS # 100-41-4). (CAS # 98-82-8).
 National Pollutant Release Inventory (NPRI)..... Some components are subject to reporting under NPRI. Please check your responsibility. (CAS # 1330-20-7 (CAT 1A &5)). (CAS # 100-41-4 (CAT 1A)). (CAS # 98-82-8 (CAT 1A)).
 Environmental Emergency Regulations.... Some components of this product are on the Environmental Emergency Regulations and may require additional reporting. (CAS # 1330-20-7), (CAS # 100-41-4).
 TSCA inventory status..... All components are either listed or exempt from the TSCA. .
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Xylene. Ethylbenzene. Cumene. n-Butyl Acetate.
 EPA hazardous air pollutants (HAPS) 4,4'-methylenediphenyl diisocyanate. Xylene. Ethylbenzene. Cumene.
 40CFR63
 California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Ethylbenzene). (Cumene). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... **DISCLAIMER:** All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Review Date:..... 2022-11-30.
 Date of the latest revision of the safety data sheet .. 2023-08-23