



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)

Recommended use and restrictions on .. Primer.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC) - IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosols — Category 2. Gases Under Pressure: Liquefied Gas. Skin Corrosion/Irritation — Category 2. Serious Eye Damage/Eye Irritation — Category 2A. Sensitization - Skin — Category 1. Carcinogenicity — Category 2. Reproductive Toxicity — Category 1. Specific Target Organ Toxicity — Single Exposure — Category 1. (Respiratory, CNS). Specific Target Organ Toxicity — Repeated Exposure — Category 1. (Auditory system). (Eyes). Aspiration Toxicity 1. Aquatic Acute 1. Aquatic Chronic 3.

Hazard Description..... H223 Flammable aerosol . H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 This product contains ingredients that are suspected of causing cancer. H360 May damage fertility or the unborn child. H370 Causes damage to organs. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H412 Harmful to the aquatic life with long lasting effects.

Precautionary Statements

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe the mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves and eye protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P302 + P352 - If on skin: wash with plenty of water. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P308 + P311 If exposed or concerned; call a poison center or doctor. P308 + P313 If exposed or concerned, get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P337 + P313 - If eye irritation persists get medical attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P391 Collect spillage.

Storage..... P403 Store in a well ventilated area. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Other hazards..... None known.

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|-------|
| Acetone | 67-64-1 | 15-40 |
| Propane | 74-98-6 | 7-13 |
| Titanium Dioxide | 13463-67-7 | 7-13 |
| Isobutane | 75-28-5 | 5-10 |
| Methyl Ethyl Ketone | 78-93-3 | 5-10 |
| Isobutyl Acetate | 110-19-0 | 1-5 |
| Talc | 14807-96-6 | 1-5 |
| Ethyl 3-Ethoxypropionate | 763-69-9 | 1-5 |
| Xylene | 1330-20-7 | 1-5 |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | 1-5 |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | 1-5 |
| Solvent naphtha (petroleum), light aliph. (VM&P Naphtha) | 64742-89-8 | 1-5 |
| 2-Propanol, 1-methoxy-, acetate | 108-65-6 | 1-5 |
| n-Butyl Acetate | 123-86-4 | 1-5 |
| Ethylbenzene | 100-41-4 | 0.1-1 |
| Naphtha, petroleum, hydrodesulfurized heavy | 64742-82-1 | 0.1-1 |
| N-methyl pyrrolidone | 872-50-4 | 0.1-1 |
| Benzene, ethenylmethyl- | 25013-15-4 | 0.1-1 |
| Calcium Carbonate | 1317-65-3 | 0.1-1 |

SECTION 04: FIRST-AID MEASURES

| | |
|---|---|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Consult a physician if irritation continues. |
| Skin contact..... | Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | This product contains ingredients suspected of causing cancer. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes severe skin and eye irritation. May cause breathing difficulty. Irritating to the mucous membranes. May cause redness and swelling of the tissue. May damage fertility or the unborn child. Aspiration hazard. May be fatal if swallowed and enters airways. |
| Immediate medical attention and special . treatment needed, if necessary | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable extinguishing media..... | "Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used. |
| Unsuitable extinguishing media..... | Do not use solid water streams or water jet. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Do not allow run-off from fire fighting to enter drains or water courses. Closed containers may explode when exposed to extreme heat. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Vapours can accumulate in low areas. Vapors may form explosive mixture in air. Other potentially toxic fumes. Use water spray to cool containers. Oxides of carbon (CO, CO ₂). Other potentially toxic fumes. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control. |

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 06: ACCIDENTAL RELEASE MEASURES**

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | No action shall be taken involving any personal risk or without suitable training. Ventilate and emergency procedures area. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08). Isolate area and keep unauthorized people away.. Open windows and doors to allow air circulation. Dike area to prevent spreading. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Take precautions against static discharge. Beware of possible flashback. |
| Environmental precautions..... | Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities. |
| Methods and materials for containment and cleaning up | Contain spilled material and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations. Large spill:. Dike area to contain the spill, prevent runoff from going into drains, absorb residual material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste. |

SECTION 07: HANDLING AND STORAGE

| | |
|--|---|
| Precautions for safe handling..... | Do not spray on a naked flame or any incandescent material. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat, sparks, and open flame. This material is a static accumulator. Prevent accumulation of electrostatic charges. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Do not eat, drink or smoke while using this product. Employees should wash hands and face before eating or drinking. Handle in accordance with good industrial hygiene and safety practices. |
| Conditions for safe storage, including any incompatibilities | Electrical installations / working materials must comply with the technological safety standards. Keep away from heat, sparks, and open flames. Store away from sunlight. No smoking. Pressurized container, do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush container. Do not cut, grind or weld on or near container, do not expose containers to heat, flame, sparks, static electricity , or other sources of ignition: the containers may explode and cause injury or death. Incompatible materials include, but not limited to:. Strong acids. Strong bases. Strong oxidizing agents. Strong oxidizers. Metals. Store away from reducing materials. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|---|--|-------------------|-----------------|------------------|-----------------|-----------------|
| Acetone | 250 ppm TLV CA ON AB: 500ppm (TWA); 750ppm (STEL) | 500 ppm | 1,000 ppm | Not established | 250 ppm | |
| Propane | 1,000 ppm | Not established | 1,000 ppm | Not established | 1,000 ppm | |
| Titanium Dioxide | 10 mg/m3 CA ON: 10 mg/m3 (TWA) | Not available | 15 mg/m3 | Not available | Not available | |
| Isobutane | Not established | Not established | Not established | Not established | 800 ppm | |
| Methyl Ethyl Ketone | 200 ppm CA ON: 200ppm (TWA), 300ppm (STEL) | 300 ppm | 200 ppm | Not established | 200 ppm TWA | |
| Isobutyl Acetate | 50 ppm | 150 ppm | 150 ppm | Not established | 150 ppm | |
| Talc | 2 mg/m3 CA ON: 2mg/kg (TWA) | Not available | 2 mg/m3 TWA | Not available | 2 mg/m3 | |
| Ethyl 3-Ethoxypropionate | Not established | Not established | Not established | Not established | Not established | Not established |
| Xylene | 50 ppm CA ON: 100ppm (TWA); 150ppm (STEL) | 150 ppm | 100 ppm TWA | Not available | Not available | |
| Naphtha (petroleum), hydrotreated light | 1640 mg/m3 (heptane) 1100 ppm (IDLH) | Not established | Not established | Not established | Not established | Not established |

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|--|---|-------------------|-----------------|------------------|---------------------------|
| Naphtha (petroleum), hydrotreated heavy | 175 ppm Not available | Not available | Not available | Not available | Not available |
| Solvent naphtha (petroleum), light aliph. (VM&P Naphtha) | 100 ppm Not available | 300 ppm | 100 ppm | Not established | Not established |
| 2-Propanol, 1-methoxy-, acetate | 50 ppm | 75 ppm | Not established | Not established | Not established |
| n-Butyl Acetate | 50 ppm | 150 ppm | 150 ppm | 200 ppm | 150 ppm / STEL 200 ppm |
| Ethylbenzene | CA ON: 50ppm (TWA), 150ppm (STEL) 100 ppm | 125 ppm | 100 ppm | Not established | 100 ppm / STEL 125 ppm |
| Naphtha, petroleum, hydrodesulfurized heavy | Not available Not available | Not available | Not available | Not available | Not available |
| N-methyl pyrrolidone | Not Established | Not Established | Not Established | Not Established | Not Established |
| Benzene, ethenylmethyl- | 50 ppm 25 ppm (STEV) | 100 ppm | | | |
| Calcium Carbonate | Not available Not available | Not available | 5 mg/m3 | Not available | 5 mg/m3 |
| Appropriate engineering controls..... | Local exhaust at points of emission. Ventilation system should be designed for vapors and explosion proof for handling solvent vapors. | | | | |
| Personal Protective Equipment Eye/type..... | Liquid chemical goggles. Consult your personal protective equipment supplier for additional recommendations. | | | | |
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Consult your personal protective equipment supplier for additional recommendations. | | | | |
| Gloves/ type..... | Chemical resistant gloves. Consult your personal protective equipment supplier for additional recommendations. | | | | |
| Clothing/type..... | Wear chemical resistant clothing. Consult your personal protective equipment supplier for additional recommendations. | | | | |
| Footwear/type..... | Wear chemical resistant safety boots. Consult your personal protective equipment supplier for additional recommendations. | | | | |
| Other/type..... | Emergency showers and eye wash stations should be available. | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Form..... | Aerosol. |
| Appearance/Physical state..... | Spray mist. |
| Colour..... | Not available. |
| Odour..... | Hydrocarbon. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | Not available. |
| Vapour density (air=1)..... | Not available. |
| pH..... | Not applicable. |
| Relative Density (Specific Gravity)..... | Not available. |
| Melting / Freezing point (deg C)..... | Not available. |
| Solubility..... | Not available. |
| Initial boiling point / boiling range (deg C). | Not available. |
| Evaporation rate..... | Not available. |
| Flash point (deg C), method..... | -155.27°F (-104.039 °C) Closed Cup. (Propellant). |
| Auto ignition temperature (deg C)..... | 450°C (842°F). (Propellant). |
| Upper flammable limit (% vol)..... | 2.0. (Propellant). |
| Lower flammable limit (% vol)..... | 9.5. (Propellant). |
| Aerosol Flame Projection..... | >15 cm and <100 cm. |
| Flashback..... | Yes. |

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

| | |
|--|-------------------|
| Partition coefficient — n-octanol/water..... | Not available. |
| Decomposition temperature..... | Not available. |
| Viscosity..... | Not available. |
| % Weight Volatile (VOC)..... | Greater than 30%. |
| Total MIR..... | 0.64. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. Propylene Glycol Monomethyl Ether Acetate may form peroxides of unknown stability. Gives off hydrogen by reaction with metals. Reacts with air to form peroxide. Vapours may form explosive mixture with air. |
| Conditions to avoid, including static discharge, shock or vibration | Keep away from heat. Excessive temperatures. May cause product to become unstable and auto-oxidize into Fe ₂ O ₃ which will generate additional heat. Vapours may form explosive mixture with air. Under certain conditions this heat may be sufficient to cause combustible materials to ignite. Prolonged heat/light/air exposure. Avoid exposure to moisture. Static discharge. Electrostatic charge. |
| Incompatible materials..... | Strong oxidizing agents. Acids. Bases. Oxidizing agents. Metals. Strong acids. Strong bases. |
| Hazardous decomposition products..... | Oxides of carbon (CO,CO ₂). Oxides of sulphur (sox). Methyl methacrylate, Isobornyl methacrylate. Thermal decomposition may produce acrid smoke and irritating fumes. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|---|--|
| Acetone | 50,100 mg/m ³ 8 hours, rat | 5,800 mg/kg (rat oral) |
| Propane | >1,464 mg/L 15 minutes rat | Not available |
| Titanium Dioxide | >6.8 mg/L (4 hr) | >10,000 mg/kg (rat, oral) >10,000 mg/kg (rabbit, dermal) |
| Isobutane | 52 mg/L 1 hour mouse | Not available |
| Methyl Ethyl Ketone | >5,000 ppm (6 hours, rat), 11000 ppm (45 minutes, mouse) | 3,400 mg/kg (rat, oral), >8000 mg/kg (rabbit, dermal), 670 mg/kg (mouse, oral) |
| Isobutyl Acetate | >13.24 mg/L /6 h rat | 15400 mg/kg (rat oral), >17400 mg/kg (rabbit dermal) |
| Talc | Not available | Not available |
| Ethyl 3-Ethoxypropionate | >998 ppm 6 hours | 4,309 mg/kg rat oral 4,080 mg/kg rabbit dermal |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Naphtha (petroleum), hydrotreated light | 73680 ppm 4 hours rat | >5000 mg/kg (oral, rat) >3160 mg/mg (dermal, rabbit) |
| Naphtha (petroleum), hydrotreated heavy | >8500 mg/m ³ (rat, 4 hr) | >6000 mg/kg (oral, rat) |
| Solvent naphtha (petroleum), light aliph. (VM&P Naphtha) | 3400 ppm 4hr Rat | >2000 mg/kg Oral Rat >2000 mg/kg Dermal Rat |
| 2-Propanol, 1-methoxy-, acetate | Not Available | 8,532 mg/kg rat oral 5,000 mg/kg dermal rabbit |
| n-Butyl Acetate | >33 mg/L vapour, 5.2 mg/L (rat) dust/mist | 10760 mg/kg (rat, oral) 14112 mg/kg (rabbit, dermal) |
| Ethylbenzene | No data | 3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal |
| Naphtha, petroleum, hydrodesulfurized heavy | Inhalation LC50 (Rat): > 11.6 mg/l | Oral LD50 (Rat): > 5,000 mg/kg Dermal LD50 (Rabbit): > 3,000 mg/kg |
| N-methyl pyrrolidone | No Data | 3600 mg/kg (oral, rat) |
| Benzene, ethenylmethyl- | Not available | Not available |
| Calcium Carbonate | Not available | 6450 mg/kg rat oral |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. Ingestion. | |
| Skin contact..... | Can cause moderate irritation, defatting and dermatitis. | |

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 11: TOXICOLOGICAL INFORMATION**

| | |
|--|--|
| Skin absorption..... | May be absorbed by the skin. |
| Eye contact..... | Can cause redness, irritation, tissue destruction. |
| Inhalation (acute)..... | Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness. |
| Inhalation (chronic)..... | Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. |
| Ingestion..... | May be harmful or fatal if swallowed. Swallowing causes inebriation, headache, vomiting, leading to severe illness, blindness, even death. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. |
| Serious eye damage/eye irritation..... | Causes serious eye damage. |
| Skin corrosion/irritation..... | Harmful in contact with skin. |
| Skin Sensitization..... | May cause an allergic skin reaction. |
| Respiratory Sensitization..... | Not expected to be a respiratory sensitizer. |
| Carcinogenicity..... | IARC has classified Titanium Dioxide as a "Group 2B"; possibly carcinogenic to humans. Ethylbenzene is classified as an A3 known animal carcinogen. Xylene has been listed by IARC as a Group 3; not classifiable as to its carcinogenicity to humans. |
| Reproductive effects..... | May damage fertility or the unborn child. |
| Mutagenicity..... | No evidence of mutagenicity. |
| STOT-SE..... | Solvents may decrease the skin. . Classification includes narcotic effects in a single exposure. May irritate the skin. May cause drowsiness or dizziness. |
| STOT-RE..... | Causes damage to organs through repeated or prolonged exposure. |
| Aspiration Hazard..... | May be fatal if swallowed and enters airways. |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Bioaccumulative potential..... | Not available as a product. |
| Mobility in soil..... | Not available as a product. |
| Persistence and degradability..... | Not available as a product. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. |
|---|---|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1950, AEROSOLS, Class 2.1, Ltd. Qty. |
| DOT Classification (Road)..... | UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. |
| IATA Classification (Air)..... | UN1950, AEROSOLS, Class 2.1, Ltd. Qty. |
| IMDG Classification (Marine)..... | UN1950, AEROSOLS, Class 2.1, Ltd. Qty. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|--|
| CEPA status..... | Calcium carbonate is considered a naturally occurring substance and is therefore exempt from listing on the DSL. The balance of the substances are on the DSL. |
| National Pollutant Release Inventory (NPRI)..... | Some components are subject to reporting under NPRI. Please check your responsibility. (CAS # 64742-48-9 (CAT 5)). (CAS # 108-65-6 (CAT 5)). (CAS # 100-41-4 (CAT 1A)). (CAS # 872-50-4 (CAT 1A)). (CAS # 64742-89-8 (Cat 5)). (CAS # 1330-20-7 (CAT 1A & 5)). |
| Environmental Emergency Regulations..... | Some components of this product are on the Environmental Emergency Regulations and may require additional reporting. Ethylbenzene (CAS # 100-41-4) Part 1. Xylene (CAS # 1330-20-7) Part 1. |
| Categorization of the DSL..... | Some components met the criteria under subsection 73(1) of CEPA during categorization of the DSL. Please check to see if this affects your company. (CAS # 64742-82-1). (CAS # 110-19-0). (CAS # 14807-96-6). (CAS # 64742-48-9). (CAS # 100-41-4). (CAS # 13463-67-7). (CAS # 872-50-4). (CAS # 64742-89-8). (CAS # 64742-49-0). (CAS # 1330-20-7). (CAS # 25013-15-4). |
| TSCA inventory status..... | All components are either listed or exempt from the TSCA. . |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |

PRODUCT: 13000 1K HIGH BUILD PRIMER/FILLER (BUFF)**SECTION 15: REGULATORY INFORMATION**

| | |
|--|---|
| SARA Title III | |
| Section 302 - extremely hazardous substances | None known. |
| Section 311/312 - hazard categories | Immediate health, delayed health, fire hazard. |
| Section 313 | Ethylbenzene. Xylene. N-Methyl-2-pyrrolidone. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | Ethylbenzene. Xylene. |
| California Proposition 65 | *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (N-methyl pyrrolidone (nmp)(D)). *WARNING: This product contains a chemical known to the State of California to cause cancer. (Ethylbenzene (C)). (Titanium dioxide - airborne, unbound particles of respirable size). |
| Note | The VOC content listed in section 9 is as per the interpretation that there is no CARB or ECCC category for this product format - therefore, there is no limit to meet. |

SECTION 16: OTHER INFORMATION

| | |
|--|---|
| Prepared by: | REGULATORY AFFAIRS. |
| Telephone number: | (800) 387-7981. |
| Disclaimer: | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Date of the latest revision of the safety data sheet | 2025-01-20 |