



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 13062 2K URETHANE PRIMER/SURFACER GRAY

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 13062 2K URETHANE PRIMER/SURFACER GRAY

Recommended use and restrictions on .. Paints.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 2 F: 4 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Acute Toxicity (Inhalation) — Category 4. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). Carcinogenicity — Category 1. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H350 This product contains ingredients that may cause cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P308 + P313 If exposed or concerned, get medical advice/attention.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

PRODUCT: 13062 2K URETHANE PRIMER/SURFACER GRAY**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Talc	14807-96-6	10-30
Xylene	1330-20-7	5-10
Titanium Dioxide	13463-67-7	5-10
N-Butyl Acetate	123-86-4	5-10
Toluene	108-88-3	1-5
Methyl N-Amyl Ketone	110-43-0	1-5
Methyl Isobutyl Ketone	108-10-1	1-5
Crystalline Silica	14808-60-7	0.5-5
Ethylbenzene	100-41-4	0.1-1

<<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: FIRST-AID MEASURES

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Immediately flush skin with plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Rinse mouth with water. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. The main hazard from ingestion is aspiration of the liquid into the lungs.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. This product contains ingredients that are suspected of damaging fertility or the unborn child. This product contains ingredients that may cause cancer. Causes damage to organs through prolonged or repeated exposure.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO2, dry chemical. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Flammable liquid. This material is a static accumulator. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO2). Other potentially toxic fumes.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Use non-sparking tools and equipment to pick up the spilled material.
Methods and materials for containment and cleaning up Leak/spill.....	Ventilate. Eliminate all sources of ignition. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Use non-sparking tools and equipment to pick up the spilled material. Cover spill with absorbent material and place in appropriate containers. Spill area can be washed with water. Collect wash water for approved disposal.

PRODUCT: 13062 2K URETHANE PRIMER/SURFACER GRAY**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep container closed when not in use.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	NIOSH REL
Talc	2 mg/m3	Not established	2 mg/m3 TWA	3 mg/m3 - QUE	Not established
Xylene	50 ppm	150 ppm	100 ppm TWA	Not established	Not established
Titanium Dioxide	10 mg/m3	Not established	15 mg/m3	Not established	Not established
N-Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm
Toluene	20 ppm	Not established	200 ppm	500 ppm 10 minutes	100 ppm / STEL 150 ppm
Methyl N-Amyl Ketone	50 ppm	Not established	100 ppm	465 mg/m3 TWA	Not established
Methyl Isobutyl Ketone	50 ppm	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm
Crystalline Silica	0.025 mg/m3	Not established	0.1 mg/m3 TWA	Not established	0.05 mg/m3
Ethylbenzene	100 ppm	125 ppm	100 ppm	Not established	100 ppm / STEL 125 ppm
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. . Explosion-proof exhaust ventilation.				
Personal protective equipment					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Eye/type.....	Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists.				
Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid.

Colour..... Gray.

Odour..... Solvent odour.

Odour threshold (ppm)..... Not available.

pH..... No data.

Melting / Freezing point (deg C)..... < 0 °C.

Initial boiling point / boiling range (deg C)..... > 100° C.

Flash point (deg C), method..... 4. (estimate; lowest flash point ingredient).

Evaporation rate..... Not available.

Flammability (solids and gases)..... Not applicable. Flammable liquid.

Upper flammable limit (% vol)..... 8.0.

Lower flammable limit (% vol)..... 1.0.

Vapour pressure (mm Hg)..... Not available.

Vapour density (air=1)..... >1.

Relative Density (Specific Gravity)..... 1.465.

Pounds / USG..... 12.22.

Solubility..... Negligible.

Coefficient of water/oil distribution..... Not available.

Auto ignition temperature (deg C)..... >250.

PRODUCT: 13062 2K URETHANE PRIMER/SURFACER GRAY**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Decomposition temperature..... Not available.
 Viscosity..... 3130 cps Spindle #4 @20.
 % Volatile by weight..... 31.2.
 VOC..... 456.5 g/l - 3.81 lb/usg.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
 Chemical stability..... Stable at normal temperatures and pressures.
 Possibility of hazardous reactions..... Will not occur under normal temperature and pressure.
 Conditions to avoid, including static Keep away from heat. Electrostatic charge. Static discharge.
 discharge, shock or vibration
 Incompatible materials..... Strong acids. Strong bases. Strong oxidizers. Acetic acid. Nitric acid. Bromine. Florine.
 Chlorine compounds.
 Hazardous decomposition products..... See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Talc	Not available	Not available
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Titanium Dioxide	Not Available	> 10,000 mg/kg rat oral > 10,000 mg/kg rabbit dermal
N-Butyl Acetate	>29.2 mg/L 4 hour rat >23.4 mg/L aerosol 4 hour rat	>3200 mg/kg rat oral >5000 mg/kg rabbit dermal
Toluene	8000 ppm rat inhalation 400 ppm mouse inhalation 24hr	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
Methyl N-Amyl Ketone	Not Available	1,670 mg/kg rat oral 12,600 mg/kg rabbit dermal
Methyl Isobutyl Ketone	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal
Crystalline Silica	Not available	>22,500 mg/kg oral rat
Ethylbenzene	No data	3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal
Route of exposure.....	Eye contact. Skin contact. Inhalation. Ingestion.	
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated exposure may lead to liver, kidney or central nervous system symptoms. This product contains crystalline silica. Excessive long-term exposure to crystalline silica may cause silicosis, a form of disabling, progressive and sometimes fatal fibrotic lung disease. Severe and permanent lung damage may result. Repeated contact with the skin may cause dermatitis in sensitive individuals.	
Carcinogenicity of material.....	Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. Ethylbenzene is classified as an A3 known animal carcinogen. IARC has classified Titanium Dioxide as a group 2B carcinogen. Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B).	
Reproductive effects.....	Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. Methyl Isobutyl Ketone is known by the State of California to cause adverse fetal developmental effects.	
Specific Target Organ Toxicity	May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure .	

PRODUCT: 13062 2K URETHANE PRIMER/SURFACER GRAY**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
 DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are either listed or exempt from the TSCA. .
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Ethylbenzene. Methyl Isobutyl Ketone. Toluene. Xylene.
 EPA hazardous air pollutants (HAPS) Ethylbenzene. Methyl Isobutyl Ketone. Toluene. Xylene.
 40CFR63
 California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Methyl Isobutyl Ketone (D)). (Toluene). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer. (Carbon black - airborne, unbound particles of respirable size). (Ethyl benzene). (Methyl Isobutyl Ketone (C)). (Silica, crystalline (airborne particles of respirable size). (Titanium dioxide - airborne, unbound particles of respirable size). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Date of the latest revision of the safety data sheet .. 2019-06-05