



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)

SECTION 01: IDENTIFICATION

Product identifier..... 13170 2K EPOXY PRIMER/SEALER (GRAY)
 Other means of identification
 Chemical family..... Mixture.
 Recommended use and restrictions on .. Paints.
 use
 Initial supplier identifier..... Pro Form Products Ltd.
 604 McGeachie Drive
 Milton, Ontario L9T3Y5
 Tel (905) 878-4990 Fax (905) 878-1189
 24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
 IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
 ** For medical emergencies contact your local poison control centre **.
 -
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F: 4 R: 0.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Corrosion/Irritation - Category 1B. Serious Eye Damage/Eye Irritation — Category 1. Carcinogenicity — Category 1. Aspiration Toxicity 1. Sensitization - Skin — Category 1. Specific Target Organ Toxicity — Single Exposure — Category 3. (Respiratory System). (CNS). Specific Target Organ Toxicity — Repeated Exposure — Category 1. (Respiratory). Acute Toxicity (Inhalation) — Category 4. Acute Toxicity (Oral) — Category 4. Acute Toxicity (Dermal) — Category 4.

Signal Word..... DANGER.

Hazard Description..... H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash hands thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P301 + P312 If swallowed call a poison control centre. P301 + P330 + P331 If Swallowed: Rinse mouth. Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P308 + P313 If exposed or concerned, get medical advice/attention. P310 - Immediately call your local poison control centre. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)**SECTION 02: HAZARD IDENTIFICATION**

Response	treatment see section 4 on this SDS. P330 Rinse mouth. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P363 - Wash contaminated clothing before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.
Storage.....	P403+P433+P435 Store in a well ventilated area. Keep container tightly closed. Keep cool. P405 Store locked up.
Disposal.....	P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Other hazards.....	None known.
Note	This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Talc	14807-96-6	10-30
tert-Butyl acetate	540-88-5	7-13
Diglycidyl ether of bisphenol A	25036-25-3	7-13
Titanium Dioxide	13463-67-7	5-10
4-Chlorobenzotrifluoride	98-56-6	3-7
Xylene	1330-20-7	1-7
Butyl Alcohol	71-36-3	1-5
Sepiolite Clay	63800-37-3	1-5
Distillates (petroleum), hydrotreated light	64742-47-8	0.1-1
Ethylbenzene	100-41-4	0.1-1
Crystalline Silica	14808-60-7	0.1-1
2-Propanol, 1-methoxy-, acetate	108-65-6	0.1-1
Solvent Naphtha, Light Aromatics	64742-95-6	0.1-1
Petroleum (highly purified)	8009-03-8	0.1-1
Calcium carbonate	471-34-1	0.1-1
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	61789-72-8	0.1-1.0
Carbon Black	1333-86-4	0.1-1
Aluminum Hydroxide	21645-51-2	0.1-1
Silica, Amorphous	7631-86-9	0.1-1
Acetate Ester	HMIRA # 9615	Not available
Aryl Halides	HMIRA # 9615	Not available

<<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: FIRST-AID MEASURES

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If swallowed, do not induce vomiting. Give large quantity of water. Call a physician immediately. Never give anything by mouth to an unconscious person. Rinse mouth with water. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs.
Skin contact.....	Immediately flush skin with plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. Wash clothing before reuse. If irritation persists, seek medical attention.
Eye contact.....	Check for and remove any contact lenses, if safe and easy to do so. Flush eyes for 15 minutes with plenty of water. Get medical attention immediately.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. This product contains ingredients that may cause cancer.
Indication of immediate medical attention and special treatment needed, if necessary	Treat symptomatically.
Additional information.....	In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable extinguishing media.....	Carbon dioxide, dry chemical, foam. In cases of larger fires, water spray should be used.
Unsuitable extinguishing media.....	Do not use solid water streams or water jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Do not allow run-off from fire fighting to enter drains or water courses. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO ₂). Metal oxides. Silicone dioxide. Cadmium oxide. Silica fumes. Oxides of boron. Sulfur Oxides.
Special protective equipment and precautions for fire-fighters	Extremely flammable. Keep away from heat, sparks and flame. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Environmental precautions.....	Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.
Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Take precautions against static discharge. Use non-sparking tools and equipment to pick up the spilled material. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Beware of vapours accumulating to form explosive concentrations. Vapors can accumulate in low lying areas.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).. Cover spill with inert absorbant material. Sweep up and place in container for proper disposal. Always wear ppe during cleanup. Dispose of waste material in accordance with all Local, Provincial and Federal Regulations. Stop the flow of material if safe to do so. Take precautionary measures against static discharge. Treat original container as hazardous due to any residual product still in container. Use non-sparking tools. Wear proper personal protection equipment.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Use explosion proof equipment. Use caution in solvent applications to prevent ignition of solvent. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. Wash contaminated clothing prior to reuse. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use. Attacks some types of rubber, plastics and coatings. Incompatible materials include, but not limited to:.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV		OSHA PEL		NIOSH REL
	TWA	STEL	PEL	STEL	
Talc	2 mg/m ³	Not available	2 mg/m ³ TWA	Not available	2 mg/m ³
	CA ON: 2mg/kg (TWA)				
tert-Butyl acetate	200 ppm	Not established	200 ppm	Not established	200 ppm
	CA ON AB BC: 50ppm (TWA), 200ppm (STEL)				
Diglycidyl ether of bisphenol A	Not established	Not established	Not established	Not established	Not established
Titanium Dioxide	10 mg/m ³	Not available	15 mg/m ³	Not available	Not available
	CA ON: 10 mg/m ³ (TWA)				
4-Chlorobenzotrifluoride	Not established	Not established	Not established	Not established	Not established
Xylene	50 ppm	150 ppm	100 ppm TWA	Not available	Not available
	CA ON: 100ppm (TWA); 150ppm (STEL)				

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV		PEL	OSHA PEL		NIOSH
	TWA	STEL		STEL	REL	
Butyl Alcohol	20 ppm CA ON: 20 ppm (TWA)	Not established	100 ppm	Not established	50 ppm skin	
Sepiolite Clay	Not available Not available	Not available	Not available	Not available	Not available	
Distillates (petroleum), hydrotreated light	1200 mg/m3	Not established	Not established	Not established	Not established	
Ethylbenzene	100 ppm CA ON: 20ppm (TWA)	125 ppm	100 ppm	Not established	100 ppm / STEL 125 ppm	
Crystalline Silica	0.025 mg/m3 CA ON: 0.025 mg/m3 Respirable	Not available	0.1 mg/m3 TWA	Not available	0.05 mg/m3	
2-Propanol, 1-methoxy-, acetate	50 ppm	75 ppm	Not established	Not established	Not established	
Solvent Naphtha, Light Aromatics	Not established	Not established	500 ppm (2000 mg/m3) TWA	Not established	350 mg/m3 TWA	
Petroleum (highly purified)	Not available Not available	Not available	Not available	Not available	Not available	
Calcium carbonate	Not available	Not available	Not available	Not available	TWA (respirable) 5 mg/m3 TWA (total) 10 mg/m3	
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	Not established	Not established	Not established	Not established	Not established	
Carbon Black	3 mg/m3 CA ON: 3 mg/m3 (Inhalable) TWA	Not established	3.5 mg/m3	Not established	3.5 mg/m3	
Aluminum Hydroxide	1 mg/m3	Not Established	Not Established	Not Established	5 mg/m3	
Silica, Amorphous	Not established	Not established	Not established	Not established	Not established	
Acetate Ester	Not available 200 ppm - TWA	Not available	Not available	Not available	Not available	
Aryl Halides	Not available Not available	Not available	Not available	Not available	Not available	

Appropriate engineering controls..... Local exhaust should be used to maintain levels below the exposure limits. Explosion-proof exhaust ventilation.

Personal Protective Equipment

- Respiratory/type..... Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Consult your personal protective equipment supplier for additional recommendations.
- Eye/type..... Chemical safety goggles and full faceshield if a splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.
- Gloves/ type..... Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Consult your personal protective equipment supplier for additional recommendations.
- Clothing/type..... Wear chemical resistant clothing. Consult your personal protective equipment supplier for additional recommendations.
- Footwear/type..... Wear chemical resistant safety boots. Consult your personal protective equipment supplier for additional recommendations.
- Other/type..... Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state.....	Liquid.
Colour.....	Colourless.
Odour.....	Aromatic odour.
Odour threshold (ppm).....	Not available.
pH.....	Not applicable.
Melting / Freezing point (deg C).....	Not available.
Initial boiling point / boiling range (deg C).....	Not available.
Flash point (deg C), method.....	4°C.
Evaporation rate.....	Not available.
Flammability (solids and gases).....	Not applicable. Flammable liquid.
Upper flammable limit (% vol).....	Not available.
Lower flammable limit (% vol).....	Not available.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	Not available.
Relative Density (Specific Gravity).....	1.344.
Solubility.....	Not available.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	Not available.
Decomposition temperature.....	Not available.
Viscosity.....	Not available.
% Volume Volatile exempt.....	50.12.
Formula LBS/GAL.....	11.22.
% Weight Solids.....	55.18.
% Volume Solids.....	35.82.
% Weight Volatile (VOC).....	8.81.
% Volume Volatile (VOC).....	44.44.
LBS VOC/GAL solids.....	2.8.
Total MIR.....	0.22.
Coverage (sq ft/gal @ 1 mil).....	575.
VOC LBS/GAL less exempt volatiles.....	1.98.
VOC LBS/GAL less water.....	0.99.
Percent weight binder.....	27.0.
Percent volume binder.....	16.6.
Percentage weight pigment.....	13.93.
Percentage volume pigment.....	5.69.
PVC Ratio.....	25.51.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Xylene will attack some forms of plastic, rubber and coatings. Avoid heat, sparks and flames.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Dangerous reactions possible on contact with incompatible substances. Vapours may form explosive mixture with air.
Conditions to avoid, including static discharge, shock or vibration	Electrostatic charge. Avoid excessive heat, open flames and all ignition systems.
Incompatible materials.....	Strong oxidizing agents. Strong acids. Strong bases. Amines. Plastics. Nitrates. Reducing agents.
Hazardous decomposition products.....	Carbon monoxide. Carbon dioxide. Acetic acid.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Talc	Not available	Not available
tert-Butyl acetate	>2,230 mg/m ³ 4 hours rat	4,100 mg/kg (rat, oral); >2,000 mg/kg (rabbit, dermal)
Diglycidyl ether of bisphenol A	Not Available	Not Available
Titanium Dioxide	>6.8 mg/L (4 hr)	>10,000 mg/kg (rat, oral) >10,000 mg/kg (rabbit, dermal)
4-Chlorobenzotrifluoride	4479 ppm	>6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal)
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Butyl Alcohol	8,000 ppm 4 hours	790 mg/kg rat oral 3,400 mg/kg rabbit dermal
Sepiolite Clay	Not available	Not available

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Distillates (petroleum), hydrotreated light	>3,000 mg/kg (dermal, rabbit)	>5,000 mg/kg (oral, rat)
Ethylbenzene	No data	3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal
Crystalline Silica	Not available	>22,500 mg/kg (oral rat)
2-Propanol, 1-methoxy-, acetate	Not Available	8,532 mg/kg rat oral 5,000 mg/kg dermal rabbit
Solvent Naphtha, Light Aromatics	5.2 mg/L 4 hours, rat 3400 ppm 4 hours, rat	>5,000 mg/kg (rat oral) >2,000 mg/kg (rabbit dermal)
Petroleum (highly purified)	Not available	Not available
Calcium carbonate	Not available	Not available
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	No data	No data
Carbon Black	Not available	>10,000 mg/kg (oral rat) 3,000 mg/kg (dermal rabbit)
Aluminum Hydroxide	Not Available	> 5000 mg/kg rat oral
Silica, Amorphous	Not Available	3160 mg/kg rat oral
Acetate Ester	Inhalation >16000 ppm (Rat)	Oral >5000 mg/kg (Rat) Dermal >5000 mg/kg (Rabbit)
Aryl Halides	Inhalation 33 mg/L/4h (Rat)	Oral >13000 mg/kg (Rat) Dermal >2000 mg/kg (Rabbit)

Route of exposure..... Eye contact. Skin contact. Inhalation. Ingestion.

Symptoms related to the physical, chemical and toxicological characteristics

Effects of acute exposure..... Causes serious eye irritation. Can cause redness and irritation. Can cause moderate skin irritation. May be harmful if absorbed through the skin. May cause central nervous system effects such as headache, nausea, vomiting and weakness. Talc can be absorbed into the lungs and the digestive tract, and adversely affect lung function.

Effects of chronic exposure..... Prolonged or repeated skin contact may cause drying or cracking of skin. Prolonged or repeated exposure may lead to allergic skin reactions. Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated breathing of talc may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. . Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Respiratory Sensitization..... Not expected to be a respiratory sensitizer.

Skin Sensitization..... May cause an allergic skin reaction.

Serious eye damage/eye irritation..... Causes serious eye burns and damage.

Carcinogenicity..... Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. Ethylbenzene is classified as an A3 known animal carcinogen. IARC has classified Titanium Dioxide as a "Group 2B"; possibly carcinogenic to humans. Xylene has been listed by IARC as a Group 3; not classifiable as to its carcinogenicity to humans. This product contains non-asbestiform Talc, which is classified as a Group 3 (not classifiable as to carcinogenicity to humans) by IARC .

Reproductive effects..... High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus.

STOT-SE..... May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-RE..... Respiratory system.

Aspiration Hazard..... May be fatal if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... Do not allow product to enter drains, sewers, bodies of water or soil.

Persistence and degradability..... Product data not available.

Bioaccumulative potential..... Product data not available.

Mobility in soil..... Product data not available.

Other adverse effects..... Not available.

PRODUCT: 13170 2K EPOXY PRIMER/SEALER (GRAY)**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Empty containers must be handled with care due to product residue.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
 DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (5 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... Calcium carbonate is considered a naturally occurring substance and is therefore exempt from listing on the DSL. The balance of the substances are on the DSL.
 New Substance Notification..... Some components of this product are subject to Schedule 8 of the New Substance Notification Regulations (Chemicals and Polymers). Please check to see if these Regulations will affect your company.. (CAS # 25036-25-3). (CAS # 63800-37-3).
 National Pollutant Release Inventory (NPRI)..... Some components are subject to reporting under NPRI. Please check your responsibility. (CAS # 71-36-3 (Cat 1A)). (CAS # 108-65-6 (CAT 5)). (CAS # 64742-95-6 (Cat 5)). (CAS # 64742-47-8 (CAT 5)). (CAS # 1330-20-7 (CAT 1A &5)). (CAS # 100-41-4 (CAT 1A)).
 Environmental Emergency Regulations.... Some components of this product are on the Environmental Emergency Regulations and may require additional reporting. Xylene (CAS # 1330-20-7) Part 1. Ethylbenzene (CAS # 100-41-4) Part 1.
 Categorization of the DSL..... Some components may have met the criteria under subsection 73(1) of CEPA during categorization of the DSL. Please check to see if this affects your company. (CAS # 71-36-3). (CAS # 14807-96-6). (CAS # 14808-60-7). (CAS # 108-65-6). (CAS # 64742-95-6). (CAS # 64742-47-8). (CAS # 8009-03-8). (CAS # 100-41-4). (CAS # 25036-25-3). (CAS # 61789-72-8). (CAS # 1333-86-4). (CAS # 13463-67-7). (CAS # 21645-51-2).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Butyl alcohol. Ethylbenzene. Xylene.
 EPA hazardous air pollutants (HAPS) Ethylbenzene. Toluene. Xylene.
 40CFR63
 California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause cancer. (Carbon black - airborne, unbound particles of respirable size). (Ethylbenzene (C)). (Silica, crystalline (airborne particles of respirable size(C))). (Titanium dioxide - airborne, unbound particles of respirable size). *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Toluene(D)).

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Date of the latest revision of the safety .. 2024-09-18
 data sheet