



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF

Recommended use and restrictions on .. Paints.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300. .

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Eye Irritant 2. Carcinogen 1A. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H350 This product contains ingredients that may cause cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P264 Wash thoroughly after handling. P260 Do not breathe mist, vapours, or spray. P270 Do not eat drink or smoke while using this product.

Response P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P308 + P313 If exposed or concerned, get medical advice/attention.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
tert-Butyl acetate	540-88-5	15-25
Methyl Isobutyl Ketone	108-10-1	10-20
Talc	14807-96-6	5-10
Titanium Dioxide	13463-67-7	5-10
Acetone	67-64-1	5-10
Toluene	108-88-3	2-4
N-Butyl Acetate	123-86-4	2-4
Ethanol	64-17-5	1-3

PRODUCT: 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

Isopropyl Alcohol	67-63-0	1-3
Phosphoric Acid	7664-38-2	<0.2
Crystalline Silica	14808-60-7	<0.2

SECTION 04: FIRST-AID MEASURES

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Consult a physician if irritation continues.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO ₂). Other potentially toxic fumes.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....	Evacuate all non-essential personnel. Avoid all personal contact. Ventilate. Eliminate all sources of ignition. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Contain the spill. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material.
-----------------	---

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. Prevent accumulation of electrostatic charges. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
tert-Butyl acetate	200 ppm	Not established	200 ppm	Not established	200 ppm	
Methyl Isobutyl Ketone	50 ppm	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm	
Talc	2 mg/m ³	Not established	2 mg/m ³ TWA	3 mg/m ³ - QUE	Not established	
Titanium Dioxide	10 mg/m ³	Not established	15 mg/m ³	Not established	Not established	

PRODUCT: 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Acetone	500 ppm	750 ppm	1,000 ppm	Not established		250 ppm
Toluene	20 ppm	Not established	200 ppm	500 ppm 10 minutes		100 ppm / STEL 150 ppm
N-Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm		150 ppm / STEL 200 ppm
Ethanol	1000 ppm	1000 ppm	1000 ppm	Not established		1000 ppm
Isopropyl Alcohol	200 ppm	400 ppm	400 ppm (TWA)	500 ppm		400 ppm
Phosphoric Acid	1 mg/m ³	3 mg/m ³	1 mg/m ³	3 mg/m ³		1 mg/m ³
Crystalline Silica	0.025 mg/m ³	Not established	0.1 mg/m ³ TWA	Not established		0.05 mg/m ³
Personal protective equipment						
Eye/type.....	Liquid chemical goggles.					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Gloves/ type.....	Chemical resistant gloves. Butyl rubber. Nitrile rubber.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available.					
Appropriate engineering controls.....	Local exhaust at points of emission. Ventilation system must be designed vapor and explosion proof for handling solvent vapors.					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	No data.
Odour.....	No data.
Odour threshold (ppm).....	No data.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	No data.
pH.....	No data.
Relative Density (Specific Gravity).....	9.23 lb/usg - 1.196.
Melting / Freezing point (deg C).....	Not Available.
Solubility.....	No data.
Initial boiling point / boiling range (deg C).....	> 56 C.
Evaporation rate.....	Not available.
Flash point (deg C), method.....	-18°C. (estimated).
Auto ignition temperature (deg C).....	> 400°C.
Upper flammable limit (% vol).....	12.0.
Lower flammable limit (% vol).....	1.2.
Coefficient of water/oil distribution.....	Not available.
% Volatile by volume.....	Not available.
VOC.....	2.0 lbs/gal - 243.3 g/l.
Decomposition temperature.....	Not available.
Viscosity.....	5250 cPs. #4 @ 20 RPM.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames.
Conditions to avoid, including static	Keep away from heat. Incompatible with strong oxidizers. Alkali and reducing materials.
discharge, shock or vibration	Acids. Nitrates.
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO ₂).
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
tert-Butyl acetate	>2,230 mg/m ³ 4 hours rat	4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal
Methyl Isobutyl Ketone	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal

PRODUCT: 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Talc	Not available	Not available
Titanium Dioxide	Not Available	> 10,000 mg/kg rat oral > 10,000 mg/kg rabbit dermal
Acetone	50,100 mg/m3 8 hours rat inhalation	5,800 mg/kg rat oral
Toluene	8000 ppm rat inhalation 400 ppm mouse inhalation 24hr	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
N-Butyl Acetate	>29.2 mg/L 4 hour rat >23.4 mg/L aerosol 4 hour rat	>3200 mg/kg rat oral >5000 mg/kg rabbit dermal
Ethanol	20000 ppm/ 10 hour rat	10,600 mg/kg rat oral
Isopropyl Alcohol	16,000 ppm 8 hours rat	5,000 mg/kg rat oral. 12,800 mg/kg rabbit dermal
Phosphoric Acid	1.689 mg/L 1 hour rabbit	1,530 mg/kg rat oral 2,740 mg/kg rabbit dermal
Crystalline Silica	Not available	>22,500 mg/kg oral rat
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Ingestion.....	May be harmful or fatal if swallowed. Swallowing causes inebriation, headache, vomiting, leading to severe illness, blindness, even death. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Carcinogenicity of material.....	Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B). IARC has classified Titanium Dioxide as a group 2B carcinogen. Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. .	
Reproductive effects.....	Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Do not allow to enter waters, waste water or soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
 DOT Classification (Road)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II.
 IMDG Classification (Marine)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

PRODUCT: 13214 HIGH BUILD NITROCELLULOSE PRIMER BUFF**SECTION 15: REGULATORY INFORMATION**

CEPA status.....	Not determined.
TSCA inventory status.....	Not determined.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	Isopropyl alcohol. Methyl Isobutyl Ketone. Toluene. Zinc compounds.
EPA hazardous air pollutants (HAPS) 40CFR63	Methyl Isobutyl Ketone. Toluene.
California Proposition 65.....	*WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Methyl Isobutyl Ketone (D)). (Toluene). *WARNING: This product contains a chemical known to the State of California to cause cancer. (Carbon black - airborne, unbound particles of respirable size). (Silica, crystalline (airborne particles of respirable size). (Methyl Isobutyl Ketone (C)). (Nickel compounds). (Titanium dioxide - airborne, unbound particles of respirable size).

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Date of the latest revision of the safety data sheet ..	JUL 06/2017