



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

**PRODUCT: 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER
RED**

SECTION 01: Chemical product and company identification

Manufactured for..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product name..... 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER RED

Recommended use and restrictions on .. Paints.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300. .

SECTION 02: Hazards identification



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Irritant 2. Eye Irritation — Category 2A. Carcinogenicity — Category 1. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H351 This product contains ingredients that are suspected of causing cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P308 + P313 If exposed or concerned, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P314 - Get medical advice/attention if you feel unwell.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: Composition/Information on Ingredients

HAZARDOUS INGREDIENTS	CAS #	WT. %
tert-Butyl acetate	540-88-5	10-30
Talc	14807-96-6	10-30
Methyl Isobutyl Ketone	108-10-1	7-15

**PRODUCT: 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER
RED**

SECTION 03: Composition/Information on Ingredients

Acetone	67-64-1	5-10
Ethanol	64-17-5	1-5
Butyl Acetate	123-86-4	1-5
Toluene	108-88-3	1-5
Isopropyl Alcohol	67-63-0	0.5-1.5
Crystalline Silica	14808-60-7	0.1-1
Phosphoric Acid	7664-38-2	0.1-1

<<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: First aid measures

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. This product contains ingredients that are suspected of damaging fertility or the unborn child. This product contains ingredients that may cause cancer. Causes damage to organs through prolonged or repeated exposure.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis.

SECTION 05: Fire fighting measures

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.
Hazardous combustion products.....	Oxides of carbon (CO, CO ₂). Aldehydes. Hydrocarbon fumes and smoke.
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours.

SECTION 06: Accidental release measures

Leak/spill.....	Keep away from heat, sparks and flames. Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Use non-sparking tools and equipment to pick up the spilled material. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
-----------------	--

SECTION 07: Handling and storage

Handling procedures.....	Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

**PRODUCT: 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER
RED****SECTION 08: Exposure controls / personal protection**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
tert-Butyl acetate	200 ppm	Not established	200 ppm	Not established	200 ppm
Talc	2 mg/m3	Not established	2 mg/m3 TWA	3 mg/m3 - QUE	Not established
Methyl Isobutyl Ketone	50 ppm	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm
Acetone	500 ppm	750 ppm	1,000 ppm	Not established	250 ppm
Ethanol	1000 ppm	1000 ppm	1000 ppm	Not established	1000 ppm
Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm vacated	150 ppm - STEL 200 ppm
Toluene	20 ppm	Not established	200 ppm	500 ppm 10 minutes	100 ppm / STEL 150 ppm
Isopropyl Alcohol	200 ppm	400 ppm	400 ppm (TWA)	500 ppm	400 ppm
Crystalline Silica	0.025 mg/m3	Not established	0.1 mg/m3 TWA	Not established	0.05 mg/m3
Phosphoric Acid	1 mg/m3	3 mg/m3	1 mg/m3	3 mg/m3	1 mg/m3
Protective equipment					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.				
Gloves/ type.....	Chemical resistant gloves.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.				
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .				

SECTION 09: Physical and chemical properties

Physical state.....	Liquid.
Colour.....	Red.
Odour.....	Sweet odour. Acetate.
Odour threshold (ppm).....	Not available.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	Not available.
pH.....	Not available.
Density.....	9.51 lbs/USG; 1.139.
Melting / Freezing point (deg C).....	Not Available.
Solubility.....	Not soluble in water.
Initial boiling point / boiling range (deg C).....	98°C .
Evaporation rate.....	Not available.
Flash point (deg C), method.....	4.4. (estimate; lowest flash point ingredient).
Auto ignition temperature (deg C).....	> 300.
Upper flammable limit (% vol).....	10.5.
Lower flammable limit (% vol).....	0.9.
Coefficient of water/oil distribution.....	Not available.
% Volatile by volume.....	80.95.
VOC.....	1.69 lb/usg - 202.51 g/L.
Viscosity.....	34 sec Zahn #2.

SECTION 10: Stability and reactivity

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid.....	Keep away from heat. Incompatible with strong oxidizers. Alkalis. Acids. Nitrates. Avoid plastics.

**PRODUCT: 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER
RED****SECTION 10: Stability and reactivity**

Hazardous decomposition products..... By fire: Dense black smoke. Oxides of carbon (CO,CO2). Under hot acidic conditions: Isobutylene and acetic acid.

SECTION 11: Toxicological information

INGREDIENTS	LC50	LD50
tert-Butyl acetate	>2,230 mg/m ³ 4 hours rat	4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal
Talc	Not available	Not available
Methyl Isobutyl Ketone	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal
Acetone	50,100 mg/m ³ 8 hours rat inhalation	5,800 mg/kg rat oral
Ethanol	20000 ppm/ 10 hour rat	10,600 mg/kg rat oral
Butyl Acetate	2000 ppm 4 hours rat	10768 mg/kg oral rat 17600 mg/kg dermal rabbit
Toluene	8000 ppm rat inhalation 400 ppm mouse inhalation 24hr	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
Isopropyl Alcohol	16,000 ppm 8 hours rat	5,000 mg/kg rat oral. 12,800 mg/kg rabbit dermal
Crystalline Silica	Not available	>22,500 mg/kg oral rat
Phosphoric Acid	1.689 mg/L 1 hour rabbit	1,530 mg/kg rat oral 2,740 mg/kg rabbit dermal

Route of exposure..... Eye contact. Skin contact. Inhalation.
 Effects of chronic exposure..... Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .
 Skin contact..... Can cause moderate irritation, defatting and dermatitis.
 Skin absorption..... May be harmful if absorbed through the skin.
 Eye contact..... Can cause redness, irritation, tissue destruction.
 Inhalation (acute)..... Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.
 Inhalation (chronic)..... Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.
 Ingestion..... May be harmful or fatal if swallowed. Swallowing causes inebriation, headache, vomiting, leading to severe illness, blindness, even death. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.
 Carcinogenicity of material..... Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. . Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B).
 Reproductive effects..... Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects.
 Specific Target Organ Toxicity Causes damage to organs through prolonged or repeated exposure .

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

SECTION 13: Disposal considerations

Waste disposal..... Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

**PRODUCT: 13216 HIGH BUILD FAST DRY NITROCELLULOSE LACQUER PRIMER
RED**

SECTION 14: Transport information

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
 DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1263 - PAINT- Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Isopropyl alcohol. Methyl Isobutyl Ketone. Toluene.
 EPA hazardous air pollutants (HAPS) Methyl Isobutyl Ketone. Toluene.
 40CFR63
 California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Toluene). (Methyl Isobutyl Ketone (D)). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Cobalt compounds). (Crystalline silica). (Methyl Isobutyl Ketone (C)). (Nickel compounds). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: MAY 03/2018