

Super Kick Accelerator is an accelerator designed for acrylic urethane and polyurethane clears, paints and polyurethane (catalyzed) primers. It will help paint systems tack and cure quickly and reduces sand and buff times.

PRODUCT**SIZE****13350**

U.S. Pint (473 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

RECOMMENDED FOR:

- Acrylic urethane and polyurethane clears
- Paints and polyurethane (catalyzed) primers

ADVANTAGES

- High strength
- Reduce sand and buff times
- Finishes become durable much faster
- Better color holdout and sealing properties

DIRECTIONS FOR USE:

Use up to 1 fl oz (29.5 mL) of 13350 Super Kick Accelerator per 8 fl oz (236 mL) of primer, paint or clear.

Caution: Do not use in epoxy primers or non-catalyzed paints, clears or primers.

Clean all spray equipment immediately after use as activated paints will harden in equipment.

Caution: It is important to test the compatibility of this product with your paint system.

TECHNICAL DATA:

	13350
Physical State	Liquid
Color:	Clear, colourless
Odour:	Pungent, characteristic odour
Solubility :	No data
Flash point:	-18°C (-0.40°F)(estimate; lowest flash point ingredient)
Auto ignition temperature:	>230°C (>446°F)
VOC	0.0 g/L - 0.0 lb/usg.

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.