



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK -- LOW COST
HIGH VOC

Recommended use and restrictions on .. Paints. No restrictions on use known.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Carcinogenicity — Category 1. Serious Eye Damage — Category 1. Skin Corrosion — Category 1. Corrosive to metals 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Reproductive Toxicity — Category 2. Acute Toxicity (Dermal) — Category 3. Acute Toxicity (Inhalation) — Category 3. Acute Toxicity (Oral) — Category 4. Germ Cell Mutagenicity 2. Specific Target Organ Toxicity — Single Exposure — Category 3. (respiratory system). (narcotic effects). Specific Target Organ Toxicity — Repeated Exposure — Category 2. (liver, kidney, central nervous system). (Auditory system). (eyes). Aquatic Acute 1. Aquatic Chronic 1.

Signal Word..... DANGER.

Hazard Description..... H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H350 This product contains ingredients that may cause cancer. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves and eye protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P301 + P312 If swallowed call a poison control centre. P301 + P330 + P331 If Swallowed: Rinse mouth. Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes.

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 02: HAZARD IDENTIFICATION

| | |
|--------------------|--|
| Response | Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P308 + P313 If exposed or concerned, get medical advice/attention. P310 - Immediately call your local poison control centre. P311 Call a POISON CENTRE or doctor. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P330 Rinse mouth. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye irritation persists get medical attention. P361 + P364 Take off immediately all contaminated clothing and wash it before reuse. P362 + P364 - Take off contaminated clothing and wash before reuse. P363 - Wash contaminated clothing before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P391 Collect spillage. |
| Storage..... | P403 + P233 Store in a well ventilated area. Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up. |
| Disposal..... | P501 Dispose all unused, waste or empty containers in accordance with local regulations. |
| Other hazards..... | None known. |

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|---------|
| Talc | 14807-96-6 | 10-30 |
| Crystalline Silica | 14808-60-7 | 0.1-1 |
| Xylene | 1330-20-7 | 10-30 |
| Calcium Carbonate | 1317-65-3 | 10-30 |
| Butyl Acetate | 123-86-4 | 5-10 |
| Toluene | 108-88-3 | 5-10 |
| Ethylbenzene | 100-41-4 | 3-10 |
| Methyl N-Amyl Ketone | 110-43-0 | 1-5 |
| Methyl isobutyl ketone | 108-10-1 | 1-5 |
| Carbon Black | 1333-86-4 | 1-5 |
| Calcium borate | 13701-64-9 | 0.1-1 |
| Castor oil, sulfated, sodium | 68187-76-8 | 0.1-1 |
| Cumene | 98-82-8 | 0.1-1 |
| Distillates (Petroleum) Hydrotreated Light | 64742-47-8 | 0.1-1 |
| Petroleum (highly purified) | 8009-03-8 | 0.1-1 |
| Dibutyltin Bis (Acetylacetonate) | 22673-19-4 | 0.1-1 |
| 2,4-Pentanedione | 123-54-6 | 0.1-1.0 |
| Phosphoric Acid | 7664-38-2 | 0.1-1 |
| Calcium carbonate | 471-34-1 | 0.1-1 |

<<The actual concentration(s) withheld as a trade secret>> .

Ethyl Benzene & Cumene are in the product which present a health or environmental hazard. *NOTE*

SECTION 04: FIRST-AID MEASURES

| | |
|--|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin contact..... | Wash using plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. Drink plenty of water. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Difficulty breathing. May cause an allergic skin reaction. Dermatitis. Rash. Causes eye irritation. |
| Additional information..... | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 05: FIRE-FIGHTING MEASURES

Suitable extinguishing media..... Alcohol resistant foam. Carbon dioxide. Dry chemical. Water spray.
 Unsuitable extinguishing media..... Do not use solid water streams or water jet.
 Specific hazards arising from the Do not allow run-off from fire fighting to enter drains or water courses. Vapors may form hazardous product, such as the nature of explosive mixture in air. May produce hazardous fumes. Hazardous products may include any hazardous combustion products but not limited to: Oxides of carbon (CO, CO2). Unburned hydrocarbons. Silicon oxide. Metal oxides. Sulfur Oxides. Oxides of calcium. Oxides of boron. Oxides of phosphorous. Toxic fumes. Silica fumes.

Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Use water spray to cool containers. Dispose of all runoff water as hazardous waste.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective Avoid breathing vapours. Avoid skin and eye contact with vapors. Ensure adequate equipment and emergency procedures ventilation. Remove all sources of ignition. Ventilate area. Vapours can accumulate in low areas. Vapors can form explosive mixture in air. Do not touch spilled material.

Environmental precautions..... Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.

Methods and materials for containment Dike area to contain the spill, prevent runoff from going into drains, absorb residual and cleaning up material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste. Soak up with inert material. Keep in suitable container for disposal. Clean up any residual material with absorbent and dispose of as hazardous waste.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Use non sparking tools. Electrostatic charges may be generated during pumping. Ensure that equipment is properly bonded and grounded during filling and transferring as product may become electrostatically charged. Avoid all skin contact. Handle with care. Avoid breathing vapours or mist. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Employees should wash hands and face before eating or drinking. Avoid smoking, drinking or eating in use area. Dispose of rinse water according to local, Provincial and Federal guidelines. Handle in accordance with good industrial hygiene and safety practices.

Conditions for safe storage, including any Keep away from heat, sparks, and open flames. Keep container closed when not in use. incompatibilities Store away from incompatible materials. Store away from sunlight. Store at ambient temperatures.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|--------------------|---|----------------|---------------|--------------------|------------------------|-------|
| Talc | 2 mg/m3 CA ON: 2mg/kg (TWA) | Not available | 2 mg/m3 TWA | Not available | 2 mg/m3 | |
| Crystalline Silica | 0.025 mg/m3 CA ON: 0.025 mg/m3 Respirable | Not available | 0.1 mg/m3 TWA | Not available | 0.05 mg/m3 | |
| Xylene | 50 ppm CA ON: 100ppm (TWA); 150ppm (STEL) | 150 ppm | 100 ppm TWA | Not available | Not available | |
| Calcium Carbonate | Not available Not available | Not available | 5 mg/m3 | Not available | 5 mg/m3 | |
| Butyl Acetate | 150 ppm CA ON: 50ppm (TWA), 150 ppm (STEL) | 200 ppm | 150 ppm | 200 ppm vacated | 150 ppm - STEL 200 ppm | |
| Toluene | 20 ppm CA ON: TWA: 20 ppm | Not available | 200 ppm | 500 ppm 10 minutes | 100 ppm / STEL 150 ppm | |
| Ethylbenzene | 100 ppm | 125 ppm | 100 ppm | Not established | 100 ppm / STEL 125 ppm | |

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | ACGIH TLV | | PEL | OSHA PEL | | NIOSH |
|--|---|-----------------|--|--|--|---------------|
| | TWA | STEL | | STEL | REL | |
| Methyl N-Amyl Ketone | CA ON: 20ppm (TWA) 50 ppm | Not available | 100 ppm | 465 mg/m3 TWA | Not available | |
| Methyl isobutyl ketone | CA ON: 25 ppm; 115 mg/m3 (TWA) Not available | Not available | Not available | Not available | Not available | Not available |
| Carbon Black | 3 mg/m3 | Not established | 3.5 mg/m3 | Not established | 3.5 mg/m3 | |
| Calcium borate | CA ON: 3 mg/m3 (Inhalable) TWA Not available | Not available | TLV inhalable dust: 15 mg/m ³ OSHA | TLV respirable dust: 5 mg/m ³ OSHA | Not available | |
| Castor oil, sulfated, sodium | Not available | Not available | Not available | Not available | Not available | |
| Cumene | Not available TWA 50 ppm | Not available | TWA 50 ppm | Not available | TWA 50 ppm | |
| Distillates (Petroleum) Hydrotreated Light | 5 mg/m3 1200 mg/m3 | 197 ppm | Not available | Not available | Not available | |
| Petroleum (highly purified) | CA BC: 200mg/m3 (TWA) Skin Not available | Not available | Not available | Not available | Not available | |
| Dibutyltin Bis (Acetylacetonate) | Not available | Not available | Not available | Not available | Not available | |
| 2,4-Pentanedione | Not available | Not available | Not available | Not available | Not available | |
| Phosphoric Acid | Not available 1 mg/m3 | 3 mg/m3 | 1 mg/m3 | 3 mg/m3 | 1 mg/m3 | |
| Calcium carbonate | CA ON: 1 mg/m3(TWA), 3 mg/m3(STEL) Not available | Not available | Not available | Not available | TWA (respirable) 5 mg/m3 TWA (total) 10 mg/m3 | |

Appropriate engineering controls..... Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.

Personal Protective Equipment

Eye/type..... Chemical safety goggles and full faceshield if a splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.

Gloves/ type..... Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. Consult your personal protective equipment supplier for additional recommendations.

Clothing/type..... Wear adequate protective clothes. Consult your personal protective equipment supplier for additional recommendations.

Footwear/type..... Safety boots per local regulations. Consult your personal protective equipment supplier for additional recommendations.

Respiratory/type..... Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Consult your personal protective equipment supplier for additional recommendations.

Other/type..... Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-----------------|
| Appearance/Physical state..... | Liquid. |
| Colour..... | Not available. |
| Odour..... | Not available. |
| Odour threshold (ppm)..... | Not available. |
| pH..... | Not available. |
| Melting / Freezing point (deg C)..... | Not available. |
| Initial boiling point / boiling range (deg C). | Not available. |
| Flash point (deg C), method..... | Not available. |
| Evaporation rate..... | Not available. |
| Flammability (solids and gases)..... | Not applicable. |
| Upper flammable limit (% vol)..... | Not available. |
| Lower flammable limit (% vol)..... | Not available. |
| Vapour pressure (mm Hg)..... | Not available. |
| Vapour density (air=1)..... | Not available. |
| Relative Density (Specific Gravity)..... | 1.326. |
| Pounds / USG..... | 11.06. lbs/GAL. |
| Solubility..... | Not available. |
| Partition coefficient — n-octanol/water..... | Not available. |
| Auto ignition temperature (deg C)..... | Not available. |
| Decomposition temperature..... | Not available. |
| Viscosity..... | Not available. |
| % Volatile by volume..... | 57.92. |
| % Weight Volatile (VOC)..... | 37.34. |
| % Volume Volatile exempt..... | 0.00. |
| VOC LBS/GAL less water..... | 4.13. |
| LBS VOC/GAL solids..... | 9.8. |
| VOC LBS/GAL less exempt volatiles..... | 4.13. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | Not reactive under normal conditions of use. |
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Possibility of hazardous reactions..... | No dangerous reaction known under conditions of normal use. . |
| Incompatible materials..... | Strong oxidizing agents. Aldehydes. Amines. Bases. Halogenated compounds. Metals. Nitrogen oxides. Oxidizing agents. Peroxides. Strong acids. Ammonia. Water. Cyanides . Hydrogen peroxide. |
| Conditions to avoid, including static | Avoid heat, spark, open flames. Contact with incompatible substances. |
| discharge, shock or vibration | |
| Hazardous decomposition products..... | Calcium oxides. Carbon dioxide. Carbon monoxide. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|------------------------------|--|--|
| Talc | Not available | Not available |
| Crystalline Silica | Not available | >22,500 mg/kg (oral rat) |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Calcium Carbonate | Not available | 6450 mg/kg rat oral |
| Butyl Acetate | 390 ppm (4 hr) | 10768 mg/kg oral rat 17600 mg/kg dermal rabbit |
| Toluene | 8000ppm (rat inhalation) 400ppm mouse (inhalation 24hr) | 5,000 mg/kg (rat ora); 12,124 mg/kg (rabbit dermal) |
| Ethylbenzene | No data | 3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal |
| Methyl N-Amyl Ketone | Not available | 1,670 mg/kg rat oral 12,600 mg/kg rabbit dermal |
| Methyl isobutyl ketone | LC50 (Rat): 11.6 mg/l - 4 hr. | Not available |
| Carbon Black | Not available | >10,000 mg/kg (oral rat) 3,000 mg/kg (dermal rabbit) |
| Calcium borate | Not available | Oral > 5000 mg/kg (rabbit) Dermal > 2000 mg/kg (rabbit) |
| Castor oil, sulfated, sodium | Not available | > 15,600 mg/kg orally (rat) > 2000 mg/kg dermal (rat) |

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC**

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|---|--|
| Cumene | Not available | Not available |
| Distillates (Petroleum) Hydrotreated Light | >5.2 mg/L (4 hr.) | >5000 mg/kg (oral, rat), >2000 mg/kg (dermal, rabbit) |
| Petroleum (highly purified) | Not available | Not available |
| Dibutyltin Bis (Acetylacetonate) | Not available | 1864 mg/kg (oral, rat) |
| 2,4-Pentanedione | 1224 ppm (4 hr., rat). 5.1 mg/L (4 hr., rat) | 573 mg/kg (rat oral). 790 mg/kg (rabbit dermal) |
| Phosphoric Acid | 1.689 mg/L 1 hour rabbit | 1,530 mg/kg rat oral 2,740 mg/kg rabbit dermal |
| Calcium carbonate | Not available | Not available |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful in contact with skin. May cause an allergic skin reaction. Contact with eyes may cause irritation. Harmful if swallowed. | |
| Effects of chronic exposure..... | Prolonged inhalation may be harmful. . | |
| Aspiration Hazard..... | May be fatal if aspired into the airways. | |
| Serious eye damage/eye irritation..... | Irritating to the eyes. | |
| Skin corrosion/irritation..... | Causes skin irritation. | |
| Respiratory or Skin Sensitization..... | Not classified. | |
| Carcinogenicity..... | Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by the International Agency for Research on Cancer (IARC). . | |
| Reproductive effects..... | Suspected of damaging fertility or the unborn child. | |
| Mutagenicity..... | Not available. | |
| STOT-SE..... | Central nervous system. Certain components are known to have narcotic effects. Certain components are known to cause respiratory damage. | |
| STOT-RE..... | Target organs: Kidney. Liver. Central nervous system. Auditory system. Eyes. | |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|---|
| Ecotoxicity..... | Very toxic to aquatic life with long lasting effects. |
| Bioaccumulative potential..... | Not available as a product. |
| Mobility in soil..... | Not available as a product. |
| Persistence and degradability..... | Not available as a product. |
| Other adverse effects..... | None known. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. |
|---|---|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| UN number..... | UN1263. |
| Shipping name..... | Paint Related Material. |
| Class..... | 3. |
| Packaging group..... | II. |
| Exemptions..... | This product meets the Limited Quantity exemption when packaged in containers less than 5 liters. |
| DOT Classification (Road)..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements. |
| IATA Classification (Air)..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations. |
| IMDG Classification (Marine)..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions. |
| Marine Pollutant..... | Potential marine pollutant. |
| Proof of Classification..... | This product has been classified in accordance with DOT and Canada's Part 2 of the Transportation of Dangerous Goods regulations. |

**PRODUCT: PRODUCTION PRIMER 2K URETHANE PRIMER SURFACER BLACK --
LOW COST HIGH VOC****SECTION 15: REGULATORY INFORMATION**

| | |
|--|---|
| CEPA status..... | All substances are on the DSL or are exempt. |
| Categorization of the DSL..... | Some components met the criteria under subsection 73(1) of CEPA during categorization of the DSL. Please check to see if this affects your company. (CAS # 100-41-4). (CAS # 98-82-8). (CAS # 108-10-1). (CAS # 64742-47-8). (CAS # 8009-03-8). (CAS # 7664-38-2). (CAS # 14807-96-6). (CAS # 14808-60-7). (CAS # 1333-86-4). (CAS # 108-88-3). |
| National Pollutant Release Inventory (NPRI) | Some components are subject to reporting under NPRI. Please check your responsibility. (CAS # 1330-20-7 (CAT 1A &5)). (CAS # 100-41-4 (CAT 1A)). (CAS # 98-82-8 (CAT 1A)). (CAS # 108-10-1 (CAT 1A & 5)). (CAS # 64742-47-8 (CAT 5)). (CAS # 108-88-3 (CAT 1A &5)). |
| Environmental Emergency Regulations.... | Some components of this product are on the Environmental Emergency Regulations and may require additional reporting. (CAS # 1330-20-7). (CAS # 100-41-4). (CAS # 108-88-3). |
| TSCA inventory status..... | All components are either listed or exempt from the TSCA. . |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health, fire hazard. |
| Section 313..... | Cumene. Ethylbenzene. Xylene. Methyl Isobutyl Ketone. Phosphoric Acid. Toluene. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | Cumene. Ethylbenzene. Xylene. Toluene. Methyl Isobutyl Ketone. |
| California Proposition 65..... | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Cumene (C)). (Ethylbenzene (C)). (Methyl Isobutyl Ketone (C)). (Carbon black (C)). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Methyl Isobutyl Ketone (D)). (Toluene(D)). For more information, go to www.P65Warnings.ca.gov . |

SECTION 16: OTHER INFORMATION

| | |
|---|---|
| Prepared by: | REGULATORY AFFAIRS. |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:..... | 2022-11-30. |
| Date of the latest revision of the safety .. data sheet | 2023-09-15 |