



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 13544 URETHANE GRADE REDUCER SLOW 5 GAL

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 13544 URETHANE GRADE REDUCER SLOW 5 GAL

Recommended use and restrictions on .. Paint reducer.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritant 2. Specific Target Organ Toxicity — Single Exposure — Category 3. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys through prolonged or repeated contact.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P264 Wash thoroughly after handling. P260 Do not breathe the mist, vapours, or spray. P271 Use only outdoors or in a well ventilated area.

Response P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P308 + P313 If exposed or concerned, get medical advice/attention. P321 - For specific treatment see section 4 on this SDS.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up. P233 Keep container tightly closed.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

PRODUCT: 13544 URETHANE GRADE REDUCER SLOW 5 GAL**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
2-Propanol, 1-methoxy-, acetate	108-65-6	35-40
Solvent naphtha (petroleum), light aliph. (VM&P Naphtha)	64742-89-8	25-30
Toluene	108-88-3	20-30
Methyl Ethyl Ketone	78-93-3	7-13

SECTION 04: FIRST-AID MEASURES

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Consult a physician if irritations continues.
Skin contact.....	Immediately remove all contaminated clothing, flush skin with water for at least 15 minutes. Wash clothing before reuse. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Rinse mouth with water. Give 1 to 2 glasses of water to drink. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Get medical attention.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	Carbon dioxide, dry chemical, foam. In cases of larger fires, water spray should be used. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO ₂). Other potentially toxic fumes.
Special protective equipment and precautions for fire-fighters	Firefighters should be equipped with a breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours.
Unusual fire / explosion hazards.....	Forms peroxides of unknown stability.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....	Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Eliminate all sources of ignition. Dike area to prevent spreading. Stop leak if safe to do so. Absorb with earth, sand, or another dry inert material. Collect and contain in suitable containers. Wash area with soapy water and rinse. Collect wash water for approved disposal. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial/State, and federal regulations.
-----------------	---

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Avoid skin and eye contact. Avoid breathing vapours or mist. Keep away from heat, sparks, and open flame. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static, which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Handle and open container with care. Keep container closed when not in use. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Store containers in a cool, dry and well ventilated area, out of sunlight and away from fire hazards. Keep container closed when not in use.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
2-Propanol, 1-methoxy-, acetate	50 ppm	75 ppm	Not established	Not established	Not established	Not established

PRODUCT: 13544 URETHANE GRADE REDUCER SLOW 5 GAL**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Solvent naphtha (petroleum), light aliph. (VM&P Naphtha)	100 ppm	300 ppm	100 ppm	Not established		Not established
Toluene	20 ppm	Not established	200 ppm	500 ppm 10 minutes	100 ppm / STEL 150 ppm	
Methyl Ethyl Ketone	200 ppm	300 ppm	200 ppm	Not established	200 ppm TWA	
	CA ON: TWA: 20 ppm					
	CA ON: 200ppm (TWA), 300ppm (STEL)					
Personal Protective Equipment						
Respiratory/type.....		Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Be sure to use a NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator.				
Eye/type.....		Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists.				
Gloves/ type.....		Chemical resistant gloves. Avoid prolonged contact with natural, butyl or nitrile rubber gloves.				
Clothing/type.....		Wear adequate protective clothes.				
Footwear/type.....		Safety boots per local regulations.				
Other/type.....		Eye wash facility and emergency shower should be in close proximity.				
Appropriate engineering controls.....		Use local exhaust or general room ventilation sufficient to prevent overexposure. Thermal processing equipment should be ventilated to control gases and fumes given off during processing. Ventilation system must be designed vapor and explosion proof for handling solvent vapors.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	Clear, colourless.
Odour.....	Solvent odour.
Odour threshold (ppm).....	Not available.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	>1.
pH.....	No data.
Relative Density (Specific Gravity).....	7.14 lb/usg - 0.857.
Melting / Freezing point (deg C).....	Not available.
Solubility.....	No data.
Initial boiling point / boiling range (deg C).....	79.6.
Evaporation rate.....	Not available.
Flash point (deg C), method.....	-9 °C. (estimated).
Auto ignition temperature (deg C).....	320°C.
Upper flammable limit (% vol).....	11.5.
Lower flammable limit (% vol).....	0.9.
Partition coefficient — n-octanol/water.....	Not available.
% Volatile by volume.....	100.
VOC (less water).....	7.14 lb/usg - 855.56 g/L.
Viscosity.....	Not available.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid open flames, sparks, heat, electrical and static discharge, storage at high temperatures. A component in this product can form peroxides of unknown stability.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static discharge, shock or vibration	Oxidizing agents. Acids. Amines. Ammonia. Nitric acid. Metals. Alkalis. Copper.
Hazardous decomposition products.....	Chloroform. Hydrogen peroxide.
	See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
2-Propanol, 1-methoxy-, acetate	Not Available	8,532 mg/kg rat oral 5,000 mg/kg dermal rabbit

PRODUCT: 13544 URETHANE GRADE REDUCER SLOW 5 GAL**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Solvent naphtha (petroleum), light aliph. (VM&P Naphtha)	3400 ppm 4hr Rat	>2000 mg/kg Oral Rat >2000 mg/kg Dermal Rat
Toluene	8000ppm rat inhalation 400ppm mouse inhalation 24hr	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
Methyl Ethyl Ketone	>5,000 ppm (6 hours, rat), 11000 ppm (45 minutes, mouse)	3,400 mg/kg (rat, oral), >8000 mg/kg (rabbit, dermal), 670 mg/kg (mouse, oral)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Irritating to eyes, skin and respiratory system. Ingestion may cause adverse health effects. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. May cause central nervous system effects such as headache, nausea, vomiting and weakness.	
Effects of chronic exposure.....	Prolonged or repeated skin contact may cause drying or cracking of skin. Reports have associated repeated or prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material.....	IARC has classified Toluene as a Group 3 (Not classifiable as to its carcinogenicity to humans); ACGIH has classified Toluene as a Group A4 (Not classifiable as a human carcinogen).	
Reproductive effects.....	Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. In one study, Methyl Ethyl Ketone has been found to cause embryol toxicity in large concentrations.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Do not allow to enter waters, waste water or soil.
Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
DOT Classification (Road)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
IATA Classification (Air)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II.
IMDG Classification (Marine)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E.
Marine Pollutant..... No.
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

WHMIS 1988 classification..... B2, D2B, D2A.
CEPA status..... On Domestic Substances List (DSL).
TSCA inventory status..... All components are listed.
OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III
Section 302 - extremely hazardous substances None.
Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
Section 313..... Toluene. Methyl Ethyl Ketone.
EPA hazardous air pollutants (HAPS) Toluene.
40CFR63
California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Toluene).

PRODUCT: 13544 URETHANE GRADE REDUCER SLOW 5 GAL**SECTION 16: OTHER INFORMATION**

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from
experience and recognized technical sources. To the best of our knowledge, it is believed
to be correct as of the date of issue but we make no representations as to its accuracy or
sufficiency and do not suggest or guarantee that any hazards listed herein are the only
ones which exist. The hazard information contained herein is offered solely for the
consideration of the user, subject to his own investigation and verification of compliance
with applicable regulations, including the safe use of the product under every foreseeable
condition. The information relates only to the product designated herein, and does not
relate to its use in combination with any other material or in any other process.

Review Date:..... 2021-11-15.
Date of the latest revision of the safety .. 2017-08-30
data sheet