

An anti-corrosive coating that has excellent adhesion and flexibility. Applied on steel or galvanized metal, it stops rust by an electro-chemical action even in highly corrosive environments. Prevents rust creepage in the area of scratches unlike conventional primers. Apply to ferrous metals prior to welding to prevent corrosion and rust. May be applied after the weld for additional protection.

PRODUCT	SIZE
13804	13 oz (368 g) Aerosol

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Steel metal
- Galvanized metal

ADVANTAGES:

- Improves conductivity
- Provides corrosion protection
- Reduces distortion welding splatter

DIRECTIONS FOR USE:

A clean surface is necessary. Remove all rust, scale, paint and grease. All substrates must be degreased and sanded. For best results, use when temperature of the product and surface is between 68°F to 75°F (20°C to 24°C).

1. Shake can for 1 minute after mixing ball moves freely and repeat shaking for 10 seconds after each minute of use. NOTE: Insufficient mixing may cause permanent plugging of the spray head.
2. Apply directly to dry metal or galvanized surfaces. Do not apply over any other paints or coatings.
3. Hold can approximately 8–10" (20–25 cm) from surface, spraying evenly.
4. To assure that entire contents will be dispensed, always have the dot on can rim facing toward surface to be sprayed.
5. When finished, turn can upside down and spray about 3 seconds to clean out valve and spray head.

DRY TIMES:

Allow to dry for 15 minutes before welding.

RECOATING:

May be re-coated after 1 to 2 hours.

TECHNICAL DATA:

	13804
Physical State	Aerosol
Color:	Opaque. Gray. Silver
Odour:	Solvent odour
Solubility :	Practically insoluble in water
Flash point:	- 96.4°C or - 141°F (propellant)
Auto ignition temperature:	Not available
VOC	33.97%

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.