



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC**

### SECTION 01: IDENTIFICATION

Product identifier..... 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC  
 Other means of identification  
 Chemical family..... Mixture.  
 Recommended use and restrictions on .. Paints. This product should not be used for any other purpose other than the ones  
 use described in this section.  
 Initial supplier identifier..... Pro Form Products Ltd.  
 604 McGeachie Drive  
 Milton, Ontario L9T3Y5  
 Tel (905) 878-4990 Fax (905) 878-1189  
 24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
 IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
 \*\* For medical emergencies contact your local poison control centre \*\*.  
 -  
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.  
 HMIS..... H: 2 F: 4 R: 0.

### SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system). Carcinogenicity — Category 2. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2.  
 Signal Word..... DANGER.  
 Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 This product contains ingredients that are suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. (Ear).  
 Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe the mist, vapours, or spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.  
 Response ..... P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P308 + P313 If exposed or concerned, get medical advice/attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.  
 Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.  
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.  
 Note ..... This product mixture has been classified based on its ingredients.

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC****SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS                                   | CAS #      | WT. %   |
|--|------------|---------|
| tert-Butyl acetate   | 540-88-5   | 30-60   |
| Acetone  | 67-64-1    | 10-30   |
| Methyl N-Amyl Ketone   | 110-43-0   | 3-7     |
| Xylene   | 1330-20-7  | 3-7     |
| Toluene  | 108-88-3   | 1-5     |
| Ethyl 3-Ethoxypropionate                                     | 763-69-9   | 1-5     |
| 2-Propanol, 1-methoxy-, acetate                              | 108-65-6   | 1-5     |
| Carbon Black   | 1333-86-4  | 0.5-1.5 |
| Ethylbenzene   | 100-41-4   | 0.5-1.5 |
| Bisphenol A Epoxy Resin                                      | 25068-38-6 | 0.1-1   |
| <<The actual concentration(s) withheld as a trade secret>> . |            |         |

**SECTION 04: FIRST-AID MEASURES**

|  |  |
|--|--|
| Inhalation.....  | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.  |
| Ingestion.....   | Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.  |
| Skin contact.....  | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.   |
| Eye contact.....   | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Obtain medical attention.  |
| Most important symptoms and effects, .....<br>whether acute or delayed | Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Acetone is a serious eye irritant that can cause reversible damage to the cornea. It is slightly irritating to the skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. This product contains ingredients that are suspected of damaging fertility or the unborn child. This product contains ingredients that may cause cancer. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause respiratory irritation. |
| Additional information.....  | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.   |

**SECTION 05: FIRE-FIGHTING MEASURES**

|  |   |
|--|---|
| Suitable and unsuitable extinguishing media  | "Alcohol" foam, CO <sub>2</sub> , dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.  |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Extremely flammable. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO <sub>2</sub> ). Hydrocarbon fumes and smoke. Under hot acidic conditions: Isobutylene. Acetic acid.  |
| Special protective equipment and precautions for fire-fighters   | Acetone is a highly flammable liquid. It is easily ignited in the presence of heat, an ignition source such as a naked flame or a spark (including electrostatic discharge). Aqueous solutions of acetone can also ignite. Acetone vapors are heavier than air and can travel a long distance to an ignition source and cause flashback. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control. |

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

|   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | Extremely flammable liquid. No action shall be taken involving any personal risk or without suitable training. Use non-sparking tools and equipment to pick up the spilled material. Take precautions against static discharge. Isolate area and keep unauthorized people |
|---|---|

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC****SECTION 06: ACCIDENTAL RELEASE MEASURES**

|   |  |
|---|--|
| Personal precautions, protective equipment and emergency procedures ..... | away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways.   |
| Methods and materials for containment and cleaning up                     |  |
| Leak/spill.....   | Ventilate. Eliminate all sources of ignition. Contain the spill. Evacuate all non-essential personnel. Avoid all personal contact. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |

**SECTION 07: HANDLING AND STORAGE**

|  |  |
|--|--|
| Precautions for safe handling.....                           | Extremely flammable. Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. Avoid smoking, drinking or eating in use. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. Attacks some types of rubber, plastics and coatings.  |

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS                           | TWA  | ACGIH TLV<br>STEL | PEL             | OSHA PEL<br>STEL   | REL                    | NIOSH |
|---------------------------------------|--|-------------------|-----------------|--------------------|------------------------|-------|
| tert-Butyl acetate                    | 200 ppm  | Not established   | 200 ppm         | Not established    | 200 ppm                |       |
|                                       | CA ON: 50ppm (TWA), 150ppm (STEL)  |                   |                 |                    |                        |       |
| Acetone                               | 250 ppm TLV  | 500 ppm           | 1,000 ppm       | Not established    | 250 ppm                |       |
|                                       | CA ON: 500ppm (TWA); 750ppm (STEL)   |                   |                 |                    |                        |       |
| Methyl N-Amyl Ketone                  | 50 ppm   | Not established   | 100 ppm         | 465 mg/m3 TWA      | Not established        |       |
|                                       | ON OEL: 25 ppm; 115 mg/m3 (TWA)  |                   |                 |                    |                        |       |
| Xylene                                | 50 ppm   | 150 ppm           | 100 ppm TWA     | Not established    | Not established        |       |
|                                       | ON: 100ppm (TWA); 150ppm (STEL)  |                   |                 |                    |                        |       |
| Toluene                               | 20 ppm   | Not established   | 200 ppm         | 500 ppm 10 minutes | 100 ppm / STEL 150 ppm |       |
|                                       | CA ON: TWA: 20 ppm   |                   |                 |                    |                        |       |
| Ethyl 3-Ethoxypropionate              | Not established  | Not established   | Not established | Not established    | Not established        |       |
| 2-Propanol, 1-methoxy-, acetate       | 50 ppm   | 75 ppm            | Not established | Not established    | Not established        |       |
| Carbon Black                          | 3.5 mg/m3  | Not established   | 3.5 mg/m3       | Not established    | 3.5 mg/m3              |       |
| Ethylbenzene                          | 100 ppm  | 125 ppm           | 100 ppm         | Not established    | 100 ppm / STEL 125 ppm |       |
|                                       | CA ON: 20ppm (TWA)   |                   |                 |                    |                        |       |
| Bisphenol A Epoxy Resin               | Not established  | Not established   | Not established | Not established    | Not established        |       |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation. |                   |                 |                    |                        |       |
| Personal Protective Equipment         |  |                   |                 |                    |                        |       |
| Respiratory/type.....                 | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible in such instances.  |                   |                 |                    |                        |       |
| Eye/type.....                         | Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists.  |                   |                 |                    |                        |       |

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

|                    |  |
|--------------------|--|
| Gloves/ type.....  | Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. The following gloves are recommended: Butyl rubber. Contact glove supplier for recommendations. |
| Clothing/type..... | Wear adequate protective clothes.  |
| Footwear/type..... | Safety boots per local regulations.  |
| Other/type.....    | Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.  |

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

|  |   |
|--|---|
| Appearance/Physical state.....                     | Liquid.   |
| Colour.....  | Black.  |
| Odour.....   | Hydrocarbon odour.                                |
| Odour threshold (ppm).....                         | Not available.                                    |
| pH.....  | Not available.                                    |
| Melting / Freezing point (deg C).....              | Not available.                                    |
| Initial boiling point / boiling range (deg C)..... | 56°C. (acetone).                                  |
| Flash point (deg C), method.....                   | -18°C. (estimate; lowest flash point ingredient). |
| Evaporation rate.....                              | Not available.                                    |
| Upper flammable limit (% vol).....                 | 12.6.   |
| Lower flammable limit (% vol).....                 | 0.9.  |
| Vapour pressure (mm Hg).....                       | Not available.                                    |
| Vapour density (air=1).....                        | >1.   |
| Relative Density (Specific Gravity).....           | 0.898.  |
| Pounds / USG.....                                  | 7.50.   |
| Solubility.....                                    | Negligible.                                       |
| Partition coefficient — n-octanol/water.....       | Not available.                                    |
| Auto ignition temperature (deg C).....             | >250.   |
| Decomposition temperature.....                     | Not available.                                    |
| Viscosity.....                                     | 18 sec Zahn #2.                                   |
| % Volatile by volume.....                          | 17.92.  |
| VOC (less water).....                              | 1.29 lbs/USG; 154.6 g/L.                          |

**SECTION 10: STABILITY AND REACTIVITY**

|   |   |
|---|---|
| Reactivity .....  | Product is stable; hazardous polymerization will not occur.   |
| Chemical stability.....   | Stable at normal temperatures and pressures.  |
| Possibility of hazardous reactions.....                                   | Hazardous polymerization will not occur.  |
| Conditions to avoid, including static discharge, shock or vibration ..... | Keep away from heat. Electrostatic charge.  |
| Incompatible materials.....   | Strong acids. Strong bases. Strong oxidizers. Reducing agents. Acetone may ignite or react violently with strong oxidizing agents, such as chromic acid, chromium trioxide, chromyl chloride, hot nitric acid, potassium permanganate (in an alkaline medium), or peroxides. Aldehydes. Ammonia. Peroxides. Nitrates. Plastics. |
| Hazardous decomposition products.....                                     | No hazardous decomposition products when stored and handled correctly. Hazardous decomposition products depend on temperature, air supply, and the presence of other materials. See hazardous combustion products section 5.  |

**SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS                     | LC50   | LD50  |
|---------------------------------|--|---|
| tert-Butyl acetate              | >2,230 mg/m <sup>3</sup> 4 hours rat                     | 4,100 mg/kg (rat, oral);<br>>2,000 mg/kg (rabbit, dermal) |
| Acetone                         | 50,100 mg/m <sup>3</sup> 8 hours, rat                    | 5,800 mg/kg (rat oral)                                    |
| Methyl N-Amyl Ketone            | Not Available  | 1,670 mg/kg rat oral<br>12,600 mg/kg rabbit dermal        |
| Xylene                          | 6350 ppm 4 hours rat                                     | >3523 mg/kg rat oral                                      |
| Toluene                         | 8000 ppm rat inhalation<br>400 ppm mouse inhalation 24hr | 5,000 mg/kg rat oral;<br>12,124 mg/kg rabbit dermal       |
| Ethyl 3-Ethoxypropionate        | >998 ppm 6 hours   | 4,309 mg/kg rat oral<br>4,080 mg/kg rabbit dermal         |
| 2-Propanol, 1-methoxy-, acetate | Not Available  | 8,532 mg/kg rat oral<br>5,000 mg/kg dermal rabbit         |

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC****SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS  | LC50   | LD50  |
|--|--|---|
| Carbon Black   | Not available  | >10,000 mg/kg oral rat<br>3,000 mg/kg dermal rabbit |
| Ethylbenzene   | No data  | 3,500 mg/kg rat oral<br>17,800 mg/kg rabbit dermal  |
| Bisphenol A Epoxy Resin  | Not Available  | >10000 mg/kg (rat oral)                             |
| Route of exposure.....   | Eye contact. Skin contact. Inhalation.   |   |
| Symptoms related to the physical, chemical and toxicological characteristics |  |   |
| Skin contact.....  | Can cause moderate irritation, defatting and dermatitis.   |   |
| Skin absorption.....   | May be harmful if absorbed through the skin.   |   |
| Eye contact.....   | Causes eye irritation. Can cause redness, irritation, tissue destruction.  |   |
| Inhalation (acute).....  | Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.   |   |
| Inhalation (chronic).....  | Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.   |   |
| Ingestion.....   | Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.   |   |
| Effects of chronic exposure.....   | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.  |   |
| Sensitizing capability of material.....                                      | May cause sensitization by skin contact.   |   |
| Carcinogenicity of material.....   | IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies. Ethylbenzene is classified as an A3 known animal carcinogen.   |   |
| Reproductive effects.....  | Xylene has been classified by The Commission on Health and Safety as causing reproductive effects. High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. |   |
| Specific Target Organ Toxicity .....   | May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure . (ear).   |   |

**SECTION 12: ECOLOGICAL INFORMATION**

|                                    |  |
|------------------------------------|--|
| Ecotoxicity.....                   | Product data not available.                        |
| Persistence and degradability..... | Product data not available.                        |
| Bioaccumulative potential.....     | Product data not available.                        |
| Mobility in soil.....              | Product data not available.                        |
| Other adverse effects.....         | Do not allow to enter waters, waste water or soil. |

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Empty containers must be handled with care due to product residue.

**SECTION 14: TRANSPORT INFORMATION**

|                                   |  |
|-----------------------------------|--|
| TDG Classification.....           | UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.                       |
| DOT Classification (Road).....    | UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.                          |
| IATA Classification (Air).....    | UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.                                 |
| IMDG Classification (Marine)..... | UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.                            |
| Marine Pollutant.....             | Potential marine pollutant.  |
| Proof of Classification.....      | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

**PRODUCT: 14032 TRIM & BUMPER COATING TRIM BLACK 2.1 VOC****SECTION 15: REGULATORY INFORMATION**

|  |  |
|--|--|
| CEPA status.....                             | On Domestic Substances List (DSL).   |
| TSCA inventory status.....                   | All components are listed.   |
| OSHA.....                                    | This product is considered hazardous under the OSHA Hazard Communication Standard.   |
| SARA Title III                               |  |
| Section 302 - extremely hazardous substances | None.  |
| Section 311/312 - hazard categories.....     | Immediate health, delayed health, fire hazard.   |
| Section 313.....                             | Ethylbenzene. Glycol ethers. Toluene. Xylene.  |
| EPA hazardous air pollutants (HAPS) 40CFR63  | Benzene. Chlorobenzene. Ethylbenzene. Glycol ethers. Toluene. Vinyl acetate. Vinyl chloride. Xylene.   |
| California Proposition 65.....               | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Benzene (D)). (Toluene). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Benzene). (Carbon black - airborne, unbound particles of respirable size). (Ethyl benzene). (Vinyl chloride). For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> . |

**SECTION 16: OTHER INFORMATION**

|   |   |
|---|---|
| Prepared by: .....                                      | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. <a href="http://www.trivalent.com">www.trivalent.com</a> .  |
| Telephone number:.....                                  | (800) 387-7981.   |
| Disclaimer:.....  | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Date of the latest revision of the safety data sheet .. | 2021-01-12  |