

Molding Tape Adhesion Promoter is a liquid primer used to improve the adhesion of Acrylic Foam Tapes to exterior and interior trims involving injection molded and/or plastic parts (TPO, PPO, PP, PG, PC, PVC and ABS). Use prior to two-way tape application on exterior and interior trims.

PRODUCT	SIZE
16170	7.5 fl oz (220 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metal
- Plastic

ADVANTAGES:

- Improve adhesion of Acrylic Foam Tapes

DIRECTIONS FOR USE:

1. Remove all tape and residue from part and vehicle.
2. Clean metal parts with 19000 General Purpose Adhesive Cleaner and clean plastic parts with 19038 Plastic Parts Cleaner.
3. Let dry thoroughly.
4. Apply 16170 Adhesion Promoter on injection-molded and plastic parts.
5. Let dry 3 to 5 minutes.
6. Apply tape to part with the exterior red release liner still attached to the tape. Paint the part if necessary.
7. Remove interior release liner, being careful not to touch or contaminate the surface of the exposed adhesive.
8. Firmly roll down or rub down plastic molded part to vehicle.
9. When a heavy molding is used it might be necessary to hold it in place with duct tape for a couple of hours until adhesive sets.

Caution: Adhesion promoter will harm painted surfaces. Apply adhesion promoter and molding tape prior to painting molding.

TECHNICAL DATA:

	16170
Physical State	Liquid
Color:	Colourless
Odour:	Sweet mint-like odour
Solubility :	Soluble
Flash point:	-15°C/ 5°F (Tag Closed Cup)
Auto ignition temperature:	Not available
VOC:	0.35 lb/usg - 41.94 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.