



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 17004 TRUCK LINE PLIOGRIP URETHANE ADHESIVE 35 MIN PART A

SECTION 01: IDENTIFICATION

Product identifier..... 17004 TRUCK LINE PLIOGRIP URETHANE ADHESIVE 35 MIN PART A
Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189
24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.
Recommended use and restrictions on use .. Adhesive applications. for industrial use only-keep out of reach of children . This product
should not be used for any other purpose other than the ones described in this section.
Chemical family..... Aromatic isocyanate prepolymer.
Hazard rating
NFPA rating..... Health: 2 Fire: 1 Reactivity: 1.
HMIS..... H: 2 F: 1 R: 1.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.
Hazard Classification..... Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritant 2. Respiratory
Sensitizer — Category 1. Specific Target Organ Toxicity — Repeated Exposure —
Category 1.
Hazard Description..... H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes
serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties
if inhaled. H372 Causes damage to the liver and kidneys through prolonged or repeated
exposure.
Prevention..... P260 Do not breathe mist, vapours, or spray. P261 Avoid breathing mists, vapours and
sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using
this product. P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves and eye protection. P284 In case of inadequate ventilation
wear respiratory protection.
Response P302 + P352 - If on skin: wash with plenty of water. P321 - For specific treatment see
section 4 on this SDS. P333 + P313 If skin irritation or rash occurs, get medical
advice/attention. P362 + P364 - Take off contaminated clothing and wash before reuse.
P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337
+ P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove
person to fresh air and keep comfortable for breathing. P342 + P311 If experiencing
respiratory symptoms; call poison center or doctor. P314 - Get medical advice/attention if
you feel unwell.
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|---------|
| PART A: | | |
| Benzene, 1,1'-methylenebis[4-isocyanato- (MDI) | 101-68-8 | 30-40 |
| Talc | 14807-96-6 | 15-25 |
| 2,4-Diphenylmethane diisocyanate (MDI) | 5873-54-1 | 0.1-1.0 |
| PART B: | | |
| CLAY (TALC) | 14807-96-6 | 20-30 |

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART A**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| | | |
|------------|------------|-------|
| PIPERAZINE | 110-85-0 | 1-5 |
| BENTONITE | 71011-26-2 | 0.1-1 |

SECTION 04: FIRST-AID MEASURES

| | |
|-----------------------------|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Obtain medical attention. |
| Skin contact..... | Immediately flush skin with plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. Do not peel solidified product off the skin. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Get medical attention. |
| Additional information..... | Eye: stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapours have produced reversible corneal epithelial edema impairing vision. Skin: this compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn. Ingestion: treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. Respiratory: this compound is a known pulmonary sensitizer. Treatment is essentially symptomatic. An individual having a skin or pulmonary sensitization reaction to this material should be removed from exposure to any isocyanate. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. In all cases, if irritation persists seek medical attention. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable and unsuitable extinguishing media | Dry chemical. Carbon dioxide. Foam. In cases of larger fires, water spray should be used. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO ₂). Oxides of nitrogen. Smoke. Hydrogen cyanide. Isocyanates. Other potentially toxic fumes. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. During a fire, isocyanate vapours and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. |
| Unusual fire / explosion hazards..... | Reaction between water or foam and hot MDI can be vigorous. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-------------------|---|
| Leak/spill..... | Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. |
| Major spills..... | If temporary control of isocyanate vapour is required, a blanket of protein foam may be placed over spill. If transportation spill occurs in United States, call Chemtrec 1-800-424-9300. If transportation spill occurs in Canada, call Canutec at (613) 996-6666. Large quantities may be pumped into closed, but not sealed, containers for disposal. |
| Minor spills..... | Cover spill area with suitable absorbent material (e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Saturate absorbent material with neutralizing solution. Recommended portion is ten parts neutralizing solution to one part spilled material. Suggested neutralization solution: 90% water + 5% concentrated ammonia + 5% detergent (dish soap). Add an additional layer of absorbent material. Use shovel to move absorbent material around to ensure that all spilled material comes in contact with the neutralizing solution. Shovel all absorbed material, including absorbent socks or spill pillows, into an appropriate salvage drum. Add further amounts of neutralizing solution. Allow to stand (covered loosely) for 48 to 72 hours, to allow any gases to escape. |
| Clean up..... | Decontaminate spill area with decontamination solution. Area can then be washed with soap and water. |

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART A**SECTION 07: HANDLING AND STORAGE**

| | |
|--|---|
| Precautions for safe handling..... | Avoid skin and eye contact. Do not breathe vapours, mist or dust. Use adequate ventilation. Decomposition products can be highly toxic and irritating. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapour or spray mist. Warning properties (irritation of the eyes, nose and throat or odour) are not adequate to prevent chronic overexposure from inhalation. Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Wear respiratory protection if material is heated, sprayed, used in confined space, or if exposure limit is exceeded. Employee education and training are important. |
| Conditions for safe storage, including any incompatibilities | Store in tightly closed containers to prevent moisture contamination. Store in a cool, dry and well ventilated area. Do not reseal if contamination is suspected. Exposure to vapours of heated isocyanates can be extremely dangerous. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|--|--|-----------------|-----------------|----------------------|-----------------|
| Benzene, 1,1'-methylenebis[4-isocyanato- (MDI) | 0.005 ppm | Not established | 0.005 ppm TWA | 0.005 ppm AB OEL TWA | 0.05 mg/m3 |
| Talc | 2 mg/m3 CA ON: 2mg/kg (TWA) | Not established | 2 mg/m3 TWA | Not established | Not established |
| 2,4-Diphenylmethane diidocyanate (MDI) | Not established | Not established | Not established | Not established | Not established |
| CLAY (TALC) | 2 mg/m3 | Not established | 2 mg/m3 TWA | 3 mg/m3 - QUE | Not established |
| PIPERAZINE | Not established | Not established | Not established | Not established | Not established |
| BENTONITE | Not Established | Not Established | Not Established | Not Established | Not Established |
| Eye/type..... | Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists. Contact lenses should not be worn when working with this chemical. | | | | |
| Respiratory/type..... | In case of insufficient ventilation, wear suitable respiratory equipment. An approved air purifying respirator with organic vapour cartridges and particulate prefilter can be used to minimize exposure. However, this should be permitted only for short periods of time (< 1 hour) at relatively low concentrations (at or near the exposure limit). Protection provided by air-purifying respirators is limited. The use of a positive pressure air supplied respirator is mandatory when airborne concentrations are not known or airborne solvent levels are 10 times the appropriate exposure limit or spraying is performed in a confined space or with limited ventilation. Use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator. | | | | |
| Gloves/ type..... | Chemical resistant gloves: butyl rubber, nitrile rubber, neoprene, PVC. Practice good hygiene, wash thoroughly before handling any food. | | | | |
| Clothing/type..... | Wear adequate protective clothes. Wear long sleeves and trousers to prevent dermal exposure. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Other/type..... | Eye wash facility and emergency shower should be in close proximity. Educate and train employees on the safe use and handling of the product. | | | | |
| Appropriate engineering controls..... | Ventilate adequately. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Vent work area to ensure airborne concentrations are below the current occupational exposure limits. Avoid breathing mists; if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices. | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|--|
| Appearance/Physical state..... | Part A: Viscous liquid. | Part B: Viscous liquid. |
| Colour..... | Part A: Beige. | Part B: Green. |
| Odour..... | Part A: No data. | Part B: No data. |
| Odour threshold (ppm)..... | Part A: Not available. | Part B: . No data. |
| Vapour pressure (mm Hg)..... | Part A: <0.013 hPa @ 25C. | Part B: 3.000 hPa @ 25°C. |
| Vapour density (air=1)..... | Part A: >1. | Part B: >1. |
| pH..... | Part A: . No data. | Part B: . No Data. |
| Relative Density (Specific Gravity)..... | Part A: 1.288 g/cm3 @ 20°C - 10.72 lb/USG @ 25°C. | Part B: 1.225 g/cm3 @ 20°C - 10.2 lb/usg @ 25°C. |
| Melting / Freezing point (deg C)..... | Part A: . Not available. | Part B: . No data. |
| Solubility..... | Part A: Practically insoluble in water. | Part B: . Insoluble in water. |
| Initial boiling point / boiling range (deg C). | Part A: >200°C (>392°F). | Part B: No data. |
| Evaporation rate..... | Part A: . <1. (butyl acetate = 1). | Part B: . 1.0. Ethyl ether = 1.0. |
| Flash point (deg C), method..... | Part A: >100°C, >212°F. | Part B: . >93.4°C, >200°F . |

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART A**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

| | | |
|--|-----------------------------------|--------------------|
| Auto ignition temperature (deg C)..... | Part A: Not available. | Part B: No data. |
| Upper flammable limit (% vol)..... | Part A: . No data. | Part B: . No Data. |
| Lower flammable limit (% vol)..... | Part A: . No Data. | Part B: . No data. |
| Partition coefficient — n-octanol/water..... | Part A: . Not available. | Part B: . No data. |
| VOC (less water)..... | Part A: 2.55 lb/USG - 305.57 g/L. | Part B: . No data. |
| Viscosity..... | Part A: . Not available. | Part B: . No data. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Contact with moisture and other materials will react with isocyanates. |
| Conditions to avoid, including static discharge, shock or vibration | Water, amines, strong bases, alcohols. Copper alloys. |
| Hazardous decomposition products..... | See hazardous combustion products section 5. |
| Possibility of hazardous reactions..... | Contact with moisture, other materials that react with isocyanates, or temperatures above 177C, may cause polymerization. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|--|---|
| Benzene, 1,1'-methylenebis[4-isocyanato- (MDI) | 490 mg/m ³ 4 hr 0.369 mg/L 4 hr | 9,200 mg/kg rat oral >7,900 mg/kg rabbit dermal |
| Talc | Not available | Not available |
| 2,4-Diphenylmethane diisocyanate (MDI) | No data | No data |
| CLAY (TALC) | No data | No data |
| PIPERAZINE | No data | 1,900 mg/kg oral rat; 4,000 mg/kg dermal rabbit |
| BENTONITE | No Data | No Data |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | SKIN: Irritant. Can cause reddening, itching and swelling. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling and rash. Cured material is difficult to remove. Contact with MDI can cause discoloration. EYE: Product liquid, aerosols or vapours are irritating. Can cause tearing, reddening and swelling. May cause temporary corneal injury. INHALATION: Vapour/mists at concentrations above the exposure limits can irritate (burning sensation) the mucous membranes in the respiratory tract. This can cause a runny nose, sore throat, coughing, chest discomfort, difficulty breathing and reduced pulmonary functioning. Persons with pre-existing, nonspecific bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as asthma attack. These symptoms can be delayed up to several hours after exposure. Effects are usually reversible. INGESTION: May cause irritation. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea. Talc can be absorbed into the lungs and the digestive tract, and adversely affect lung function. | |
| Effects of chronic exposure..... | As a result of previous repeated overexposure or a single large dose, certain individuals develop sensitization, which will cause them to react to a later exposure to product at levels well below the TLV. Symptoms, including chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed. There are reports that once sensitized, an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and, in severe cases, for several years. Prolonged or repeated exposure may cause lung damage, including a decrease in lung function. Possible risk of irreversible effects. Prolonged skin contact may cause reddening, swelling, rash, blistering, and in some cases, skin sensitization. Sensitization can be permanent. Prolonged vapour contact with eyes may cause conjunctivitis. Talc has been shown to cause fibrosis of the lungs. | |
| Sensitizing capability of material..... | Isocyanates are known to cause skin and respiratory sensitization in humans. Animal tests have indicated that respiratory sensitization can result from skin contact with diisocyanates. | |
| Carcinogenicity of material..... | 4,4'-Methylenediphenyl diisocyanate is listed by IARC as a Group 3 carcinogen. This product contains non-asbestiform Talc, which is classified as a Group 3 (not classifiable as to carcinogenicity to humans) by IARC. | |
| Note..... | This product is an inert plastic when fully cured, and as such, is non-hazardous. Exposure to unreacted chemicals can occur when handling the individual components in pails or when using cartridges from the time of dispensing until the mixed material has cured. The mixed material is actually curing as it is dispensed in an increasingly viscous form, making it unlikely to present an inhalation hazard. The semi-viscous mixture does not flow like a liquid when dispensed, thus minimizing the possibility of accidental skin contact. | |

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART A**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable federal, provincial/State and local regulations. Industrial incineration is the preferred method. Empty containers retain product residue; observe all precautions for the product. Decontaminate containers prior to disposal. Empty decontaminated containers should be crushed to prevent reuse. Do not heat or cut empty containers with electric or gas torch as vapours and gases may be toxic.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... Not regulated.
 IATA Classification (Air)..... Not regulated.
 IMDG Classification (Marine)..... Not regulated.
 Marine Pollutant..... No.

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health.
 Section 313..... 4,4'-methylenediphenyl diisocyanate.
 EPA hazardous air pollutants (HAPS) Methylene Diphenyl Diisocyanate (MDI).
 40CFR63
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Review Date:..... 2021-11-15.
 Date of the latest revision of the safety data sheet .. 2015-07-27



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 17004 TRUCK LINE PLIOGRIP URETHANE ADHESIVE 35 MIN PART B

SECTION 01: IDENTIFICATION

Product identifier..... 17004 TRUCK LINE PLIOGRIP URETHANE ADHESIVE 35 MIN PART B
Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189
24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.
Recommended use and restrictions on .. Adhesive applications.
use
Chemical family..... Polyol preparation.
Hazard rating
NFPA rating..... Health: 2 Fire: 1 Reactivity: 0.
HMIS..... H: 2* F: 1 R: 0.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.
Hazard Classification..... Acute Toxicity 4. Respiratory Sensitizer — Category 1. Skin Sensitizer — Category 1.
Carcinogenicity — Category 2. Specific Target Organ Toxicity — Single Exposure —
Category 3. Specific Target Organ Toxicity — Repeated Exposure — Category 2.
Hazard Description..... H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H332 Harmful
if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 This product contains ingredients that are suspected of causing cancer.
Prevention..... P202 Do not handle this product until all safety instructions have been read and
understood. P233 Keep container tightly closed. P261 Avoid breathing mists, vapours and
sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using
this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work
clothing should not be allowed out of the workplace. P273 Avoid release to the
environment. P280 Wear protective gloves and eye protection. P284 In case of inadequate
ventilation wear respiratory protection. P410 Protect from sunlight.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|----------------------------|------------|---------|
| Talc | 14807-96-6 | 10-20 |
| BENTONITE | 71011-26-2 | 1-5 |
| PIPERAZINE | 110-85-0 | 0.1-1.0 |
| Crystalline Silica | 14808-60-7 | 0.1-1 |

SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
least 15 minutes. Consult a physician if irritation continues.
Skin contact..... Wash using plenty of soap and water. Remove contaminated clothing. Do not peel
solidified product off the skin. If irritation persists, seek medical attention.
Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
difficult, give oxygen, obtain medical attention.

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART B**SECTION 04: FIRST-AID MEASURES**

Ingestion..... If swallowed, drink plenty of water. Wash out mouth repeatedly. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Get medical attention.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media Carbon dioxide. Dry chemical. In cases of larger fires, water spray should be used.

Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products By fire: protect against potentially toxic and irritating fumes. Oxides of carbon (CO, CO₂). Other potentially toxic fumes.

Special protective equipment and precautions for fire-fighters Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Avoid breathing vapours or mist. Avoid skin and eye contact. Handle in accordance with good industrial hygiene and safety practices. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities Keep container closed when not in use. Store away from sunlight. Store in a cool, dry and well ventilated area.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | ACGIH TLV | | OSHA PEL | | NIOSH |
|---------------------------------------|---|-----------------|---------------------------|-----------------|------------------------|
| | TWA | STEL | PEL | STEL | |
| Talc | 2 mg/m ³ CA ON: 2mg/kg (TWA) | Not established | 2 mg/m ³ TWA | Not established | Not established |
| BENTONITE | Not Established | Not Established | Not Established | Not Established | Not Established |
| PIPERAZINE | Not established | Not established | Not established | Not established | Not established |
| Crystalline Silica | 0.025 mg/m ³ CA ON: 0.025 mg/m ³ Respirable | Not established | 0.1 mg/m ³ TWA | Not established | 0.05 mg/m ³ |
| Personal Protective Equipment | | | | | |
| Eye/type..... | Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists. | | | | |
| Respiratory/type..... | Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator. | | | | |
| Gloves/ type..... | Chemical resistant gloves: butyl rubber, nitrile rubber, neoprene, PVC. | | | | |
| Clothing/type..... | Wear adequate protective clothes. Wear long sleeves and trousers to prevent dermal exposure. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Other/type..... | Eye wash facility and emergency shower should be in close proximity. | | | | |
| Appropriate engineering controls..... | Use local exhaust or general room ventilation sufficient to prevent overexposure. | | | | |
| Exposure limits | | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Viscous liquid.

Colour..... Green.

Odour..... No data.

Odour threshold (ppm)..... Not available.

Vapour pressure (mm Hg)..... 3 hPa @ 25°C.

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART B**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

| | |
|--|--|
| Vapour density (air=1)..... | >1. |
| pH..... | No data. |
| Relative Density (Specific Gravity)..... | 1.225 g/cm ³ @ 20°C - 10.2 lb/usg @ 25°C. |
| Melting / Freezing point (deg C)..... | Not available. |
| Solubility..... | Insoluble in water. |
| Initial boiling point / boiling range (deg C). | No data. |
| Evaporation rate..... | 1.0. |
| Flash point (deg C), method..... | >93.4°C, >200°F . |
| Auto ignition temperature (deg C)..... | Not available. |
| Upper flammable limit (% vol)..... | No data. |
| Lower flammable limit (% vol)..... | No data. |
| Partition coefficient — n-octanol/water..... | Not available. |
| VOC (less water)..... | 0.0 g/L - 0.0 lb/usg. |
| Viscosity..... | Not available. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Reaction will occur in the presence of isocyanates. A component in this product absorbs humidity (hygroscopic). Avoid exposure to moisture. A component in this product is sensitive to light. Avoid exposure to sunlight. |
| Conditions to avoid, including static discharge, shock or vibration | Isocyanates. Oxidizing and reducing agents. |
| Hazardous decomposition products..... | See hazardous combustion products section 5. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|---|--|---|
| Talc | Not available | Not available |
| BENTONITE | No Data | No Data |
| PIPERAZINE | No data | 1,900 mg/kg oral rat; 4,000 mg/kg dermal rabbit |
| Crystalline Silica | Not available | >22,500 mg/kg oral rat |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | May cause slight eye and slight skin irritation. Talc can be absorbed into the lungs and the digestive tract, and adversely affect lung function. | |
| Effects of chronic exposure..... | Prolonged or repeated breathing of talc may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. . | |
| Sensitizing capability of material..... | Piperazine is suspected of being both a dermal and respiratory sensitizing agent. | |
| Carcinogenicity of material..... | This product contains non-asbestiform Talc, which is classified as a Group 3 (not classifiable as to carcinogenicity to humans) by IARC . Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. | |
| Note..... | This product is an inert plastic when fully cured, and as such, is non-hazardous. Exposure to unreacted chemicals can occur when handling the individual components in pails or when using cartridges from the time of dispensing until the mixed material has cured. The mixed material is actually curing as it is dispensed in an increasingly viscous form, making it unlikely to present an inhalation hazard. The semi-viscous mixture does not flow like a liquid when dispensed, thus minimizing the possibility of accidental skin contact. | |
| Toxicological Data | | |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Empty containers must be handled with care due to product residue. Empty drums should be reconditioned by a properly licensed drum recycler. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. |
|---|---|

PRODUCT: 17004 TRUCK LINE PLOGRIP URETHANE ADHESIVE 35 MIN PART B**SECTION 14: TRANSPORT INFORMATION**

| | |
|-----------------------------------|----------------|
| TDG Classification..... | Not regulated. |
| IATA Classification (Air)..... | Not regulated. |
| IMDG Classification (Marine)..... | Not regulated. |
| Marine Pollutant..... | No. |

SECTION 15: REGULATORY INFORMATION

| | |
|--|---|
| WHMIS 1988 classification..... | D2A, D2B. |
| CEPA status..... | On Domestic Substances List (DSL). |
| Section 313..... | None. |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | None. |
| TSCA inventory status..... | All components are listed. |
| California Proposition 65..... | This product contains Bentonite known by the State of California to cause cancer, birth defects or reproductive harm. |

SECTION 16: OTHER INFORMATION

| | |
|---|---|
| Prepared by: | REGULATORY AFFAIRS. |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:..... | 2021-11-15. |
| Date of the latest revision of the safety .. data sheet | 2014-04-05 |