

Superior two part epoxy adhesive designed to bond steel, aluminum, SMC and fiberglass truck parts and panels. It seals and bonds in one application, and longer work time allows for adjusting and handling. The glass beads mixed in this formulation provide the adequate spacing between parts for optimal bond strength. Use 17904, 17906 or 17914 replacement nozzle (24 elements).

PRODUCT

SIZE

17200

13.5 fl oz (400 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Steel
- Aluminum
- SMC
- Fiberglass
- Panels

DIRECTIONS FOR USE:

1. Read carefully instructions sheet included before proceeding.
2. Remove plastic lid protector.
3. Open cartridge by breaking off the tip with a flat screwdriver removing both plugs.
4. Place cartridge into channels on dispensing gun.
5. Work trigger until both plungers are snug against bottom plugs.
6. Pre dispense 5cm (2") of product making sure both sides are equalized and color of the product is uniform. Dispose of this material.
7. Attach mixing nozzle to cartridge and apply product.
8. When application is completed, do not remove mixing nozzle. Store for future use. Always check for any solids build up in the area of cartridge head/nozzle, if contaminants are visible, change nozzle.
9. Use a new mixing nozzle when re-used.
10. Always use applicator gun and mixing nozzle to mix material. Do not mix by hand.
11. Store cartridges at temperature between 18°C and 35°C (65°F and 95°F).

TECHNICAL DATA:

	17200 Part A	17200 Part B
Physical State	Viscous liquid	
Color:	Black	Tan
Odour:	No data	Very faint, amine-like
Solubility :	Insoluble in water	Practically insoluble in water
Flash point:	>99°C/>210.2°F (Setaflash Closed Cup)	>93.4°C/ >200°F
Auto ignition temperature:	No data	No data

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.