

Product Data Sheet

Multi Purpose Contact Adhesive bonds all types of rubber and vinyl weatherstrip to metal substrates. It is fast drying and offers great bonding strength. It may also be used for bonding materials such as rubber or plastic foam and sponge, canvas, cork, leather and more, to metal, wood, plastic and many other substrates.

PRODUCT

SIZE

18000

7.4 oz (220 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Rubber
- Plastic foam and sponge
- Canvas
- Cork
- Leather
- Metal
- Wood
- Plastic

DIRECTIONS FOR USE:

1. Clean both surfaces to be joined, being sure to remove all mold release agents from new weather stripping.
2. Apply a thin coat of Multi Purpose Contact Adhesive to both surfaces and allow to flash for 1 to 2 minutes.
3. Apply a second thin coat of adhesive to weatherstrip section not over 3 feet (91 cm) in length and bond immediately.

Note: Avoid getting adhesive on exposed painted surfaces. Clean excess adhesive with 19000 General Purpose Adhesive Cleaner.

TECHNICAL DATA:

	18000
Physical State	Liquid
Color:	Amber
Odour:	Aromatic odour
Solubility :	Not soluble in water
Flash point:	-30°C/-22°F (Tag Closed Cup)

Auto ignition temperature:	>203°C (>397.4°F)
VOC	550 g/L - 4.59 lbs/gal

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.