

Rubber/Solvent Based Economical Seam Sealer 18100, 18102

A single component, fast drying, rubber/solvent based, economy sealer that skins in 2 to 3 minutes. Use to seal small gaps or seams where minimal flexibility is required. This product is easily tooled into a fine featheredge. Adheres to bare or painted metals and automotive plastics.

PRODUCT**SIZE****COLOR****18100**

10.14 fl oz (300 ml)

White

18102

10.14 fl oz (300 ml)

Black

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Painted metals
- Automotive plastics

ADVANTAGES:

- Fine featheredge

DIRECTIONS FOR USE:

1. Temperature of material and surfaces should be above 65°F (18°C). Clean metal surfaces with 19160 Heavy Duty Wax & Grease Remover (Strong). Clean plastic surfaces with 19040 Plastic Parts Cleaner.
2. Cut spout to desired bead size and puncture inner seal.
3. Flow bead directly into seam or joint. Brush or feather if desired.
4. Can be painted after surface skins. For best results, paint after 1 hour.
5. Sealer must be painted if exposed to ultra violet rays.

Note: Do not use on seams and joints that have a lot of mechanical stress, shock and vibration. Do not use to fill gaps larger than 1/8" (3 mm). Use 18120 or 18122 Urethane Sealer/Adhesive for these applications.

TECHNICAL DATA:

	18100	18102
Physical State	Paste	
Color:	White	Black
Odour:	Aromatic odour	
Solubility :	Not soluble in water	

Rubber/Solvent Based Economical Seam Sealer 18100, 18102

Flash point:	4°C / 39.2°F (Tag Closed Cup)
Auto ignition temperature:	No data
VOC:	513 g/L - 4.28 lb/usg

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.