

Epoxy sealer designed to seal interior or exterior seams. This high solids formulation prevents shrinking and cracking. Excellent adhesion to metals, SMC and most plastics. Use 17904 or 17906 or 17914 replacement nozzle (24 elements).

PRODUCT

SIZE

18140

6.8 fl oz (200 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES

- Metals
- SMC
- Plastics

ADVANTAGES

- Excellent adhesion

DIRECTIONS FOR USE:

Remove plastic lid protector. Open cartridge by breaking off the tip with a flat screwdriver removing both plugs. Place cartridge into channels on dispensing gun. Work trigger until both plungers are snug against bottom plugs. Pre-dispense 2" (5 cm) of product making sure both sides are equalized and color of the product is uniform. Dispose of this material. Attach mixing nozzle to cartridge and apply product. When application is completed, do not remove mixing nozzle. Store for future use. Always check for any solids build up in the area of cartridge head/nozzle, if contaminants are visible, change nozzle. Use a new mixing nozzle when re-used. Always use applicator gun and mixing nozzle to mix material. Do not mix by hand. Store cartridges at temperature between 65°F to 95°F (18°C to 35°C). Substrate to be repaired should be at 70°F (21°C) or above.

1. Clean metal surfaces with 19000 General Purpose Adhesive Cleaner. Clean plastic surfaces with 19040 Plastic Parts Cleaner.
2. Cut mixing nozzle to desired bead size.
3. Flow bead directly into seam or joint. Brush or feather if desired.
4. Can be painted after 30 minutes.
5. Paint sealer if exposed to ultra violet rays.

Product Data Sheet

*77°F (25°C)	18140
Working Time:	5-10 minutes
Sanding Time:	15-30 minutes
Cure Time:	2 hours
Full Cure:	6-8 hours

TECHNICAL DATA:

	18140 Parte A	18140 Parte B
Physical State	Thick liquid, paste	
Color:	Pale yellow	Light yellow
Odour:	Little or no odour	Sweet odour
Solubility :	Insoluble	Insoluble in water
Flash point:	266°C (510.8°F)	>93°C (>199.4°F)
Auto ignition temperature:	Not available	Not available
VOC	0.0 g/L - 0.0 lb/usc	No data

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.