



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: 19128 SPRAY GUN PAINT REMOVER AEROSOL

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 19128 SPRAY GUN PAINT REMOVER AEROSOL

Recommended use and restrictions on .. Cleaner.
use


Chemical family..... Solvent blend.

NFPA rating..... Health: 3 Fire: 3 Reactivity: 0.

HMIS..... H: 3 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosols — Category 1. Gases Under Pressure: Liquefied Gas. Aspiration Toxicity 1. Serious Eye Damage/Eye Irritation — Category 2A. Skin Corrosion/Irritation — Category 3. Specific Target Organ Toxicity — Single Exposure — Category 3.

Hazard Description..... H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H316 Causes mild skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P312 Call a POISON CENTER/doctor if you feel unwell. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye irritation persists get medical attention.

Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	80-100
Carbon dioxide	124-38-9	5-10
Naphtha (petroleum), hydrotreated light	64742-49-0	3-7
Isopropyl Alcohol	67-63-0	3-7

PRODUCT: 19128 SPRAY GUN PAINT REMOVER AEROSOL**SECTION 04: FIRST-AID MEASURES**

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove contaminated clothing and launder before reuse. Rinse skin for 15-20 minutes. Obtain medical attention immediately.
Inhalation.....	Move to fresh air. If not breathing, give artificial respiration. Obtain medical attention immediately.
Ingestion.....	Do not induce vomiting. Rinse mouth with water. If ingestion is suspected, contact physician or poison control center immediately.
Most important symptoms and effects, whether acute or delayed	Aspiration hazard.
Immediate medical attention and special treatment needed, if necessary	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable extinguishing media.....	"Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used.
Unsuitable extinguishing media.....	Do not use solid water streams or water jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Contents under pressure. Pressurized container may explode when exposed to heat or flame. .
Special protective equipment and precautions for fire-fighters	Extremely flammable aerosol. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. . Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate personnel to a safe area. Keep unnecessary and unprotected personnel from entering spill area and upwind from spill area. Avoid walking through spilled material. Avoid breathing vapours. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear appropriate personal protection equipment.
Environmental precautions.....	Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.
Methods and materials for containment and cleaning up	Contain spilled material and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapours. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well ventilated areas.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Store away from sunlight. Do not store above 50 deg C. Do not puncture, incinerate or crush container. Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from all sources of heat and ignition. Store away from acids. Store away from oxidizing agents.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
	TWA	STEL		STEL	STEL		
Acetone	250 ppm TLV CA ON AB: 500ppm (TWA); 750ppm (STEL)	500 ppm	1,000 ppm	Not established	Not established	250 ppm	
Carbon dioxide	5000 ppm	30000 ppm	5000 ppm	No data	No data	5000 ppm 10 hours STEL 30000 ppm 15 minutes	
	STEL 30000ppm (3%)						

PRODUCT: 19128 SPRAY GUN PAINT REMOVER AEROSOL**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Naphtha (petroleum), hydrotreated light	1640 mg/m3 (heptane) 1100 ppm (IDLH)	Not established	Not established	Not established	Not established	Not established
Isopropyl Alcohol	200 ppm	400 ppm	400 ppm (TWA)	500 ppm	400 ppm	
	CA ON: 200 ppm (TWA), 400 ppm (STEL)					
Appropriate engineering controls.....	Local exhaust should be used to maintain levels below the exposure limits.					
Respiratory/type.....	Wear a dust or mist respirator. Consult your personal protective equipment supplier for additional recommendations.					
Eye/type.....	Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.					
Gloves/ type.....	Chemical resistant gloves. Consult your personal protective equipment supplier for additional recommendations.					
Clothing/type.....	Wear chemical resistant clothing. Consult your personal protective equipment supplier for additional recommendations.					
Footwear/type.....	Wear chemical resistant safety boots. Consult your personal protective equipment supplier for additional recommendations.					
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Aerosol. Spray mist.
Colour.....	Not available.
Odour.....	Hydrocarbon.
Odour threshold (ppm).....	62 ppm. (Acetone).
Vapour pressure (mm Hg).....	108-185. (Acetone).
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Melting / Freezing point (deg C).....	-95.35 - -93.9 °C. (Acetone).
Solubility.....	Soluble in Water.
Initial boiling point / boiling range (deg C).....	>55 °C. (Liquid).
Evaporation rate.....	> 5.
Flash point (deg C), method.....	-18 - -17 °C. (Acetone).
Auto ignition temperature (deg C).....	465-560 °C. (acetone).
Upper flammable limit (% vol).....	14.3. (acetone).
Lower flammable limit (% vol).....	2.5. (acetone).
Partition coefficient — n-octanol/water.....	Not available.
% Volatile by volume.....	Not available.
VOC LBS/GAL less water.....	Not available.
Viscosity.....	Not available.
Relative Density (Specific Gravity).....	0.770-0.790.
Aerosol Flame Projection.....	>15 cm and <100 cm.
Flashback.....	Yes.
VOC Content.....	NMT 10.
NOTE.....	NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Product is stable under normal conditions of use.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Incompatible materials.....	Strong oxidizing agents. Strong acids.
Conditions to avoid, including static discharge, shock or vibration	Avoid heat, spark, open flames and other sources of ignition.
Hazardous decomposition products.....	Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	50,100 mg/m3 8 hours, rat	5,800 mg/kg (rat oral)
Carbon dioxide	No data	No data

PRODUCT: 19128 SPRAY GUN PAINT REMOVER AEROSOL**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Naphtha (petroleum), hydrotreated light	73680 ppm 4 hours rat	>5000 mg/kg (oral, rat) >3160 mg/mg (dermal, rabbit)
Isopropyl Alcohol	72600 mg/m3, rat (4 hr)	1870 mg/kg (oral, rat). 4059 mg/kg (dermal, rabbit)
Route of exposure.....	Eye contact. Skin contact. Inhalation. Ingestion.	
Symptoms related to the physical, chemical and toxicological characteristics	Irritation effects.	
Effects of acute exposure.....	No known significant effects.	
Serious eye damage/eye irritation.....	Causes serious eye irritation.	
Skin corrosion/irritation.....	Causes mild skin irritation. Prolonged contact may be more irritating.	
Respiratory Sensitization.....	Not expected to be a respiratory sensitizer.	
Skin Sensitization.....	Not expected to be a skin sensitizer.	
Carcinogenicity.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.	
Reproductive effects.....	No component of this product present at levels greater than or equal to 0.1% .	
Mutagenicity.....	No component of this product present at levels greater than or equal to 0.1% .	
STOT-SE.....	May cause drowsiness or dizziness. May cause respiratory irritation.	
STOT-RE.....	Not classified.	
Aspiration Hazard.....	May be fatal if swallowed and enters airways.	
Effects of chronic exposure.....	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil. This product contains the following substance which may also be hazardous for the environment: Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae: not available . Naphtha (CAS # 64742-49-0): Toxicity to fish: LC50 4.1 mg/L, 96 hrs; Toxicity to Daphnia: EC50 10 mg/L, 48 hrs; Toxicity to algae: EC50 11 mg/L, 72 hrs; NOEC 0.1 mg/L, 72 hrs. Isopropanol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs.
Bioaccumulative potential.....	No product data available.
Mobility in soil.....	No product data available.
Persistence and degradability.....	No product data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.
---	---

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1950 - AEROSOLS - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
DOT Classification (Road).....	UN1950 - AEROSOLS - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air).....	UN1950 - AEROSOLS - Class 2.1 - Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	On Domestic Substances List (DSL).
National Pollutant Release Inventory (NPRI)(CAS # 67-63-0 (Cat 1A & 5)).	
Environmental Emergency Regulations....	None listed in this product.
Categorization of the DSL.....	(CAS # 67-64-1). (CAS # 67-63-0). (CAS # 64742-49-0).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	

PRODUCT: 19128 SPRAY GUN PAINT REMOVER AEROSOL

SECTION 15: REGULATORY INFORMATION

Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Isopropyl alcohol.
 EPA hazardous air pollutants (HAPS) None known.
 40CFR63
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety .. 2024-11-15
 data sheet