PR

SAFETY DATA SHEET

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

PRODUCT: 20232 BUTYL TAPE 1/8 X 1/4 X 15

FORM

SECTION 01: IDENTIFICATION

Initial supplier identifier	Pro Form Products Ltd.
	604 McGeachie Drive
	Milton, Ontario L9T3Y5
	Tel (905) 878-4990 Fax (905) 878-1189
Product identifier	20232 BÚTYL TAPE 1/8 X 1/4 X 15
Recommended use and restrictions on	Automotive.
use	
Chemical family	Article.
Chemical family NFPA rating	Health: 0 Fire: 1 Reactivity: 0.
HMIS	H:0 F:1 R:0.
24 hour emergency number:	For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
5,	IN THE UNITED STATES CALL CHEMTRÉC 1-800-424-9300.
	** For medical emergencies contact your local poison control centre **

SECTION 02: HAZARD IDENTIFICATION

Signal Word	
Hazard Classification	Not classified.
Hazard Description	Not classified.
Note	Product is an article.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS

CAS #

WT. %

PRODUCT IS AN ARTICLE AND NOT A CHEMICAL

SECTION 04: FIRST-AID MEASURES

Eye contact Skin contact Inhalation	Flush for 15 minutes using plenty of water. If irritation persists seek medical attention. Wash skin with soap and water. If irritation persists, seek medical attention. No specific treatment is necessary since this material is not likely to be hazardous by inhalation.
Most important symptoms and effects,	Ingestion is unlikely. Contact a physician if unusual reaction is noted. May cause mild skin irritation. May cause slight eye irritation.
Additional information	In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media Specific hazards arising from the

hazardous product, such as the nature of any hazardous combustion products Special protective equipment andprecautions for fire-fighters

.. Carbon dioxide, dry chemical, foam. Treat as a petroleum fire.

Oxides of carbon (CO, CO2). Hydrocarbons. Toxic fumes.

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....

..... Wear recommended protective equipment. Pick up solids and put in a dust bin. Keep in a suitable, closed container for disposal.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling	Keep away from heat, sparks, and open flame. Handle in accordance with good industrial hygiene and safety practices. Employees should wash hands and face before eating or
Conditions for safe storage, including any incompatibilities	drinking. Store in a cool, dry and well ventilated area. Protect containers from physical damage. Do not store above 49C.



PRODUCT: 20232 BUTYL TAPE 1/8 X 1/4 X 15

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ATWA	CGIH TLV STEL	PEL	OSHA PEL STEL	NIOSH REL
Respiratory/type Eye/type		None required under norm Where contact with this ma eve irritation after repeated	aterial is possib	ole, eye protection is recommen	nded. May cause
Gloves/ type		Use of proper hygiene pra irritation after repeated or	ctices in the wo	contact. orkplace is recommended. Ma tact.	y cause skin
Clothing/type		repeated or prolonged con	itact.	nt dermal exposure. May cause	
Footwear/type Other/type		Safety boots per local regulation Educate and train employed	ulations. ees on the safe	e use and handling of the produ eating, drinking, or using toba	ct. Employees
Appropriate enginee	ring controls	Good general ventilation s	hould be suffic	ient to control airborne levels.	

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state Colour Odour threshold (ppm) Vapour pressure (mm Hg) Vapour density (air=1) PH Relative Density (Specific Gravity) Melting / Freezing point (deg C) Solubility Initial boiling point / boiling range (deg C). Evaporation rate Flash point (deg C), method Auto ignition temperature (deg C) Upper flammable limit (% vol) Lower flammable limit (% vol) Partition coefficient — n-octanol/water VOC (less water)	Black mastic, soft solid. Black. Faint. Characteristic odour. Not applicable. Not applicable. Not applicable. ~1.3. Not applicable. Not applicable. No data. Non volatile. No data.
---	---

SECTION 10: STABILITY AND REACTIVITY

Chemical stability
Reactivity
F USSIDIIILY OF HAZATUOUS TEACHORS
Conditions to avoid, including static
discharge, shock or vibration
Hazardous decomposition products

Stable at normal temperatures and pressures. Avoid heat, sparks and flames. Hazardous polymerization will not occur. Will not occur under normal temperature and pressure. Incompatible with strong solvents.

Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS		LC50	LD50
Route of exposure Effects of acute exposure Effects of chronic exposure Carcinogenicity of material	Carbon black has been sl finding to humans is unce Research on Cancer (IAF		animals. The relevance of this the International Agency for
Reproductive effects	carcinogen. None.		

SECTION 12: ECOLOGICAL INFORMATION

Persistence and degradability..... Not available.

Powered by



PRODUCT: 20232 BUTYL TAPE 1/8 X 1/4 X 15

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal . and methods of disposal, including any contaminated packaging

Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification	Not regulated.
DOT Classification (Road)	
IATA Classification (Air)	Not regulated.
IMDG Classification (Marine)	Not regulated.
Marine Pollutant	No.
Proof of Classification	In accordance v
	2 2014) 100 0

No.
In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July
2, 2014) - we certify that classification of this product is correct.

SECTION 15: REGULATORY INFORMATION

CEPA status	This is an article and not subject to the DSL.
SARA Title III Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories Section 313 EPA hazardous air pollutants (HAPS)	None.
40CFR63 California Proposition 65	are known to the State of California to cause cancer . (Carbon black - airborne, unbound
	particles of respirable size). (Silica, crystalline (airborne particles of respirable size). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: Telephone number: Disclaimer:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com. (800) 387-7981. DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date: Date of the latest revision of the safety data sheet	2021-11-15. 2018-05-10

