

Wax Based Permanent Rustproofing

21004, 21006, 21010, 21026, 21028, 21032

Wax based rustproofing offers a durable protection to prevent corrosion. This formulation will creep and penetrate tight areas, will repel humidity and protect against corrosion. This coating will transform into a tacky film, sealing off the surface treated with a premium quality protection against corrosion. This coating will not drip or weep but will remain tacky and offer superior resistance to road abrasion and weathering.

PRODUCT	SIZE	COLOR
21004	U.S. Gallon (3.78 L)	Black
21006	5 U.S. Gallons (18.9 L)	Black
21008	55 U.S. Gallons (205 L)	Black
21026	U.S. Gallon (3.78 L)	Amber
21028	5 U.S. Gallons (18.9 L)	Amber
21032	55 U.S. Gallons (205 L)	Amber

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metal

ADVANTAGES:

- Never becomes brittle or loses adhesion
- Protects against rust, salt and corrosion
- Creeps and penetrates
- Resist abrasion

DIRECTIONS FOR USE:

1. Clean the surface and remove rust.
2. Allow four hours before exposing to wet road conditions.
3. This product is not recommended for application in temperatures below 60°F (16°C).

Caution: For metal applications only! Do not apply to SMC, fiberglass, plastic or rubber components. For metal verification, use a magnet.

Product Data Sheet

TECHNICAL DATA:

	21004, 21006, 21010	21026, 21028, 21032
Physical State	Liquid	
Color:	Black	Amber
Odour:	Light solvent, sweet odour	
Solubility :	Insoluble in water	
Flash point:	60°C (140°F)	
Auto ignition temperature:	>100°C (212°F)	
VOC	4.32 lbs/gal - 518 g/L	2.63 lbs/gal - 315 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.