

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

#### 21210 DRIPLESS OIL ANNUAL RUSTPROOFING (BLACK) PRODUCT:

#### **SECTION 01: IDENTIFICATION**

Initial supplier identifier..... Pro Form Products Ltd. 604 McGeachie Drive

Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... 21210 DRIPLESS OIL ANNUAL RUSTPROOFING (BLACK)

Recommended use and restrictions on ... Rust proofing. This product should not be used for any other purpose other than the ones described in this section.

Mixture. Health: 2 Fire: 2 Reactivity: 0.

Chemical family..... NFPA rating..... HMIS.....

H: 2 F: 2 R: 0.

24 hour emergency number:.....

For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.

\*\* For medical emergencies contact your local poison control centre \*\*.

#### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... WARNING. Hazard Classification..... Carcinogenicity — Category 2. Hazard Description..... Precautionary Statements H351 This product contains ingredients that are suspected of causing cancer. P201 Obtain special instructions before use. P202 Do not handle this product until all Prevention..... safety instructions have been read and understood. P280 Wear protective gloves and eye protection. P308 + P313 If exposed or concerned, get medical advice/attention. Response ..... P405 Store locked up. Storage..... Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations. Other hazards..... None known. This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS						
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %				
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	30-60				
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	30-60				
Residual oils (petroleum), solvent-refined	64742-01-4	30-60				
Propylene carbonate	108-32-7	1-5				
Carbon Black	1333-86-4	1-5				

# **SECTION 04: FIRST-AID MEASURES**

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
least 15 minutes. Consult a physician if irritation continues. Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. If irritation persists, seek medical attention.
If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
difficult, give oxygen, obtain medical attention.  Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Seek medical assistance as soon as possible.

# PRODUCT: 21210 DRIPLESS OIL ANNUAL RUSTPROOFING (BLACK)

## **SECTION 04: FIRST-AID MEASURES**

Most important symptoms and effects, ..... whether acute or delayed Additional information......

May cause eye irritation. May cause slight eye irritation. This product contains ingredients that may cause cancer.

Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

modical additionates are provided a copy of the safety data of

#### **SECTION 05: FIRE-FIGHTING MEASURES**

"Alcohol" foam, CO2, dry chemical. Water spray. Do not use solid water streams or water jet.

Non-flammable. May be combustible at high temperatures.

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes.

#### **SECTION 06: ACCIDENTAL RELEASE MEASURES**

Environmental precautions.....

Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.

Personal precautions, protective equipment Do not touch spilled material. Wear appropriate personal protection equipment and emergency procedures

Methods and materials for containment and cleaning up

Ventilate. Eliminate all sources of ignition. Cover spill with inert absorbant material. Sweep up and place in container for proper disposal. Always wear ppe during cleanup. Dispose of waste material in accordance with all Local, Provincial and Federal Regulations.

# **SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....

Ventilate area. Avoid contact with skin and eye. Avoid breathing vapours or mist. Keep away from heat, sparks, and open flame. Wear appropriate protective equipment. Keep container closed when not in use. Do not eat, drink or smoke while using this product. Wash hands and arms after handling. Handle in accordance with good industrial hygiene and safety practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from sunlight. Store in a cool, dry and well ventilated area. Store away from incompatible materials. Incompatible materials include, but not limited to:. Strong oxidizing agents.

## **SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	CGIH TLV STEL	OSH. PEL	A PEL STEL	NIOSH REL		
Distillates (petroleum), solvent-refined heavy paraffinic	5 mg/m3 (8 hr)	Not established	5 mg/m3 (8 hr)	Not established	Not established		
Distillates (petroleum), hydrotreated heavy paraffinic	5 mg/m3		5 mg/m3		10 mg/m3 (STEL)		
Residual oils (petroleum), solvent-refined	5 mg/m3	Not established	5 mg/m3	Not established	Not established		
Propylene carbonate	Not established		Not established		Not established		
Carbon Black	3 mg/m3	Not established	3.5 mg/m3	Not established	3.5 mg/m3		
CA ON: 3 mg/m3 (Inhalable) TWA							
Appropriate engineering controls		Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.					
Personal Protective Equipment							
Respiratory/type	piratory/type			e and/or filter may ipment supplier for			
Eye/type		Safety glasses with side-s	e-shields. Chemical safety goggles and full faceshield if a splash our personal protective equipment supplier for additional				
Gloves/ type Chemical resista			oves. Nitrile rubber. Consult your personal protective equipment recommendations.				

# PRODUCT: 21210 DRIPLESS OIL ANNUAL RUSTPROOFING (BLACK)

# **SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Other/type...... Eye wash facility and emergency shower should be in close proximity.

## SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Semi-solid grease. Colour..... Black. Odour..... Characteristic odour. Odour threshold (ppm)..... 100 ppm. Not applicable. pH..... -10. >150 Solubility...... Insoluble in water. Evaporation rate..... <1. (butyl acetate = 1). Vapour pressure (mm Hg)..... <1 kPa @ 25C. Not flammable. Not available. Upper flammable limit (% vol)...... Lower flammable limit (% vol)..... Not available. Not available. Auto ignition temperature (deg C)..... 350°C. Vapour density (air=1)......Relative Density (Specific Gravity)..... >1. 0.9. kg/L. (water = 1). Partition coefficient — n-octanol/water.....

Decomposition temperature..... Not available. Not available. Not available. Not available. Not available.

#### **SECTION 10: STABILITY AND REACTIVITY**

Chemical stability...... Stable at normal temperatures and pressures.

Reactivity ...... No dangerous reaction known under conditions of normal use.

Possibility of hazardous reactions....... Hazardous polymerization will not occur. Conditions to avoid, including static ....... Incompatible with strong oxidizers.

discharge, shock or vibration

## **SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS		LC50	LD50		
Distillates (petroleum), solvent-refined heavy paraffinic		2.18 mg/L 4 hours rat	>5,000 mg/kg rat oral		
Distillates (petroleum), hydrotreated heavy paraffinic		Not available	>5000 mg/kg (skin, rabbit). >15000 mg/kg (oral, rat)		
Residual oils (petroleum), solvent-refined		2.18 mg/L (4 hr, rat)	>5000 mg/kg (oral, rat)		
Propylene carbonate		Not avaialble	>5000 mg/kg (oral, rat) >2000 mg/kg (dermal, rat)		
Carbon Black		Not available	>10,000 mg/kg (oral rat ) 3,000 mg/kg (dermal rabbit)		
Route of exposure Eye contact	Eye contact. Skin contact. Inhalation. Ingestion. May cause redness and irritation to the eyes. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.				
Skin contact	Prolonged contact may case irritation and/or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404): tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.  Inhalation of aerosols or oil mist may cause chemical pneumonia with fever, cough and				
IngestionAcute Toxicity Estimate (ATE)	shortness of breath, or pulmonary edema.  May cause gastrointestinal irritation and diarrhea.  ATEMix: Oral and Skin >2000 mg/kg; Inhalation >20 mg/L/4h (vapours); Inhalation >5 mg/L/4h (dust and mist).  Not expected to be a skin sensitizer.				
Respiratory Sensitization	on				

# PRODUCT: 21210 DRIPLESS OIL ANNUAL RUSTPROOFING (BLACK)

# **SECTION 11: TOXICOLOGICAL INFORMATION**

IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans. Carcinogenicity.....

Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by the International Agency for

Research on Cancer (IARC). .

Reproductive effects..... No component of this product present at levels greater than or equal to 0.1%. Mutagenicity.....

No component of this product present at levels greater than or equal to 0.1%.

STOT-SE..... Does not meet the criteria for this classification. Does not meet the criteria for this classification.

## **SECTION 12: ECOLOGICAL INFORMATION**

Environmental.....

Do not allow to enter waters, waste water or soil. Biodegradable (<30% in 28 days). Not readily biodegradable (OECD 301B, IUCLID). Persistence and degradability.....

Mobility in soil..... Insoluble in water. Low mobility. Will adsorb to soil particles. This substance will pollute the

water and contaminates the soil.

Bioaccumulative potential..... Some potential to bioaccumulate. (Log Kow of >3 and/or BCF >500).

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal. and methods of disposal, including any contaminated packaging

Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

#### **SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... Not regulated. DOT Classification (Road)..... Not regulated. IATA Classification (Air)..... Not regulated. IMDG Classification (Marine)..... Not regulated.

Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July

2, 2014) - we certify that classification of this product is correct. .

# **SECTION 15: REGULATORY INFORMATION**

CEPA status..... On Domestic Substances List (DSL).

National Pollutant Release Inventory (NPRI)None listed in this product. Environmental Emergency Regulations.... None listed in this product.

Categorization of the DSL..... Some components met the criteria under subsection 73(1) of CEPA during categorization

of the DSL. Please check to see if this affects your company. (CAS # 1333-86-4).

TSCA inventory status......OSHA..... All components are listed.

This product is considered hazardous under the OSHA Hazard Communication Standard.

SARA Title III

Section 302 - extremely hazardous ........ None.

substances

Section 311/312 - hazard categories...... Section 313..... Immediate health. Delayed Health.

None. EPA hazardous air pollutants (HAPS) ...... None.

40CFR63

\*WARNING: This product contains a chemical known to the State of California to cause cancer. (Carbon black (C)). For more information, go to www.P65Warnings.ca.gov. California Proposition 65.....

## **SECTION 16: OTHER INFORMATION**

REGULATORY AFFAIRS. (800) 387-7981. Prepared by: .....

Telephone number:.....

DISCLAIMER: All information appearing herein is based upon data obtained from Disclaimer:....

experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not

relate to its use in combination with any other material or in any other process. 2024-09-10

Date of the latest revision of the safety ...

data sheet

