

A fast drying, heavy bodied rubber and asphalt coating for sealing, sound deadening, hiding repairs and rustproofing. Provides excellent adhesion to bare or painted metals and plastics. Also works as a sealant for house gutters, fence posts and trees after pruning. Should not be used as a Rocker Panel protector. Paintable Rubberized Undercoat will cause the paint to decolor and the asphalt may bleed through.

PRODUCT	SIZE
----------------	-------------

22100	15.5 oz (439 g)
22102	19.75 oz (560 g)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metals
- Plastics
- House gutters
- Fence posts
- Trees after pruning

ADVANTAGES:

- Resists abrasion
- Remain flexible
- Sound deadens
- Heavy bodied

DIRECTION FOR USE:

1. Remove all rust, wax, silicone, grease, dirt and other contaminants. Surface must be clean and dry. Mask off area to avoid overspray.
2. Shake can for 1 minute after mixing ball moves freely. Note: Insufficient mixing may cause permanent plugging of the sprayhead.
3. Spray approximately 10z to 12 inches (25-30 cm) from the surface. Distance will determine the texture.
4. To assure that the entire contents will be dispensed, rotate the spray head so the spray opening is in line with the dot on the can rim.
5. Apply a medium and even coat.
6. When finished, turn can upside down and spray about 3 seconds to clean out spray head.

Product Data Sheet

TECHNICAL DATA:

	22100, 22102
Physical State	Aerosol
Color:	Black
Odour:	Hydrocarbon odour
Solubility :	Slightly soluble in water
Flash point:	23°C / 73.4°F (liquid)
Auto ignition temperature:	>232°C (449.6°F)
VOC	3.09 lbs/usg - 370.27 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.