



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PFUS30040 2:1 CLEARCOAT

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PFUS30040 2:1 CLEARCOAT

Recommended use and restrictions on .. Clearcoat.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritant 2. Acute Toxicity 4. Reproductive Toxicity — Category 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361 Suspected of damaging fertility or the unborn child.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P240 Ground and bond container and receiving equipment. P233 Keep container tightly closed. P242 Use only non-sparking tools. P241 Use explosion proof equipment. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P264 Wash hands thoroughly after handling. P261 Avoid breathing mists, vapours and sprays. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace.

Response P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P302 + P352 - If on skin: wash with plenty of water. P321 - For specific treatment see section 4 on this SDS. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P308 + P313 If exposed or concerned, get medical advice/attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|----------------------------|----------|-------|
| n-Butyl Acetate | 123-86-4 | 6-19 |
| Acetone | 67-64-1 | 10-15 |
| 4-Chlorobenzotrifluoride | 98-56-6 | 1-5 |

PRODUCT: PFUS30040 2:1 CLEARCOAT**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| | | |
|--|------------|------|
| n-Amyl Propionate (Pure) | 624-54-4 | 1-5 |
| Methyl N-Amyl Ketone | 110-43-0 | 1-5 |
| Xylene | 1330-20-7 | 1-5 |
| Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate | 41556-26-7 | <0.5 |

SECTION 04: FIRST-AID MEASURES

| | |
|-----------------------------|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Additional information..... | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable and unsuitable extinguishing media | "Alcohol" foam, CO2, dry chemical. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO2). Oxides of nitrogen. Hydrogen chloride. hydrogen flouride. Hydrocarbon fumes and smoke. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-----------------|---|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). |
|-----------------|---|

SECTION 07: HANDLING AND STORAGE

| | |
|--|---|
| Precautions for safe handling..... | Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|-----------------|-------------|-------------------|-----------|------------------|------------------------|-------|
| n-Butyl Acetate | 50 ppm | 150 ppm | 150 ppm | 200 ppm | 150 ppm / STEL 200 ppm | |
| Acetone | 250 ppm TLV | 500 ppm | 1,000 ppm | Not established | 250 ppm | |

CA ON: 50ppm (TWA), 150ppm (STEL)

PRODUCT: PFUS30040 2:1 CLEARCOAT**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS | ACGIH TLV | | OSHA PEL | | NIOSH |
|---|---|-----------------|-----------------|-----------------|-----------------|
| | TWA | STEL | PEL | STEL | |
| | CA ON: 500ppm (TWA); 750ppm (STEL) | | | | |
| 4-Chlorobenzotrifluoride | Not established | Not established | Not established | Not established | Not established |
| n-Amyl Propionate (Pure) | No data | No data | No data | No data | No data |
| Methyl N-Amyl Ketone | 50 ppm | Not established | 100 ppm | 465 mg/m3 TWA | Not established |
| | ON OEL: 25 ppm; 115 mg/m3 (TWA) | | | | |
| Xylene | 50 ppm | 150 ppm | 100 ppm TWA | Not established | Not established |
| | CA ON: 100ppm (TWA); 150ppm (STEL) | | | | |
| Bis (1,2,2,6,6-Pentamethyl-4- Piperidyl) Sebacate | Not established | Not established | Not established | Not established | Not established |
| Personal Protective Equipment | | | | | |
| Eye/type..... | Liquid chemical goggles. | | | | |
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. | | | | |
| Gloves/ type..... | Chemical resistant gloves. | | | | |
| Clothing/type..... | Wear adequate protective clothes. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Other/type..... | Emergency showers and eye wash stations should be available. | | | | |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|------------------------|
| Appearance/Physical state..... | Liquid. |
| Colour..... | Clear. |
| Odour..... | Solvent odour. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | Not available. |
| Vapour density (air=1)..... | >1. |
| pH..... | No data. |
| Relative Density (Specific Gravity)..... | 8.35 lbs/USG; 1.0. |
| Melting / Freezing point (deg C)..... | Not available. |
| Solubility..... | No data. |
| Initial boiling point / boiling range (deg C)..... | > 56 °C. |
| Evaporation rate..... | Not available. |
| Flash point (deg C), method..... | -18°C. (estimated). |
| Auto ignition temperature (deg C)..... | >367. |
| Upper flammable limit (% vol)..... | 12.6. |
| Lower flammable limit (% vol)..... | 0.9. |
| Partition coefficient — n-octanol/water..... | Not available. |
| VOC (less water)..... | 307 g/L - 2.56 lb/gal. |
| Viscosity..... | 18 sec Zahn #2. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Conditions to avoid, including static discharge, shock or vibration | Keep away from heat. Incompatible with strong oxidizers. Strong acids. Strong bases. |
| Hazardous decomposition products..... | By fire: Oxides of carbon (CO,CO2). Dense black smoke. Oxides of nitrogen. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT: PFUS30040 2:1 CLEARCOAT**SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS | LC50 | LD50 |
|--|---|---|
| n-Butyl Acetate | >33 mg/L vapour, (rat) dust/mist | 5.2 mg/L 10760 mg/kg (rat, oral) 14112 mg/kg (rabbit, dermal) |
| Acetone | 50,100 mg/m ³ 8 hours, rat | 5,800 mg/kg (rat oral) |
| 4-Chlorobenzotrifluoride | 4479 ppm | >6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal) |
| n-Amyl Propionate (Pure) | No data | LD50 >13,984 mg/kg oral rat |
| Methyl N-Amyl Ketone | Not Available | 1,670 mg/kg rat oral 12,600 mg/kg rabbit dermal |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate | Not Available | 2369-3920 mg/kg (oral rat), >2000 mg/kg (dermal rabbit) |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Contact with eyes may cause irritation. Causes skin irritation. Inhalation of high vapour may cause central nervous system effects, dizziness, headache, nausea, or loss of coordination. | |
| Effects of chronic exposure..... | Chronic exposure to organic solvent vapours have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. A substance in this product may cause skin sensitization after prolonged or repeated contact. | |
| Carcinogenicity of material..... | None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen. | |
| Sensitizing capability of material..... | May cause sensitization by skin contact. | |
| Reproductive effects..... | Acetone has been shown to cause reproductive effects in rats by ingestion and inhalation. High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. | |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|--|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Empty containers must be handled with care due to product residue. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. |
|---|--|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters. |
| IATA Classification (Air)..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II. |
| IMDG Classification (Marine)..... | UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|--|
| WHMIS 1988 classification..... | B2. D2A. D2B. |
| CEPA status..... | On Domestic Substances List (DSL). |
| TSCA inventory status..... | Not determined. |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health, fire hazard. |
| Section 313..... | Xylene. |
| EPA hazardous air pollutants (HAPS) | Xylene. Benzene. Toluene. |
| 40CFR63 | |

PRODUCT: PFUS30040 2:1 CLEARCOAT

SECTION 15: REGULATORY INFORMATION

California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Toluene). (Benzene (D)). *WARNING: This product contains a chemical known to the State of California to cause cancer. (Benzene). (Ethyl benzene).

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Review Date:..... 2021-11-08.
 Date of the latest revision of the safety .. 2017-07-27
 data sheet