

Surface cleaner to be used as a fast, mild, solvent cleaner to remove silicone, wax and grease or any other contaminants prior to sanding. Flashes quickly leaving no residue. Can be used on bare metal, existing finishes and cured primed surfaces. Safe to use with pump & spray bottle. Note: It has to be transferred to a hand-held spray bottle prior to use.

PRODUCT	SIZE
PF 693	946 ml (U.S. Quart)
PF 693-1	3.78 L (U.S. Gallon)
PF 693-5	18.9 L (5 U.S. Gallons)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES

- Primed or painted metal
- Bare metal

ADVANTAGES

- Cleans bare metal, existing finishes and primed surfaces
- Not as strong as PF 605, PF 621 and PF 600

DIRECTIONS FOR USE:

1. Pour into a 4 fl oz container. Use prior to sanding. Spray surface liberally with Wax & Grease Remover (Fast Mild) from hand held spray bottle.
2. Wipe dry while the surface is still wet.
3. Always wipe dry in the same direction, changing cloths as one cloth will merely shift rather than remove grease.

Caution: This product is not recommended for use on plastic or fibreglass, over freshly painted surfaces or over fresh primers-sealers. Soaked wipers should not be allowed to remain on finished surfaces. Dispose of cloth safely to avoid risk of spontaneous combustion fire.

TECHNICAL DATA:

	PF 693, PF 693-1, PF 693-5
Physical State	Liquid
Color:	Clear, colourless
Odour:	Mild odour, Petroleum

Solubility :	Negligible
Flash point:	-8°C (18°F)(estimate; lowest flash point ingredient)
Auto ignition temperature:	282°C (540°F)
VOC LBS/GAL less exempt volatiles:	708.19 g/L • 5.91 lbs/gal

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.