

A tough, flexible and textured coating that can be painted. It will provide good protection against road abrasion and weathering. Excellent adhesion to metals and plastics.

PRODUCT	SIZE	COLOR
PF 718C	850 ml (28.7 fl oz)	Black
PF 718-1C	3.78 L (U.S. Gallon)	Black
PF 718-5C	18.9 L (5 U.S. Gallons)	Black

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metals
- Plastics

ADVANTAGES:

- Resists abrasion
- Remains flexible
- High solids
- Will not crack

DIRECTIONS FOR USE:

All substrates must be degreased and sanded. Surface must be free of rust, wax, silicone, grease, dirt and other contaminants. For best results, use when temperature of the can and surface is between 21°C and 24°C (70°F and 75°F).

1. Clean metal surfaces with PF 605 Wax and Grease Remover (Strong). Clean plastic surfaces with PF 606 Plastic Parts Cleaner.
2. Shake can well before using.
3. Using a Syphon Gun at 50 to 80 psi, adjust air pressure and spray approximately 25 to 30 cm (10 to 12 inches) from surface. Distance and pressure at the gun will determine texture.

DRYING TIME: Approximately 90 minutes.

CLEANING INSTRUCTIONS: Clean equipment immediately after use with lacquer thinner.

TECHNICAL DATA:

	PF 718C, PF 718-1C, PF 718-5C
Physical State	Liquid
Color:	Black
Odour:	Solvent odour. Camphor-like.

Solubility :	Negligible
Flash point:	4°C (39.2°F) (estimate; lowest flash point ingredient)
Auto ignition temperature:	> 232°C (> 449.6°F)
VOC:	1.7 lb/usg • 203.7 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.