

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

PRODUCT: PB1201-5 ENGINE BLOCK DEGREASER

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189 Product identifier..... PB1201-5 ENGINE BLOCK DEGREASER Recommended use and restrictions on ... Automotive. This product should not be used for any other purpose other than the ones described in this section. Chemical family..... Mixture. Health: 2 Fire: 2 Reactivity: 0. NFPA rating..... HMIS..... H: 2 F: 2 R: 0. For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.

** For medical emergencies contact your local poison control centre **. 24 hour emergency number:....

SECTION 02: HAZARD IDENTIFICATION



Signal Word	DANGER.
Signal WordHazard Classification	Flammable Liquid 3. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Serious
	Eye Damage — Category 1.
Hazard Description	H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an
·	allergic skin reaction. H318 Causes serious eye damage.
Prevention	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233
	Keep container tightly closed. P240 Ground and bond container and receiving equipment.
	P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take
	precautionary measures against static discharge. P261 Avoid breathing mists, vapours and
	sprays. P264 Wash thoroughly after handling. P272 Contaminated work clothing should not
	be allowed out of the workplace. P280 Wear protective gloves and eye protection.
Response	P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 +
	P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse
	thoroughly with water and use safety shower . P305 + P351 + P338 If in eyes rinse
	cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing until medical help arrives. P310 - Immediately call your local poison
	control centre. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off
	contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs,
	get medical advice/attention.
Storage	P403 + P235 Store in well ventilated area. Keep cool.
Storage Disposal	P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Note	This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %	
Alcohol ethoxylate	Confidential (HMIRA #9608)	1-5	
Alkylaryl sulfonate	Confidential (HMIRA #9608)	1-5	
N-N-dimethyl 9-decenamide	1356964-77-6	1-5	
D-Limonene	5989-27-5	0.5-1.5	
Sodium Carbonate	497-19-8	0.1-1	

<<The actual concentration(s) withheld as a trade secret>> .



PRODUCT: PB1201-5 ENGINE BLOCK DEGREASER

SECTION 04: FIRST-AID MEASURES

Eye contact	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact	Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. If irritation persists, seek medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion	Rinse mouth with water. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Get medical attention.
Most important symptoms and effects, whether acute or delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct
Additional information	contact with eyes may cause temporary irritation. Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media Specific hazards arising from the

Specific hazards arising from thehazardous product, such as the nature of any hazardous combustion products Special protective equipment andprecautions for fire-fighters

"Alcohol" foam, CO2, dry chemical. Water fog. Do not use water in a jet.

During fire, gases hazardous to health may be formed. The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Leak/spill.....

Keep away from heat, sparks and flames. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

Personal precautions, protective equipment and emergency procedures

Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....

Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities

Store in a cool and dry place, for product integrity. Keep away from heat, sparks, and open flames. Keep container closed when not in use.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA AC	GIH TLV STEL	OS PEL	HA PEL STEL	NIOSH REL
Alcohol ethoxylate	Not established				
Alkylaryl sulfonate	Not established				
N-N-dimethyl 9-decenamide	Not Established				
D-Limonene	Not established				
Sodium Carbonate	Not Established				

PRODUCT: PB1201-5 ENGINE BLOCK DEGREASER

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protective Equipment	
Respiratory/type	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator
Eye/type	when contaminant levels exceed the recommended exposure limits. Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard
Gloves/ type	exists. Wear skin protection equipment. The selection of skin protection equipment depends on
310 v 63/ typo	the nature of the work to be performed.
Clothing/type	Wear adequate protective clothes.
Footwear/type	Safety boots per local regulations.
Other/type	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.
Appropriate engineering controls	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air
	contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Colour	quid. ght yellow. clear to slightly hazy. itrus odour. Orange. ot available. kaline. 0 °C. 93.3 °C. 7.5 C. (estimate; lowest flash point ingredient). ot available. flammable liquid. ot available. ot data. 99 lbs/USG.
--------	--

SECTION 10: STABILITY AND REACTIVITY

Sensitizing capability of material.....

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Alcohol ethoxylate	Not determined	Not determined
Alkylaryl sulfonate	Not determined	Not determined
N-N-dimethyl 9-decenamide	Not Available	550 mg/kg (oral, rat)
D-Limonene	Not Available	>5,000 mg/kg Rat oral >5,000 mg/kg Rabbit dermal
Sodium Carbonate	Not Available	2800 mg/kg Rat Oral
Route of exposure Effects of acute exposure Effects of chronic exposure	 Skin contact. Eye contact. Ingestion. Can cause moderate skin irritation. Causes serious eye irritation. Prolonged or repeated exposure may result in skin sensitization. 	

May cause sensitization by skin contact.

PRODUCT: PB1201-5 ENGINE BLOCK DEGREASER

SECTION 11: TOXICOLOGICAL INFORMATION

D-Limonene is listed as a Group 3 Carcinogen by IARC; not classifiable as to its Carcinogenicity of material.....

carcinogenicity to humans

Reproductive effects..... No data on reproductive effects were found in the literature sources consulted.

SECTION 12: ECOLOGICAL INFORMATION

H411 Toxic to aquatic life with long lasting effects.

Persistence and degradability..... Readily biodegradable.

Other adverse effects..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal. and methods of disposal, including any contaminated packaging

Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Empty containers must be handled with care due to product residue.

SECTION 14: TRANSPORT INFORMATION

UN1993 - FLAMMABLE LIQUID, N.O.S. (d-Limonene), Class 3, PG III. Limited Quantity TDG Classification..... Index: 5 L. This product is a flammable liquid, Class 3, Packing Group III material with a

flash point >37.8C and is exempt from the application of these regulations in non-bulk (<

450L) packaging as per TDG 1.33. UN1993 - FLAMMABLE LIQUID, N.O.S. (d-Limonene), Class 3, PG III. Refer to 49CRF DOT Classification (Road).....

172.101 for additional non-bulk packaging requirements. With a flash point > 38C, this product may be reclassified as a combustible liquid and is exempt from application of the

regulations in non-bulk packaging (< 450L) as per DOT 173.150 (f)(1)&(2). UN1993 - FLAMMABLE LIQUID, N.O.S. (d-Limonene), Class 3, PG III. Limited Quantity. IATA Classification (Air).....

Do not ship by air without checking appropriate IATA regulations.
UN1993 - FLAMMABLE LIQUID, N.O.S. (d-Limonene), Class 3, PG III. Limited Quantity.

IMDG Classification (Marine)..... Check IMDG regulations for limited quantity exemptions.

Marine Pollutant..... Potential marine pollutant.

In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July Proof of Classification.....

2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

Hazardous Materials Information Review . Claim #9608; April 11, 2016.

CEPA status.....

TSCA inventory status.....

OSHA.....

SARA Title III

Section 302 - extremely hazardous

substances

Section 311/312 - hazard categories...... Section 313.....

EPA hazardous air pollutants (HAPS)

40CFR63

California Proposition 65.....

On Domestic Substances List (DSL).

All components are listed.

This product is considered hazardous under the OSHA Hazard Communication Standard.

Immediate health. Fire hazard.

None.

None.

None.

! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm.

(Ethylene glycol (ingested)). (Methanol). www.P65Warnings.ca.gov. For more information, go to

SECTION 16: OTHER INFORMATION

REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com. Prepared by:

(800) 387-7981. Telephone number:.....

DISCLAIMER: All information appearing herein is based upon data obtained from Disclaimer:..... experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not

relate to its use in combination with any other material or in any other process. 2021-11-15.

Review Date:..... Date of the latest revision of the safety ...

data sheet

2018-10-22

