

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

PB 2001-55 ACID FREE WHEEL CLEANER PRODUCT:

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd. 604 McGeachie Drive

Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PB 2001-55 ACID FREE WHEEL CLEANER

Recommended use and restrictions on ...

Cleaner. for industrial use only-keep out of reach of children .

Chemical family.....

Health: 3 Fire: 1 Reactivity: 0.

NFPA rating..... HMIS..... H: 3 F: 1 R: 0.

For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.

** For medical emergencies contact your local poison control centre **. 24 hour emergency number:....

SECTION 02: HAZARD IDENTIFICATION



DANGER.
DANGER. Serious Eye Damage — Category 1. Skin Irritation — Category 2. Skin Sensitizer —
Category 1. Flammable Liquid 4.
H227 Combustible liquid. H315 Causes skin irritation. H317 May cause an allergic skin
reaction. H318 Causes serious eye damage.
P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P261
Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P272
Contaminated work clothing should not be allowed out of the workplace. P280 Wear
protective gloves and eye protection.
P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P305 +
P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact
lenses, if present and easy to do. Continue rinsing until medical help arrives. P310 -
Immediately call your local poison control centre. P302 + P352 - If on skin: wash with
plenty of water. P333 + P313 If skin irritation or rash occurs, get medical advice/attention.
P362 + P364 - Take off contaminated clothing and wash before reuse.
P403 Store in a well ventilated area.
P501 Dispose all unused, waste or empty containers in accordance with local regulations.
This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %	
Sodium hydroxide	1310-73-2	1-5	
Propylene glycol monobutyl ether	5131-66-8	1-5	
Disodium metasilicate	6834-92-0	0.5-1.5	
Disodium cocoampho dipropionate	68604-71-7	0.1-1	

<<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: FIRST-AID MEASURES

Check for and remove any contact lenses, if safe and easy to do so. Immediately flush eyes with running water for a minimum of 30 minutes preferably up to 60 minutes. Get medical attention immediately.



SECTION 04: FIRST-AID MEASURES

Remove all contaminated clothing and immediately wash the exposed areas with copious Skin contact..... amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. If ingestion is suspected, contact physician or poison control center immediately. If Ingestion..... spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Most important symptoms and effects, Causes severe skin burns and eye damage. Symptoms may include stinging, tearing, whether acute or delayed redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Can cause skin sensitization. Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media

"Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used.

Special protective equipment andprecautions for fire-fighters

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

Unusual fire / explosion hazards.....

Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source.

..... Oxides of

Specific hazards arising from thehazardous product, such as the nature of any hazardous combustion products

Oxides of carbon (CO, CO2). Hydrocarbon fumes and smoke.

SECTION 06: ACCIDENTAL RELEASE MEASURES

ammonia (3-8%) and detergent (2%).

Personal precautions, protective equipment and emergency procedures

Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways.

Methods and materials for containment and cleaning up

Dike area to contain the spill, prevent runoff from going into drains, absorb residual material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....

Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.

Conditions for safe storage, including any incompatibilities

Keep container closed when not in use. Store away from all sources of heat and ignition. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA ACG	IH TLV STEL	OS PEL	HA PEL STEL	NIOSH REL
Sodium hydroxide Propylene glycol monobutyl ether	2 mg/m3 Not Established	Not Established Not Established	2 mg/m3 Not Established	Not Established Not Established	Not Established Not Established
Disodium metasilicate	2 mg/m3 (analogy)	Not Established	Not Established	Not Established	Not Established



SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

	ACGIH TI	_V		- L		NIOSH
INGREDIENTS	IIVVA	rel Pel	·1 S	TEL	REL	
	1	·	_			

Disodium cocoampho dipropionate

Not Established

Not Established

Not Established

Not Established

Not Established

Appropriate engineering controls.....

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about

adequate ventilation.

Personal Protective Equipment

Respiratory/type.....

Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.

Chemical safety goggles and full faceshield if a splash hazard exists.

Eye/type..... Gloves/ type..... Wear skin protection equipment. The selection of this equipment depends on the nature of

the work to be done. Neoprene. Nitrile rubber. Wear adequate protective clothes.

Clothing/type..... Safety boots per local regulations. Footwear/type.....

Emergency showers and eye wash stations should be available. Employees should wash Other/type.....

their hands and face before eating, drinking, or using tobacco products.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid. Milky white. Colour..... Odour..... Mild odour. Odour threshold (ppm)..... Not available. No Data. pH..... Melting / Freezing point (deg C)..... 0°C Initial boiling point / boiling range (deg C). Flash point (deg C), method..... 100°C 62 C. (estimate; lowest flash point ingredient). Evaporation rate..... Similar to water. Flammability (solids and gases)..... Not applicable. 1.1. No data. Vapour density (air=1)..... Similar to water. Relative Density (Specific Gravity)..... 8.43 lb/usg - 1.01 g/mL. Solubility.....Partition coefficient — n-octanol/water..... Auto ignition temperature (deg C)..... Soluble. No data. > 260°C Decomposition temperature..... Not available. Viscosity..... No data VOC (less water)..... 0.02 lbs/USG.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong

oxidizing agents.

Chemical stability..... Stable at normal temperatures and pressures. Possibility of hazardous reactions..... Hazardous polymerization will not occur.

Conditions to avoid, including static discharge, shock or vibration

Hazardous decomposition products......

Incompatible materails.....

Keep away from heat. Incompatible with strong oxidizers.

Strong oxidizing agents. Aldehydes.

No hazardous decomposition products when stored and handled correctly.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Sodium hydroxide	hydroxide No Data 104-340 mg/k mg/kg derma	
Propylene glycol monobutyl ether	>651 ppm 4 Hr Rat	2,700 mg/kg Rat Oral >2,000 mg/kg Rat Skin
Disodium metasilicate	> 2.06 g/m3	1153 mg/kg (oral, rat) >5000 mg/kg (dermal, rat)



SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

Disodium cocoampho dipropionate No Data No Data

Route of exposure..... Eye contact. Skin contact. Inhalation.

Hazardous in contact with skin, by ingestion, and by inhalation. Causes serious eye Effects of acute exposure..... irritation. Inhalation may cause respiratory tract irritation. Inhalation of high vapour may

cause central nervous system effects, dizziness, headache, nausea, or loss of

coordination.

Breathing high concentrations of vapour may cause anesthetic effects and serious health Effects of chronic exposure.....

effects. Prolonged or repeated skin contact may cause drying or cracking of skin.

Intentional misuse by deliberately concentrating and inhaling this product may be harmful

or fatal.

No component of this product present at levels greater than or equal to 0.1% is identified Carcinogenicity of material.....

as probable, possible or confirmed human carcinogen by IARC or ACGIH. Reproductive effects..... No component of this product present at levels greater than or equal to 0.1%.

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Do not allow to enter waters, waste water or soil.

Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal. and methods of disposal, including any contaminated packaging

Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

Not regulated. Not regulated. IATA Classification (Air)..... Not regulated. IMDG Classification (Marine)..... Not regulated.

Marine Pollutant..... Potential marine pollutant.

In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. Proof of Classification.....

SECTION 15: REGULATORY INFORMATION

On DSL, or exempt. CEPA status.....

TSCA inventory status..... All components are either listed or exempt from the TSCA. .

This product is considered hazardous under the OSHA Hazard Communication Standard. OSHA..... SARA Title III

Section 302 - extremely hazardous None.

substances

Section 311/312 - hazard categories...... Section 313.....

Disclaimer:.....

EPA hazardous air pollutants (HAPS)

40CFR63

California Proposition 65.....

Immediate health, delayed health.

None above De minimus % limit.

1,3-Dichloropropene. Methanol. Methylene Chloride (Dichloromethane).

! WARNING: This product can expose you to chemicals including [see below], which

are known to the State of California to cause birth defects or other reproductive harm. (Methanol). ***! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer. (Dichloromethane). For more information, go to www.P65Warnings.ca.gov. (Methylene chloride).

SECTION 16: OTHER INFORMATION

REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com. Prepared by: Telephone number:.... (800) 387-7981.

DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or quarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

SECTION 16: OTHER INFORMATION

Review Date: 2022-11-30. Date of the latest revision of the safety 2018-10-03

data sheet

