



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PB 2308-4 IN AND OUT CLEANER/DRESSING**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PB 2308-4 IN AND OUT CLEANER/DRESSING

Recommended use and restrictions on .. Cleaner.  
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Specific Target Organ Toxicity — Single Exposure — Category 3.  
(narcotic effects). (respiratory system).

Hazard Description..... H225 Highly flammable liquid and vapour. H335 May cause respiratory irritation. H336 May  
cause drowsiness or dizziness.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233  
Keep container tightly closed. P240 Ground and bond container and receiving equipment.  
P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take  
precautionary measures against static discharge. P261 Avoid breathing mists, vapours and  
sprays. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves  
and eye protection.

Response ..... P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 +  
P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse  
thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to  
fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you  
feel unwell.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool.  
P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note ..... This product mixture has been classified based on its ingredients.

### SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Distillates (Petroleum) Hydrotreated Light	64742-47-8	60-100
Light Aliphatic Solvent Naphtha	64742-89-8	1-5
<<The actual concentration(s) withheld as a trade secret>> .		

### SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at  
least 15 minutes. Consult a physician if irritation continues.

Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious  
amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If  
irritation persists, seek medical attention.

**PRODUCT: PB 2308-4 IN AND OUT CLEANER/DRESSING**

**SECTION 04: FIRST-AID MEASURES**

Ingestion..... If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Most important symptoms and effects, ..... May cause mild skin irritation. May cause slight eye irritation. May cause respiratory whether acute or delayed irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable and unsuitable extinguishing ..... "Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used. media Do not use water in a jet.

Specific hazards arising from the ..... Oxides of carbon (CO, CO2). Formaldehyde. Hydrocarbon fumes and smoke. hazardous product, such as the nature of any hazardous combustion products

Special protective equipment and ..... Firefighter should be equipped with self-contained breathing apparatus and full protective precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Leak/spill..... Keep away from heat, sparks and flames. Ventilate. Eliminate all sources of ignition. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities Store away from all sources of heat and ignition. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use.

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Distillates (Petroleum) Hydrotreated Light	1200 mg/m3	197 ppm	Not established	Not established	Not established	Not established
	CA BC: 200mg/m3 (TWA) Skin					
Light Aliphatic Solvent Naphtha	Not established	Not established	Not established	Not established	Not established	Not established
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.					
Gloves/ type.....	Chemical resistant gloves.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.					

**PRODUCT: PB 2308-4 IN AND OUT CLEANER/DRESSING****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Appropriate engineering controls..... Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state..... Liquid.  
 Colour..... Clear to pale yellow.  
 Odour..... Hydrocarbon odour.  
 Odour threshold (ppm)..... Not available.  
 Vapour pressure (mm Hg)..... Not available.  
 Vapour density (air=1)..... >1.  
 pH..... Not applicable.  
 Relative Density (Specific Gravity)..... 6.84 lbs/USG.  
 Melting / Freezing point (deg C)..... Not available.  
 Solubility..... Negligible.  
 Initial boiling point / boiling range (deg C). >65.  
 Evaporation rate..... No data.  
 Flash point (deg C), method..... 14-18 . (estimate; lowest flash point ingredient).  
 Auto ignition temperature (deg C)..... 250.  
 Upper flammable limit (% vol)..... 7.  
 Lower flammable limit (% vol)..... 0.5.  
 Partition coefficient — n-octanol/water..... Not available.  
 % Volatile by volume..... Not available.  
 VOC (less water)..... 0.15 lbs/USG.  
 Viscosity..... 200 cPs. #4 @ 20 RPM.

**SECTION 10: STABILITY AND REACTIVITY**

Chemical stability..... Stable at normal temperatures and pressures.  
 Reactivity ..... If heated above 150C, may form formaldehyde gas.  
 Possibility of hazardous reactions..... Hazardous polymerization will not occur.  
 Conditions to avoid, including static ..... Keep away from heat. Incompatible with strong oxidizers.  
 discharge, shock or vibration  
 Hazardous decomposition products..... Oxides of carbon (CO,CO2). Formaldehyde. Dense black smoke.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Distillates (Petroleum) Hydrotreated Light	>5.2 mg/L (4 hr.)	>5000 mg/kg (oral, rat), >2000 mg/kg (dermal, rabbit)
Light Aliphatic Solvent Naphtha	3400 ppm 4hr rat	3000 mg/kg dermal rat
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Ingestion.....	May be harmful or fatal if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material.....	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.	
Reproductive effects.....	No data on reproductive effects were found in the literature sources consulted.	
Specific Target Organ Toxicity .....	May cause drowsiness or dizziness. May cause respiratory irritation.	

**PRODUCT: PB 2308-4 IN AND OUT CLEANER/DRESSING****SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.  
 Persistence and degradability..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN1268 - PETROLEUM DISTILLATES, N.O.S. (Naphtha) - Class 3 - PGII - this product meets limited quantity exemption when shipped in containers less than 1 litre.  
 DOT Classification (Road)..... UN1268 - PETROLEUM DISTILLATES, N.O.S. (Naphtha) - Class 3 - PGII. Ltd Qty (1 Liter/0.26 Gallons). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.  
 IATA Classification (Air)..... UN1268 - PETROLEUM DISTILLATES, N.O.S. (Naphtha) - Class 3 - PGII . Limited Quantity. Do not ship by air without checking appropriate IATA regulations.  
 IMDG Classification (Marine)..... UN1268 - PETROLEUM DISTILLATES, N.O.S. (Naphtha) - Class 3 - PGII . Limited Quantity. Check IMDG regulations for limited quantity exemptions.  
 Marine Pollutant..... No.  
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**SECTION 15: REGULATORY INFORMATION**

CEPA status..... On Domestic Substances List (DSL).  
 TSCA inventory status..... All components are listed.  
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.  
 SARA Title III  
 Section 302 - extremely hazardous ..... None.  
 substances  
 Section 311/312 - hazard categories..... Immediate health. Fire hazard.  
 Section 313..... None.  
 EPA hazardous air pollutants (HAPS) ..... None.  
 40CFR63  
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16: OTHER INFORMATION**

Prepared by: ..... REGULATORY AFFAIRS. Trivalent Data Systems Ltd. [www.trivalent.com](http://www.trivalent.com).  
 Telephone number:..... (800) 387-7981.  
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.  
 Review Date:..... 2022-11-30.  
 Date of the latest revision of the safety .. 2018-07-24  
 data sheet