



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PB3001-4 EXTRA CUT COMPOUND

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PB3001-4 EXTRA CUT COMPOUND

Recommended use and restrictions on .. Compound.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 3. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Repeated Exposure — Category 1. Health Hazard Not Otherwise Classified 1. Causes serious damage to the respiratory tract.

Hazard Description..... H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P314 - Get medical advice/attention if you feel unwell.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|-------|
| Naphtha (petroleum), heavy alkylate | 64741-65-7 | 7-13 |
| Distillates (Petroleum) Hydrotreated Light | 64742-47-8 | 7-13 |
| Propylene glycol monobutyl ether | 5131-66-8 | 1-5 |
| Monoethanolamine | 141-43-5 | 1-5 |

<<The actual concentration(s) withheld as a trade secret>> .

PRODUCT: PB3001-4 EXTRA CUT COMPOUND**SECTION 04: FIRST-AID MEASURES**

| | |
|--|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Can cause skin sensitization. Causes damage to organs through prolonged or repeated exposure. |
| Additional information..... | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable and unsuitable extinguishing media | "Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO ₂). Other potentially toxic fumes. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. |
| Unusual fire / explosion hazards..... | Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-----------------|---|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Remove all possible sources of ignition in the surrounding area. Use explosion-proof or hand pumps and non-sparking tools and equipment. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|---|

SECTION 07: HANDLING AND STORAGE

| | |
|--|---|
| Precautions for safe handling..... | Keep away from heat, sparks, and open flame. This material is a static accumulator. Prevent accumulation of electrostatic charges. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|--|--|-------------------|-----------------|------------------|-----------------|
| Naphtha (petroleum), heavy alkylate | 525 mg/m ³ | Not established | Not established | Not established | Not established |
| Distillates (Petroleum) Hydrotreated Light | 1200 mg/m ³ | 197 ppm | Not established | Not established | Not established |
| | CA BC: 200mg/m ³ (TWA) Skin | | | | |
| Propylene glycol monobutyl ether | Not Established | Not Established | Not Established | Not Established | Not Established |

PRODUCT: PB3001-4 EXTRA CUT COMPOUND**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|---------------------------------------|---|-------------------|-----------------|------------------|-----------------|
| Monoethanolamine | 3 ppm | 6 ppm | Not Established | Not Established | Not Established |
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. | | | | |
| Eye/type..... | Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists. | | | | |
| Gloves/ type..... | Chemical resistant gloves. | | | | |
| Clothing/type..... | Wear adequate protective clothes. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Other/type..... | Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products. | | | | |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-----------------------------|
| Appearance/Physical state..... | Liquid. |
| Colour..... | Milky white. |
| Odour..... | Weak petroleum hydrocarbon. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | No data. |
| Vapour density (air=1)..... | >1. |
| pH..... | 7.0 - 9.0. |
| Relative Density (Specific Gravity)..... | 7.6 lbs/USD - 0.910. |
| Melting / Freezing point (deg C)..... | < 0 °C. |
| Solubility..... | Water dilutable. |
| Initial boiling point / boiling range (deg C)..... | > 100° C. |
| Evaporation rate..... | <1. |
| Flash point (deg C), method..... | 56. (Closed Cup). |
| Auto ignition temperature (deg C)..... | 246C. |
| Upper flammable limit (% vol)..... | 23.5. |
| Lower flammable limit (% vol)..... | 0.5. |
| Partition coefficient — n-octanol/water..... | Not available. |
| VOC (less water)..... | 1.68 lbs/USG. |
| Viscosity..... | 1932 cps Spindle #4. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. Heating above 60°C in the presence of aluminum can result in corrosion and generation of flammable hydrogen gas. . |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |
| Conditions to avoid, including static | Keep away from heat. Incompatible with strong oxidizers. |
| discharge, shock or vibration | |
| Hazardous decomposition products..... | Oxides of carbon (CO,CO2). Thermal decomposition may release acrolein. Does not decompose up to 204°C (400°F). |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|--|--|
| Naphtha (petroleum), heavy alkylate | >4000 mg/kg dermal rat | >8000 mg/kg oral rat |
| Distillates (Petroleum) Hydrotreated Light | >5.2 mg/L (4 hr.) | >5000 mg/kg (oral, rat), >2000 mg/kg (dermal, rabbit) |
| Propylene glycol monobutyl ether | >651 ppm 4 Hr Rat | 2,700 mg/kg Rat Oral >2,000 mg/kg Rat Skin |
| Monoethanolamine | 232 ppm Guinea Pig | 1720 mg/kg Rat Oral 1018 mg/kg Rabbit Dermal |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |

PRODUCT: PB3001-4 EXTRA CUT COMPOUND**SECTION 11: TOXICOLOGICAL INFORMATION**

| | |
|---|---|
| Effects of acute exposure..... | The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. May be harmful if absorbed through the skin. |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. |
| Carcinogenicity of material..... | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH. |
| Reproductive effects..... | No known reproductive effects. |
| Sensitizing capability of material..... | May cause sensitization by skin contact. |
| Specific Target Organ Toxicity..... | Causes damage to organs through prolonged or repeated exposure . |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. |
|---|---|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillate) - Class 3 - Packing Group III - This product meets limited quantity exemption when shipped in containers less than 5 litres. |
| DOT Classification (Road)..... | UN1993 - FLAMMABLE LIQUID, N.O.S. (Petroleum distillates) - Class 3 - PGIII - Ltd Qty (5 Liters/1.3 Gallons). |
| IATA Classification (Air)..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - Packing Group III . Limited Quantity. Do not ship by air without checking appropriate IATA regulations. |
| IMDG Classification (Marine)..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Solvent naphtha) - Class 3 - Packing Group III . EmS: F-E, S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|---|
| CEPA status..... | On DSL, or exempt. |
| TSCA inventory status..... | All components are either listed or exempt from the TSCA. . |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health, fire hazard. |
| Section 313..... | Aluminum Oxide (fibrous forms only). |
| EPA hazardous air pollutants (HAPS) 40CFR63 | Methylene Chloride (Dichloromethane). 1,3-Dichloropropene. |
| California Proposition 65..... | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Dichloroprene). (Ethyl acrylate). (Methylene chloride). For more information, go to www.P65Warnings.ca.gov . |

SECTION 16: OTHER INFORMATION

| | |
|------------------------|---|
| Prepared by: | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com . |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:..... | 2021-11-04. |

PRODUCT: PB3001-4 EXTRA CUT COMPOUND**SECTION 16: OTHER INFORMATION**

Date of the latest revision of the safety .. 2018-07-12
data sheet