



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PB3004-4 ULTRA FINE SWIRL REMOVER

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PB3004-4 ULTRA FINE SWIRL REMOVER

Recommended use and restrictions on .. Cleaner.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 3. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system).

Hazard Description..... H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|-------|
| Distillates (Petroleum) Hydrotreated Light | 64742-47-8 | 20-30 |
| Light Aliphatic Solvent Naphtha | 64742-89-8 | 7-13 |
| Tetrasodium EDTA | 64-02-8 | 1-5 |

PRODUCT: PB3004-4 ULTRA FINE SWIRL REMOVER**SECTION 04: FIRST-AID MEASURES**

| | |
|---|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. This product could cause chemical pneumonitis through aspiration of the product into the lungs following accidental ingestion. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. High vapour concentrations may be irritating to the respiratory tract. |
| Additional information..... | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable and unsuitable extinguishing media | "Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. |
| Unusual fire / explosion hazards..... | Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO2). Hydrocarbon fumes and smoke. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-----------------|--|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Avoid all personal contact. Evacuate all non-essential personnel. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|--|

SECTION 07: HANDLING AND STORAGE

| | |
|--|---|
| Precautions for safe handling..... | Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep container closed when not in use. Store away from all sources of heat and ignition. Store away from oxidizing and reducing materials. Store away from sunlight. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|---|----------------------------|-------------------|-----------------|------------------|-----------------|
| Distillates (Petroleum) Hydrotreated Light | 1200 mg/m3 | 197 ppm | Not established | Not established | Not established |
| | CA BC: 200mg/m3 (TWA) Skin | | | | |
| Light Aliphatic Solvent Naphtha | Not established | Not established | Not established | Not established | Not established |
| Tetrasodium EDTA | Not Established | Not Established | Not Established | Not Established | Not Established |

PRODUCT: PB3004-4 ULTRA FINE SWIRL REMOVER**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| | |
|---------------------------------------|---|
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. |
| Eye/type..... | Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists. |
| Gloves/ type..... | Chemical resistant gloves. |
| Clothing/type..... | Wear adequate protective clothes. |
| Footwear/type..... | Safety boots per local regulations. |
| Other/type..... | Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products. |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-------------------------|
| Appearance/Physical state..... | Liquid. |
| Colour..... | Pale yellow. |
| Odour..... | Mild odour. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | No data. |
| Vapour density (air=1)..... | >1. |
| pH..... | 6.0 - 8.0. |
| Relative Density (Specific Gravity)..... | 7.85 lbs/USG; 0.940. |
| Melting / Freezing point (deg C)..... | ~ 0°C. |
| Solubility..... | No data. |
| Initial boiling point / boiling range (deg C)..... | ~ 100°C . |
| Evaporation rate..... | No data. |
| Flash point (deg C), method..... | 53. (Closed Cup). |
| Auto ignition temperature (deg C)..... | >230 C. |
| Upper flammable limit (% vol)..... | 12.0. |
| Lower flammable limit (% vol)..... | 0.5. |
| Partition coefficient — n-octanol/water..... | No data. |
| VOC (less water)..... | 2.01 lb/USG; 240.9 g/L. |
| Viscosity..... | Spindle #4 1975cps. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |
| Conditions to avoid, including static | Keep away from heat. Incompatible with strong oxidizers. |
| discharge, shock or vibration | |
| Hazardous decomposition products..... | Oxides of carbon (CO,CO2). Dense black smoke. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|--|--|
| Distillates (Petroleum) Hydrotreated Light | >5.2 mg/L (4 hr.) | >5000 mg/kg (oral, rat), >2000 mg/kg (dermal, rabbit) |
| Light Aliphatic Solvent Naphtha | 3400 ppm 4hr rat | 3000 mg/kg dermal rat |
| Tetrasodium EDTA | Not Available | Not Available |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | Hazardous in contact with skin, by ingestion, and by inhalation. Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Skin contact with adhesive that is not fully cured may cause an allergic skin reaction or other skin irritation. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use. Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing | |

PRODUCT: PB3004-4 ULTRA FINE SWIRL REMOVER**SECTION 11: TOXICOLOGICAL INFORMATION**

| | |
|--------------------------------------|--|
| Effects of acute exposure..... | this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal. Breathing of glass fibers can cause short-term irritation of the mouth, nose, and throat. Other symptoms may include coughing and wheezing. Because of the structure of the fibers, they do not enter the lungs (See Other Health Effects). Can cause moderate skin irritation, defatting and dermatitis. Inhalation may cause respiratory tract irritation. Inhalation of high vapour may cause central nervous system effects, dizziness, headache, nausea, or loss of coordination. Aspiration of liquid into lungs can cause chemical pneumonitis. |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. |
| Carcinogenicity of material..... | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH. |
| Reproductive effects..... | No component of this product present at levels greater than or equal to 0.1% . |
| Specific Target Organ Toxicity | May cause drowsiness or dizziness. May cause respiratory irritation. |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. |
|---|---|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - PGIII - Regulated in bulk only. This product is a flammable liquid, Class 3, Packing Group III material with a flash point >37.8C and is exempt from the application of these regulations in non-bulk (< 450L) packaging as per TDG 1.33. |
| DOT Classification (Road)..... | 49CFR173.150 provides an exception to the requirements of subsection 172.101 flammable liquids in Packing Group III and combustible liquids, inner packagings not over 5.0 L (1.3 gallons) net capacity each, packed in a strong outer packaging. Otherwise this product is classified as;. UN1993 - FLAMMABLE LIQUID, N.O.S. (Petroleum distillates) - Class 3 - PGIII - Ltd Qty (5 Liters/1.3 Gallons). Refer to 49CFR 172.101 for additional non-bulk packaging requirements. |
| IATA Classification (Air)..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - Packing Group III . Limited Quantity. Do not ship by air without checking appropriate IATA regulations. |
| IMDG Classification (Marine)..... | UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - PGIII - EmS: F-E, S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|---|---|
| CEPA status..... | On Domestic Substances List (DSL). |
| TSCA inventory status..... | All components are listed. |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III Section 302 - extremely hazardous | None. |
| substances Section 311/312 - hazard categories..... | Immediate health, delayed health. Fire hazard. |
| Section 313..... | None above De minimus % limit. |
| EPA hazardous air pollutants (HAPS) | Benzene. Dichloroprene. Ethylbenzene. Methanol. Methylene Chloride (Dichloromethane). Xylene. |
| 40CFR63 | |

PRODUCT: PB3004-4 ULTRA FINE SWIRL REMOVER

SECTION 15: REGULATORY INFORMATION

California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Benzene (D)). (Methanol). (Ethylene oxide [dev]) . *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Benzene). (Cumene). (Dioxane). (Ethyl acrylate). (Ethyl benzene). (Ethylene oxide). (Dichloroprene). (Methylene chloride). (Naphthalene). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Review Date:..... 2021-11-15.
Date of the latest revision of the safety .. 2018-07-25
data sheet