

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

# PRODUCT: PF 136 WHITE CREAM HARDENER

#### **SECTION 01: IDENTIFICATION**

Initial supplier identifier..... Pro Form Products Ltd. 604 McGeachie Drive

Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189 PF 136 WHITE CREAM HARDENER

Product identifier..... Recommended use and restrictions on ...

Accelerator and activator.

Chemical family.....

24 hour emergency number:.....

Health: 2 Fire: 1 Reactivity: 1.

NFPA rating..... HMIS..... H: 2 F: 1 R: 1.

For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.

\*\* For medical emergencies contact your local poison control centre \*\*.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... WARNING. Organic Peroxides — Type E. Skin Sensitizer — Category 1. Eye Irritation — Category Hazard Classification..... Hazard Description..... H242 Heating may cause a fire. H317 May cause an allergic skin reaction. H319 Causes serious eve irritation. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P234 Keep only in original packaging. P235 Keep cool. P240 Ground and bond container and Prevention..... receiving equipment. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.
P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact Response ..... lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P321 - For specific treatment see section 4 on this SDS P403 Store in a well ventilated area. P410 Protect from sunlight. P411 Store at temperatures not exceeding 38°C / 100°F. P420 Store separately. Storage..... P501 Dispose all unused, waste or empty containers in accordance with local regulations. Disposal..... This product mixture has been classified based on its ingredients. Note .....

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS					
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %			
Benzoyl peroxide C9-11-branched alkyl benzoate	94-36-0 131298-44-7	50-55 15-20			

## **SECTION 04: FIRST-AID MEASURES**

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Immediately remove all contaminated clothing, flush skin with water for at least 15 minutes. Wash clothing before reuse. If irritation persists, seek medical attention. Wash skin with soap and water.



### PRODUCT: PF 136 WHITE CREAM HARDENER

### **SECTION 04: FIRST-AID MEASURES**

Most important symptoms and effects, ..... Can cause skin sensitization. Causes serious eye irritation. whether acute or delayed

Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

#### SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing ..... "Alc media

Specific hazards arising from the ..... The

"Alcohol" foam, CO2, dry chemical. Do not use water in a jet.

Additional information.....

Thermal decomposition products are toxic. May include:. Oxides of carbon (CO, CO2). Emits toxic fumes under fire conditions.

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

Unusual fire / explosion hazards.....

Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source. This material is an oxidizer and may increase the intensity of any fire and the possibility of an explosion.

### **SECTION 06: ACCIDENTAL RELEASE MEASURES**

Leak/spill.....

Ventilate. Eliminate all sources of ignition. Isolate area and keep unauthorized people away. Do not walk through spilled material. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Recover spilled material and place in suitable containers for recycling or disposal. Avoid solvent cleaners. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

## **SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....

Keep away from heat, sparks, and open flame. Do not breathe vapours, mist or dust. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle in accordance with good industrial hygiene and safety practices. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Handle and open container with care. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from strong oxidizers. Store away from acids.

## SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	PEL	SHA PEL STEL	NIOSH REL		
Benzoyl peroxide	5 mg/m3	Not Established	5 mg/m3	Not Established	5 mg/m3 TWA		
C9-11-branched alkyl benzoate	No data						
Respiratory/type		Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Eye/type		Liquid chemical goggles.		•			
Gloves/ type		Chemical resistant gloves.					
Clothing/type							
Footwear/type							
Other/type							
Appropriate engineering	controls	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air					

## PRODUCT: PF 136 WHITE CREAM HARDENER

## SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Appropriate engineering controls.....

contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for quidance about adequate ventilation.

### **SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Viscosity	Appearance/Physical state	
-----------	---------------------------	--

## **SECTION 10: STABILITY AND REACTIVITY**

Chemical stability..... Stable at normal temperatures and pressures.

Reactivity ..... Hazardous polymerization will not occur. Avoid heat, sparks and flames.

Possibility of hazardous reactions..... Hazardous polymerization will not occur.

Conditions to avoid, including static .......

discharge, shock or vibration Incompatible materails.....

Hazardous decomposition products.....

Avoid heat, spark, open flames. Strong oxidizing agents. Acids.

No hazardous decomposition products when stored and handled correctly. See

hazardous combustion products section 5.

## SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

Benzoyl peroxide >24.3 mg/L (4 hr., vapour) 7710 mg/kg (Rat, Oral)

Not available C9-11-branched alkyl benzoate Not available

Route of exposure..... Eye contact. Skin contact. Ingestion. Inhalation.

Effects of acute exposure..... Causes serious eye irritation. Contact with paste may result in irritation, redness, tearing,

and blurred vision. May cause sensitization by skin contact. May cause skin irritation. Effects of chronic exposure..... Prolonged or repeated skin contact may cause drying or cracking of skin.

Carcinogenicity of material..... This product is not listed by NTP, IARC or regulated as a carcinogen by OSHA.

Reproductive effects..... No data

May cause sensitization by skin contact. Sensitizing capability of material.....

### **SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil. This material meets the definition of a

marine pollutant.

Other adverse effects

Persistence and degradability..... Not available.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal. and methods of disposal, including any contaminated packaging

Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.



### PRODUCT: PF 136 WHITE CREAM HARDENER

### **SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. The product meets the Limited Quantity exemption when packaged in containers less than 0.5 kg. UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. DOT Classification (Road)..... Limited quantity: 0.5 kg (solids). UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. Do IATA Classification (Air)..... not ship by air without checking appropriate IATA regulations.
UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. IMDG Classification (Marine)..... EmS-No: F-J, S-R. Check IMDG regulations for limited quantity exemptions. Marine Pollutant..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July Proof of Classification..... 2, 2014) - we certify that classification of this product is correct. .

### **SECTION 15: REGULATORY INFORMATION**

On Domestic Substances List (DSL). CEPA status.....

TSCA inventory status..... All components are listed.

OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.

SARA Title III

Section 302 - extremely hazardous ....... None. substances

Section 311/312 - hazard categories....... Fire hazard. Reactive. Section 313..... Benzoyl peroxide.

EPA hazardous air pollutants (HAPS) ...... None.

40CFR63

California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to www.P65Warnings.ca.gov.

### **SECTION 16: OTHER INFORMATION**

Prepared by: ..... REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.

Telephone number..... Disclaimer:.....

(800) 387-7981.
DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not

relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety ... 2019-10-31

data sheet