O

PR

# SAFETY DATA SHEET

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

# PRODUCT: PF 138 BLUE CREAM HARDENER 0.50Z

FORM

## **SECTION 01: IDENTIFICATION**

Initial supplier identifier	Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189
Product identifier	PF 138 BLUE CREAM HARDENER 0.50Z
Recommended use and restrictions on	Accelerator and activator.
use	
Chemical family NFPA rating	Mixture.
HMIS	
24 hour emergency number:	For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
	IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
	** For medical emergencies contact your local poison control centre **.

### **SECTION 02: HAZARD IDENTIFICATION**



Signal Word	WARNING.
Hazard Classification	Organic Peroxides — Type E. Skin Sensitizer — Category 1. Eye Irritation — Category 2A.
Hazard Description	H242 Heating may cause a fire. H317 May cause an allergic skin reaction. H319 Causes serious eve irritation.
Prevention	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P234 Keep only in original packaging. P235 Keep cool. P240 Ground and bond container and receiving equipment. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.
Response	P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P321 - For specific treatment see section 4 on this SDS.
Storage	P403 Store in a well ventilated area. P410 Protect from sunlight. P411 Store at temperatures not exceeding 38°C / 100°F. P420 Store separately.
Disposal	
Note	This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS		
CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Benzoyl peroxide	94-36-0	50-55
C9-11-branched alkyl benzoate	131298-44-7	15-20

#### SECTION 04: FIRST-AID MEASURES

Eye contact	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
Skin contact	least 15 minutes. Obtain medical attention. Immediately remove all contaminated clothing, flush skin with water for at least 15 minutes.
	Wash clothing before reuse. If irritation persists, seek medical attention. Wash skin with soap and water.

Powered by

SAFETY DATA SHEET

### PRODUCT: PF 138 BLUE CREAM HARDENER 0.50Z

# SECTION 04: FIRST-AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
Ingestion	difficult, give oxygen, obtain medical attention. Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head
	down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed	
Additional information	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

#### SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO2, dry chemical. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Thermal decomposition products are toxic. May include:. Oxides of carbon (CO, CO2). Emits toxic fumes under fire conditions.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.
Unusual fire / explosion hazards	

#### SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....

Ventilate. Eliminate all sources of ignition. Isolate area and keep unauthorized people away. Do not walk through spilled material. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Recover spilled material and place in suitable containers for recycling or disposal. Avoid solvent cleaners. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

### SECTION 07: HANDLING AND STORAGE

Precautions for safe handling	all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle in accordance with good industrial hygiene and safety practices. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from strong oxidizers. Store away from acids.

### SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	OSH PEL	IA PEL STEL	NIOSH REL
Benzoyl peroxide	5 mg/m3	Not Established	5 mg/m3	Not Established	5 mg/m3 TWA
C9-11-branched alkyl benzoate	No data				
Respiratory/type Eye/type Gloves/ type Clothing/type Footwear/type Other/type Appropriate engineering		Local exhaust ventilation i when contaminant levels e Liquid chemical goggles. Chemical resistant gloves Wear adequate protective Safety boots per local regu Emergency showers and e Provide natural or mecha exposure limits. Local med	exceed the recomme clothes. ulations. eye wash stations sh	nded exposure limits. hould be available.	

**ECIS** 

#### PRODUCT: PF 138 BLUE CREAM HARDENER 0.50Z

#### SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Appropriate engineering controls.....

contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.

#### SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

### **SECTION 10: STABILITY AND REACTIVITY**

Chemical stability
Reactivity
Possibility of hazardous reactions
Conditions to avoid, including static
discharge, shock or vibration Incompatible materails
Incompătible materails

Stable at normal temperatures and pressures. Hazardous polymerization will not occur. Avoid heat, sparks and flames. Hazardous polymerization will not occur. Avoid heat, spark, open flames.

Hazardous decomposition products.....

Strong oxidizing agents. Acids. No hazardous decomposition products when stored and handled correctly. See hazardous combustion products section 5.

# SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50	
Benzoyl peroxide	>24.3 mg/L (4 hr., vapo	ur) 7710 mg/kg (Rat, Oral)	
C9-11-branched alkyl benzoate	Not available	Not available	
Route of exposure Effects of acute exposure			
Effects of chronic exposure Carcinogenicity of material Reproductive effects Sensitizing capability of material	<ul> <li>Prolonged or repeated skin contact may cause drying or cracking of skin.</li> <li>This product is not listed by NTP, IARC or regulated as a carcinogen by OSHA.</li> <li>No data.</li> </ul>		

#### **SECTION 12: ECOLOGICAL INFORMATION**

Environmental.....

Do not allow to enter waters, waste water or soil. This material meets the definition of a marine pollutant.

Other adverse effects Persistence and degradability.....

Not available.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal . and methods of disposal, including any contaminated packaging

Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.



SAFETY DATA SHEET

# PRODUCT: PF 138 BLUE CREAM HARDENER 0.50Z

### **SECTION 14: TRANSPORT INFORMATION**

TDG Classification	The product meets the Limited Quantity exemption when packaged in containers less than
DOT Classification (Road)	
IATA Classification (Air)	Limited quantity: 0.5 kg (solids). UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. Do
IMDG Classification (Marine)	not ship by air without checking appropriate IATA regulations. UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. EmS-No: F-J, S-R. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant Proof of Classification	Yes.

# **SECTION 15: REGULATORY INFORMATION**

CEPA status TSCA inventory status OSHA SARA Title III	On Domestic Substances List (DSL). All components are listed. This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA The III Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories Section 313 EPA hazardous air pollutants (HAPS)	Benzoyl peroxide.
40CFR63 California Proposition 65	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to www.P65Warnings.ca.gov.

# **SECTION 16: OTHER INFORMATION**

Prepared by: Telephone number: Disclaimer:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com. (800) 387-7981. DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Date of the latest revision of the safety data sheet	2019-10-31

