



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF 164 SHORT STRAND BODY FILLER 750ML**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 164 SHORT STRAND BODY FILLER 750ML

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

Recommended use and restrictions on .. Automotive. This product should not be used for any other purpose other than the ones  
use described in this section.

Chemical family..... Mixture.

Hazard rating

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 3. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritant 2. Specific Target Organ Toxicity — Single Exposure — Category 3. Carcinogenicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H351 This product contains ingredients that are suspected of causing cancer. H372 Causes damage to the liver and kidneys through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash hands thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response ..... P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P308 + P313 If exposed or concerned, get medical advice/attention. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye irritation persists get medical attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

**PRODUCT: PF 164 SHORT STRAND BODY FILLER 750ML****SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Talc	14807-96-6	15-40
Styrene	100-42-5	10-15
Glass, oxide, chemicals	65997-17-3	10-15
Magnesium Carbonate	546-93-0	7-13
Chlorite	1318-59-8	7-13
PRECIPITATED SILICON DIOXIDE	112926-00-8	3-7
Calcium Carbonate	1317-65-3	1-5
Titanium Dioxide	13463-67-7	0.1-1
CHROMIUM III OXIDE	1308-38-9	0.1-1.0

**SECTION 04: FIRST-AID MEASURES**

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO <sub>2</sub> , dry chemical.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO <sub>2</sub> ).
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

**PRODUCT: PF 164 SHORT STRAND BODY FILLER 750ML****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	ACGIH TLV		OSHA PEL		NIOSH REL
	TWA	STEL	PEL	STEL	
Talc	2 mg/m3 CA ON: 2mg/kg (TWA)	Not established	2 mg/m3 TWA	Not established	Not established
Styrene	20 ppm CA ON: 35ppm (TWA), 100ppm (STEL)	40 ppm	100 ppm	Not established	100 ppm
Glass, oxide, chemicals	5 mg/m3	Not established	Not established	Not established	5 mg/m3 total dust
Magnesium Carbonate	Not established No data	Not established	Not established	Not established	Not established
Chlorite	No data No data	No data	No data	No data	No data
PRECIPITATED SILICON DIOXIDE	Not established	Not established	Not established	Not established	Not established
Calcium Carbonate	Not established	Not established	5 mg/m3	Not established	5 mg/m3
Titanium Dioxide	10 mg/m3 CA ON: 10 mg/m3 (TWA)	Not established	15 mg/m3	Not established	Not established
CHROMIUM III OXIDE	Not established	Not established	Not established	Not established	Not established

**Personal Protective Equipment**

Eye/type.....	Liquid chemical goggles.
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.

## Exposure limits

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state.....	Paste.
Colour.....	Green.
Odour.....	Hydrocarbon odour.
Odour threshold (ppm).....	0.15-25 ppm (Styrene).
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Relative Density (Specific Gravity).....	1.397 - 11.66 lb/usg.
Melting / Freezing point (deg C).....	-30°C.
Solubility.....	Slightly soluble in water.
Initial boiling point / boiling range (deg C).....	145°C.
Evaporation rate.....	Moderate.
Flash point (deg C), method.....	32°C Closed Cup.
Auto ignition temperature (deg C).....	490°C.
Upper flammable limit (% vol).....	8.9.
Lower flammable limit (% vol).....	1.1.
Partition coefficient — n-octanol/water.....	Not available.
VOC (less water).....	0.40 lbs/USG.
Viscosity.....	650 000 cps Brooke spindle F @ 10rpm.

**SECTION 10: STABILITY AND REACTIVITY**

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity .....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Conditions to avoid, including static discharge, shock or vibration .....	Keep away from heat. Incompatible with strong oxidizers.

**PRODUCT: PF 164 SHORT STRAND BODY FILLER 750ML****SECTION 10: STABILITY AND REACTIVITY**

Hazardous decomposition products..... Oxides of carbon (CO,CO2).  
 Possibility of hazardous reactions..... Will not occur under normal temperature and pressure.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Talc	Not available	Not available
Styrene	2770 ppm 4 hr rat	5000 mg/kg rat oral
Glass, oxide, chemicals	No data	No data
Magnesium Carbonate	Not available	Not available
Chlorite	No data	No data
PRECIPITATED SILICON DIOXIDE	No data	>5,000 mg/kg rat oral; > 2,000 mg/kg rabbit dermal
Calcium Carbonate	Not available	6450 mg/kg rat oral
Titanium Dioxide	>6.8 mg/L (4 hr)	>10,000 mg/kg (rat, oral) >10,000 mg/kg (rabbit, dermal)
CHROMIUM III OXIDE	Not available	Not available
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated exposure may result in skin sensitization. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis. May cause sensitization by skin contact.	
Skin absorption.....	Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Solvent vapours may be irritating to the eyes, nose and throat, resulting in redness, burning and itching of eyes, dryness of the throat and tightness in the chest. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation.	
Ingestion.....	Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.	
Carcinogenicity of material.....	Titanium dioxide is known to the state of California to cause cancer and developmental effects.	
Reproductive effects.....	None.	
Toxicological Data		

**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.  
 Persistence and degradability..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN3269 - Polyester Resin Kit - Class 3 - Packing Group III - This product meets the criteria for Limited Quantity Exemptions when packaged in containers less than 5 litres .  
 DOT Classification (Road)..... UN3269 - Polyester Resin Kit - Class 3 - Packing Group III - Ltd Qty (5 Liters/1.3 Gallons).  
 IATA Classification (Air)..... UN3269 - Polyester Resin Kit - Class 3 - Packing Group III.  
 IMDG Classification (Marine)..... UN3269 - Polyester Resin Kit - Class 3 - Packing Group III - EmS: F-E S-D.

PRODUCT: PF 164 SHORT STRAND BODY FILLER 750ML

SECTION 14: TRANSPORT INFORMATION

Marine Pollutant..... Potential marine pollutant.
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

WHMIS 1988 classification..... B2, D2A, D2B.
CEPA status..... On Domestic Substances List (DSL).
OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III
Section 302 - extremely hazardous ..... None.
substances
Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
Section 313..... Styrene.
EPA hazardous air pollutants (HAPS) ..... Styrene.
40CFR63
TSCA inventory status..... All components are listed.
California Proposition 65..... Titanium dioxide is known to the State of California to cause cancer.

SECTION 16: OTHER INFORMATION

Prepared by: ..... REGULATORY AFFAIRS.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:..... 2022-11-30.
Date of the latest revision of the safety .. 2019-04-18
data sheet



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: BLUE CREAM HARDENER**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... BLUE CREAM HARDENER

Recommended use and restrictions on .. Accelerator and activator.  
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 1 Reactivity: 1.

HMIS..... H: 2 F: 1 R: 1.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... WARNING.

Hazard Classification..... Organic Peroxides — Type E. Skin Sensitizer — Category 1. Eye Irritation — Category 2A.

Hazard Description..... H242 Heating may cause a fire. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P234 Keep only in original packaging. P235 Keep cool. P240 Ground and bond container and receiving equipment. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.

Response ..... P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P321 - For specific treatment see section 4 on this SDS.

Storage..... P403 Store in a well ventilated area. P410 Protect from sunlight. P411 Store at temperatures not exceeding 38°C / 100°F. P420 Store separately.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note ..... This product mixture has been classified based on its ingredients.

### SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Benzoyl peroxide	94-36-0	50-55
C9-11-branched alkyl benzoate	131298-44-7	15-20

### SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Skin contact..... Immediately remove all contaminated clothing, flush skin with water for at least 15 minutes. Wash clothing before reuse. If irritation persists, seek medical attention. Wash skin with soap and water.

**PRODUCT: BLUE CREAM HARDENER****SECTION 04: FIRST-AID MEASURES**

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, ..... whether acute or delayed	Can cause skin sensitization. Causes serious eye irritation.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO <sub>2</sub> , dry chemical. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO <sub>2</sub> ). Emits toxic fumes under fire conditions.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.
Unusual fire / explosion hazards.....	Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source. This material is an oxidizer and may increase the intensity of any fire and the possibility of an explosion.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Isolate area and keep unauthorized people away. Do not walk through spilled material. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Recover spilled material and place in suitable containers for recycling or disposal. Avoid solvent cleaners. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
-----------------	--

**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. Do not breathe vapours, mist or dust. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle in accordance with good industrial hygiene and safety practices. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from strong oxidizers. Store away from acids.

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Benzoyl peroxide	5 mg/m <sup>3</sup>	Not Established	5 mg/m <sup>3</sup>	Not Established		5 mg/m <sup>3</sup> TWA
C9-11-branched alkyl benzoate	No data					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Eye/type.....	Liquid chemical goggles.					
Gloves/ type.....	Chemical resistant gloves.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available.					
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air					

**PRODUCT: BLUE CREAM HARDENER****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Appropriate engineering controls..... contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state..... Paste / solid.  
 Colour..... Blue/white.  
 Odour..... No data.  
 Odour threshold (ppm)..... Not available.  
 pH..... No data.  
 Melting / Freezing point (deg C)..... No data.  
 Initial boiling point / boiling range (deg C). No data.  
 Flash point (deg C), method..... 94.  
 Evaporation rate..... No data.  
 Flammability (solids and gases)..... Not applicable.  
 Upper flammable limit (% vol)..... No data.  
 Lower flammable limit (% vol)..... No data.  
 Vapour pressure (mm Hg)..... No data.  
 Vapour density (air=1)..... No data.  
 Relative Density (Specific Gravity)..... 1.2.  
 Pounds / USG..... 10.  
 Solubility..... No data.  
 Partition coefficient — n-octanol/water..... Not available.  
 Auto ignition temperature (deg C)..... Not available.  
 Decomposition temperature..... Not available.  
 Viscosity..... Not available.  
 VOC (less water)..... 2.3 lbs/USG.

**SECTION 10: STABILITY AND REACTIVITY**

Chemical stability..... Stable at normal temperatures and pressures.  
 Reactivity ..... Hazardous polymerization will not occur. Avoid heat, sparks and flames.  
 Possibility of hazardous reactions..... Hazardous polymerization will not occur.  
 Conditions to avoid, including static ..... Avoid heat, spark, open flames.  
 discharge, shock or vibration  
 Incompatible materials..... Strong oxidizing agents. Acids.  
 Hazardous decomposition products..... No hazardous decomposition products when stored and handled correctly. See hazardous combustion products section 5.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Benzoyl peroxide	>24.3 mg/L (4 hr., vapour)	7710 mg/kg (Rat, Oral)
C9-11-branched alkyl benzoate	Not available	Not available
Route of exposure.....	Eye contact. Skin contact. Ingestion. Inhalation.	
Effects of acute exposure.....	Causes serious eye irritation. Contact with paste may result in irritation, redness, tearing, and blurred vision. May cause sensitization by skin contact. May cause skin irritation.	
Effects of chronic exposure.....	Prolonged or repeated skin contact may cause drying or cracking of skin.	
Carcinogenicity of material.....	This product is not listed by NTP, IARC or regulated as a carcinogen by OSHA.	
Reproductive effects.....	No data.	
Sensitizing capability of material.....	May cause sensitization by skin contact.	

**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil. This material meets the definition of a marine pollutant.  
 Other adverse effects  
 Persistence and degradability..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.



**PRODUCT: BLUE CREAM HARDENER****SECTION 14: TRANSPORT INFORMATION**

TDG Classification.....	UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. The product meets the Limited Quantity exemption when packaged in containers less than 0.5 kg.
DOT Classification (Road).....	UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. Limited quantity: 0.5 kg (solids).
IATA Classification (Air).....	UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN3108 - ORGANIC PEROXIDE TYPE E, SOLID (Benzoyl peroxide), Class 5.2, PG II. EmS-No: F-J, S-R. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	Yes.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**SECTION 15: REGULATORY INFORMATION**

CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances .....	None.
Section 311/312 - hazard categories.....	Fire hazard. Reactive.
Section 313.....	Benzoyl peroxide.
EPA hazardous air pollutants (HAPS) 40CFR63 .....	None.
California Proposition 65.....	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .

**SECTION 16: OTHER INFORMATION**

Prepared by: .....	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. <a href="http://www.trivalent.com">www.trivalent.com</a> .
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:.....	2022-11-30.
Date of the latest revision of the safety data sheet .....	2019-10-31