

A one-part red lacquer putty used to fill minor holes, scratches, pinholes, dents and other imperfections on metal or other body fillers. Dries quickly and sands easily.

PRODUCT

PF 183

COLOR

Red

SIZE

284 ml (9.6 fl oz)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

FEATURES:

- Ready to use
- Use on metals, wood and fibreglass
- Use on sanded, painted or primed surfaces

SUITABLE SUBSTRATES

- Galvanized steel
- Steel
- Aluminum
- TPO
- Body fillers
- Wood
- Fiberglass
- Painted or primed surfaces

DIRECTIONS FOR USE:

1. Knead the tube before use.
2. Clean surface with a PF 605 Wax and Grease Remover (Strong). Apply several thin coats with spreader, allowing each coat to dry thoroughly. Do not fill deep cracks or apply in thick film.
3. Drying time varies, depending on thickness of product applied and temperature. A normal wait time would be 20-25 minutes at 21°C (70°F) or warmer.
4. When repair has been sanded, apply primer.
5. Use Pro Form Acetone PF 602 or a lacquer thinner to clean tools.

TECHNICAL DATA:

	PF 183
Physical state	Liquid
Color	Red
Odour	Aromatic
Solubility	Partially in water

Flash point (deg C), method	16°C (60.8°F) (Closed cup)
Auto ignition temperature (deg C)	> 400°C (> 752°F)
VOC	499.7 g/L • 4.2 lbs/gal

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATIONS

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.