

Brushable Rubber Based Seam Sealer PF 206

Brushable Rubber Based Seam Sealer is paintable, sandable and formulated to dry quickly and withstand exposure to weather and temperature variations. It can be used on bare metal and all types of painted and primed surfaces. Use to seal sheet metal overlap joints and to match OEM seam sealer in trunks, floor pans, firewalls, etc. Will air dry in less than 1 hour.

PRODUCT

SIZE

PF 206

946 ml (U.S. Quart)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Bare metal
- Painted and primed surfaces

ADVANTAGES:

- Paintable
- Dries quickly
- Waterproof

SURFACE PREPARATION:

1. Wash surface with soap and water.
2. Clean metal surfaces with PF 605 Wax and Grease Remover. Clean plastic surfaces with PF 606 Plastic Parts Cleaner. Wipe dry while the surface is still wet.

DIRECTIONS FOR USE:

1. Apply an even coat of PF 206 Brushable Sealer with a stiff brush or a spatula.
2. Can be smoothed with solvent soaked spatula or fingers.
3. Allow 30 to 40 minutes to dry before applying paint.
4. Clean excess sealer with PF 600 General Purpose Adhesive Cleaner.

TECHNICAL DATA:

	PF 206
Physical State	Paste
Color:	Off white
Odour:	Aromatic
Solubility :	Not soluble in water
Flash point:	4°C (39.2°F) (Tag Closed Cup)



Product Data Sheet

Brushable Rubber Based
Seam Sealer
PF 206

Table with 2 columns: Property (Auto ignition temperature, VOC) and Value (480°C (896°F), 363 g/L • 3.03 lbs/gal)

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product.