



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF 206 BRUSHABLE SEAM SEALER OFF WHITE**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 206 BRUSHABLE SEAM SEALER OFF WHITE

Recommended use and restrictions on .. Coatings.  
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 2 F: 4 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Corrosion/Irritation — Category 2. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Single Exposure — Category 3. (CNS). (Narcotic Effects). Specific Target Organ Toxicity — Repeated Exposure — Category 2. (Respiratory system).

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe the mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response ..... P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P308 + P313 If exposed or concerned, get medical advice/attention. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.

Storage..... P403+P433+P435 Store in a well ventilated area. Keep container tightly closed. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Other hazards..... None known.

**PRODUCT: PF 206 BRUSHABLE SEAM SEALER OFF WHITE****SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS | CAS #    | WT. % |
|----------------------------|----------|-------|
| Toluene                    | 108-88-3 | 5-10  |

**SECTION 04: FIRST-AID MEASURES**

|  |  |
|--|--|
| Eye contact.....   | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Obtain medical attention.  |
| Skin contact.....  | Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. If irritation persists, seek medical attention.   |
| Inhalation.....  | Move to fresh air. If not breathing, give artificial respiration. Obtain immediate medical attention.  |
| Ingestion.....   | Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs.                         |
| Most important symptoms and effects, ..... whether acute or delayed    | Causes skin irritation. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. |
| Immediate medical attention and special treatment needed, if necessary | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.   |

**SECTION 05: FIRE-FIGHTING MEASURES**

|  |  |
|--|--|
| Suitable extinguishing media.....  | Foam, "alcohol" foam, CO2, dry chemical, water fog.  |
| Unsuitable extinguishing media.....  | Do not use solid water streams or water jet.   |
| Specific hazards arising from the ..... hazardous product, such as the nature of any hazardous combustion products | Extremely flammable. Avoid heat, sparks and open flames. Hazardous combustion products may include but not limited to: Oxides of carbon (CO, CO2). Oxides of silica.   |
| Special protective equipment and ..... precautions for fire-fighters   | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. |

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

|   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | No action shall be taken involving any personal risk or without suitable training. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Wear appropriate personal protection equipment. |
| Environmental precautions.....                                      | Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.   |
| Methods and materials for containment and cleaning up               | Ventilate. Eliminate all sources of ignition. Shovel or vacuum spilled material into container for disposal. Treat original container as hazardous due to any residual product still in container.  |

**SECTION 07: HANDLING AND STORAGE**

|  |   |
|--|---|
| Precautions for safe handling.....                           | Keep away from heat, sparks, and open flame. Ground handling equipment. Avoid breathing vapours or mist. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle and open container with care. Employees should wash hands and face before eating or drinking. Handle in accordance with good industrial hygiene and safety practices. |
| Conditions for safe storage, including any incompatibilities | Store in a cool area, away from all sources of heat and ignition. Store away from fluorine and strong oxidizing agents. Keep container closed when not in use. Store away from sunlight. Incompatible materials include, but not limited to: Strong oxidizers.  |

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS        | TWA    | ACGIH TLV<br>STEL | PEL     | OSHA PEL<br>STEL   | REL                    | NIOSH |
|--------------------|--------|-------------------|---------|--------------------|------------------------|-------|
| Toluene            | 20 ppm | Not available     | 200 ppm | 500 ppm 10 minutes | 100 ppm / STEL 150 ppm |       |
| CA ON: TWA: 20 ppm |        |                   |         |                    |                        |       |

**PRODUCT: PF 206 BRUSHABLE SEAM SEALER OFF WHITE****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

|                                       |   |
|---------------------------------------|---|
| Personal Protective Equipment         |   |
| Respiratory/type.....                 | Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.   |
| Eye/type.....                         | Chemical safety goggles and full faceshield if a splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.  |
| Gloves/ type.....                     | Chemical resistant gloves. Consult your personal protective equipment supplier for additional recommendations.  |
| Clothing/type.....                    | Wear chemical resistant clothing. Consult your personal protective equipment supplier for additional recommendations.                                       |
| Footwear/type.....                    | Safety shoes. Consult your personal protective equipment supplier for additional recommendations.   |
| Other/type.....                       | Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products. |
| Appropriate engineering controls..... | Local exhaust should be used to maintain levels below the exposure limits.  |

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

|  |                             |
|--|-----------------------------|
| Appearance/Physical state.....                     | Light. Paste.               |
| Colour.....  | Dark grey.                  |
| Odour.....   | Aromatic.                   |
| Odour threshold (ppm).....                         | Not available.              |
| Vapour pressure (mm Hg).....                       | Not available.              |
| Vapour density (air=1).....                        | >1.                         |
| pH.....  | Not applicable.             |
| Relative Density (Specific Gravity).....           | 1.55 lbs/USG.               |
| Melting / Freezing point (deg C).....              | Not available.              |
| Solubility.....                                    | Not soluble in water.       |
| Initial boiling point / boiling range (deg C)..... | 111°C .                     |
| Evaporation rate.....                              | > 1.0. (butyl acetate = 1). |
| Flash point (deg C), method.....                   | 4 °C. (Tag Closed Cup).     |
| Auto ignition temperature (deg C).....             | 480°C.                      |
| Upper flammable limit (% vol).....                 | 7.                          |
| Lower flammable limit (% vol).....                 | 1.0.                        |
| Partition coefficient — n-octanol/water.....       | Not available.              |
| % Volatile by weight.....                          | 7.                          |
| VOC Content.....                                   | 140g/Ltr. – 0.93Lb's/ Gal.  |
| Decomposition temperature.....                     | Not available.              |
| Viscosity.....                                     | Not available.              |

**SECTION 10: STABILITY AND REACTIVITY**

|   |  |
|---|--|
| Chemical stability.....   | Stable at normal temperatures and pressures.   |
| Reactivity .....  | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions.....                                   | Hazardous polymerization will not occur.   |
| Conditions to avoid, including static discharge, shock or vibration ..... | Keep away from heat.   |
| Hazardous decomposition products.....                                     | Oxides of carbon (CO,CO2).   |

**SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS                            | LC50   | LD50  |
|--|--|---|
| Toluene                                | 8000ppm (rat inhalation)<br>400ppm mouse (inhalation 24hr)   | 5,000 mg/kg (rat ora);<br>12,124 mg/kg (rabbit dermal ) |
| Route of exposure.....                 | Eye contact. Skin contact. Inhalation. Ingestion.  |   |
| Skin corrosion/irritation.....         | Causes skin irritation. Dermatitis & defatting of the skin.  |   |
| Serious eye damage/eye irritation..... | Irritating to the eyes.  |   |
| Skin Sensitization.....                | Not available.   |   |
| Respiratory Sensitization.....         | May cause irritation.  |   |
| Carcinogenicity.....                   | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH. |   |
| Mutagenicity.....                      | Not available.   |   |
| Reproductive effects.....              | Suspected of damaging fertility or the unborn child.   |   |
| STOT-SE.....                           | Classification includes narcotic effects in a single exposure. Intentional misuse of this product may be harmful or fatal.                                       |   |
| STOT-RE.....                           | Conjunctiva & mucous membranes of upper respiratory tract may be irritated.  |   |
| Aspiration Hazard.....                 | Does not meet the criteria for this classification.  |   |

**PRODUCT: PF 206 BRUSHABLE SEAM SEALER OFF WHITE****SECTION 12: ECOLOGICAL INFORMATION**

|                                    |  |
|------------------------------------|--|
| Bioaccumulative potential.....     | No product data available.   |
| Ecotoxicity.....                   | Do not allow product to enter drains, sewers, bodies of water or soil. |
| Mobility in soil.....              | Not available.   |
| Persistence and degradability..... | Not available.   |

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Empty containers must be handled with care due to product residue.

**SECTION 14: TRANSPORT INFORMATION**

|                                   |   |
|-----------------------------------|---|
| TDG Classification.....           | UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II - This product meets the criteria for Limited Quantity Exemptions when packaged in containers equal to or less than 5 litres. |
| DOT Classification (Road).....    | UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II - Ltd Qty (1 Liters/0.3 Gallons). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.                      |
| IATA Classification (Air).....    | UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II. Do not ship by air without checking appropriate IATA regulations.  |
| IMDG Classification (Marine)..... | UN1133 - ADHESIVES - Class 3 - PG II EmS: F-E S-E. Check IMDG regulations for limited quantity exemptions.  |
| Marine Pollutant.....             | No.   |
| Proof of Classification.....      | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .  |

**SECTION 15: REGULATORY INFORMATION**

|  |   |
|--|---|
| CEPA status.....                                   | On Domestic Substances List (DSL).  |
| National Pollutant Release Inventory (NPRI).....   | (CAS # 108-88-3 (CAT 1A &5)).   |
| Environmental Emergency Regulations....            | Toluene (CAS # 108-88-3) Part 1.  |
| Categorization of the DSL.....                     | (CAS # 108-88-3).   |
| TSCA inventory status.....                         | All components are listed.  |
| OSHA.....  | This product is considered hazardous under the OSHA Hazard Communication Standard.  |
| SARA Title III                                     |   |
| Section 302 - extremely hazardous substances ..... | None known.   |
| Section 311/312 - hazard categories.....           | Immediate health, delayed health, fire hazard.  |
| Section 313.....                                   | Toluene.  |
| EPA hazardous air pollutants (HAPS) .....          | Toluene.  |
| 40CFR63  |   |
| California Proposition 65.....                     | *WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Toluene(D)). For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> . |

**SECTION 16: OTHER INFORMATION**

|  |   |
|--|---|
| Prepared by: .....   | REGULATORY AFFAIRS.   |
| Telephone number:.....                                     | (800) 387-7981.   |
| Disclaimer:.....   | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:.....  | 2022-11-30.   |
| Date of the latest revision of the safety data sheet ..... | 2024-03-25  |