



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF 214 FIRM-N-FLEX PREMIUM RUBBER BASED SEALER (BLACK)**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 214 FIRM-N-FLEX PREMIUM RUBBER BASED SEALER (BLACK)

Recommended use and restrictions on .. Adhesive applications. Seam sealer.  
use

Chemical family..... Hydrocarbons.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.

Hazard rating

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Corrosion/Irritation — Category 2. Serious Eye Damage/Eye Irritation — Category 2A. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Single Exposure — Category 3. (Respiratory System). (Narcotic Effects). Specific Target Organ Toxicity — Repeated Exposure — Category 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response ..... P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P308 + P313 If exposed or concerned, get medical advice/attention. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - For specific treatment see section 4 on this SDS. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye irritation persists get medical attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.

Storage..... P403+P433+P435 Store in a well ventilated area. Keep container tightly closed. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Other hazards..... None known.

**PRODUCT: PF 214 FIRM-N-FLEX PREMIUM RUBBER BASED SEALER (BLACK)**

**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Toluene	108-88-3	15-40
<<The actual concentration(s) withheld as a trade secret>> .		

**SECTION 04: FIRST-AID MEASURES**

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Skin contact..... Wash using plenty of soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Ingestion..... Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately.

Most important symptoms and effects, .... Product contains petroleum distillates.  
whether acute or delayed

Indication of immediate medical attention and special treatment needed, if necessary Treat symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable extinguishing media..... Carbon dioxide, dry chemical, foam.

Unsuitable extinguishing media..... Do not use solid water streams or water jet.

Specific hazards arising from the ..... May form combustible or explosive mixture with air. Closed containers may explode when hazardous product, such as the nature of exposed to extreme heat. Vapors are heavier than air. Vapors may form explosive mixture in air. Vapors may travel considerable distance to a source of ignition and flash back. Hazardous combustion products may include but not limited to: Oxides of carbon (CO, CO2).

Special protective equipment and ..... Firefighter should be equipped with self-contained breathing apparatus and full protective precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Evacuate personnel to a safe area. Wear appropriate personal protection equipment. Vapors can form explosive mixture in air. Vapours can accumulate in low areas. Use non-sparking tools and equipment to pick up the spilled material. Remove all sources of ignition.

Environmental precautions..... Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.

Methods and materials for containment and cleaning up Dike area to contain the spill, prevent runoff from going into drains, absorb residual material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste. Wear proper personal protection equipment.

**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating, drinking or smoking.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store at ambient temperatures. Strong acids.

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Toluene	20 ppm	Not available	200 ppm	500 ppm 10 minutes	100 ppm / STEL 150 ppm

CA ON: TWA: 20 ppm

Personal Protective Equipment  
Respiratory/type..... Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Consult your personal protective equipment supplier for additional recommendations.

**PRODUCT: PF 214 FIRM-N-FLEX PREMIUM RUBBER BASED SEALER (BLACK)****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Eye/type.....	Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists. Consult your personal protective equipment supplier for additional recommendations.
Gloves/ type.....	Gloves impervious to the material are recommended. Consult your personal protective equipment supplier for additional recommendations.
Clothing/type.....	Wear impervious protective clothing. Consult your personal protective equipment supplier for additional recommendations.
Footwear/type.....	Wear chemical resistant safety boots. Consult your personal protective equipment supplier for additional recommendations.
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.
Appropriate engineering controls.....	Local exhaust should be used to maintain levels below the exposure limits. Class I Group D approve devices.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state.....	Liquid.
Colour.....	Black.
Odour.....	Aromatic. Hydrocarbon.
Odour threshold (ppm).....	Unknown.
Vapour pressure (mm Hg).....	21. @ 20°C.
Vapour density (air=1).....	>1.
pH.....	Not available.
Relative Density (Specific Gravity).....	0.99.
Density.....	8.26 lbs.
Melting / Freezing point (deg C).....	Not determined.
Solubility.....	Insoluble.
Initial boiling point / boiling range (deg C).....	110.6 C. (231.08 F). (estimate).
Evaporation rate.....	Not available.
Flash point (deg C), method.....	4.0 C (39.2 F).
Auto ignition temperature (deg C).....	Not determined.
Decomposition temperature.....	Unknown.
Upper flammable limit (% vol).....	7.1. est.
Lower flammable limit (% vol).....	1.1. est.
Partition coefficient — n-octanol/water.....	Not available.
% Volatile by volume.....	53.9.
VOC Content.....	412 g/L.
Viscosity.....	Not available.
Specific Gravity (Liquid).....	0.99.

**SECTION 10: STABILITY AND REACTIVITY**

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity .....	Non-reactive under normal conditions of use, storage or transport.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static discharge, shock or vibration .....	Ignition sources. Incompatible with strong oxidizers. Vapours are heavier than air and may travel a considerable distance to an ignition source and flashback. Vapours may form explosive mixture with air.
Hazardous decomposition products.....	None known.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Toluene	8000ppm (rat inhalation) 400ppm mouse (inhalation 24hr)	5,000 mg/kg (rat ora); 12,124 mg/kg (rabbit dermal )
Route of exposure.....	Skin absorption. Inhalation.	
Effects of acute exposure.....	Causes skin irritation.	
Effects of chronic exposure.....	Anorexia and nervousness may persist for several months following acute overexposure. .	
Skin contact.....	Causes dry skin, dermatitis, de-fatting of the skin with chapping and cracking.	
Eye contact.....	Causes serious eye irritation.	
Ingestion.....	May be fatal if swallowed and enters airways.	
Inhalation (acute).....	Inebriation, followed by headache and nausea. Dizziness, convulsions and unconsciousness in severe cases.	
Carcinogenicity.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.	
Reproductive effects.....	Suspected of damaging fertility or the unborn child.	
STOT-SE.....	May cause drowsiness or dizziness.	

**PRODUCT: PF 214 FIRM-N-FLEX PREMIUM RUBBER BASED SEALER (BLACK)****SECTION 11: TOXICOLOGICAL INFORMATION**

STOT-RE..... May cause damage to the organs through prolonged or repeated exposure. .  
 Aspiration Hazard..... May be fatal if swallowed and enters airways.

**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.  
 Persistence and degradability..... Product data not available.  
 Bioaccumulative potential..... Partition coefficient n-octanol/water (log Kow) 2.73 .  
 Mobility in soil..... Product data not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II - This product meets the criteria for Limited Quantity Exemptions when packaged in containers equal to or less than 5 litres.  
 DOT Classification (Road)..... UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II - Ltd Qty 5 L). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.  
 IATA Classification (Air)..... UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.  
 IMDG Classification (Marine)..... UN1133 - ADHESIVES containing flammable liquid - Class 3 - Packing Group II EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.  
 Marine Pollutant..... No.  
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**SECTION 15: REGULATORY INFORMATION**

CEPA status..... On Domestic Substances List (DSL).  
 National Pollutant Release Inventory (NPRI)(CAS # 108-88-3 (CAT 1A &5)).  
 Environmental Emergency Regulations.... Toluene (CAS # 108-88-3) Part 1.  
 Categorization of the DSL..... (CAS # 108-88-3).  
 TSCA inventory status..... All components are listed.  
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.  
 SARA Title III  
 Section 302 - extremely hazardous ..... None.  
 substances  
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.  
 Section 313..... Toluene.  
 EPA hazardous air pollutants (HAPS) ..... Toluene.  
 40CFR63  
 California Proposition 65..... \*\*\* ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Toluene(D)). For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16: OTHER INFORMATION**

Prepared by: ..... REGULATORY AFFAIRS.  
 Telephone number:..... (800) 387-7981.  
 Disclaimer:..... **DISCLAIMER:** All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety data sheet .. 2024-12-09