

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

PRODUCT: PF 412 BUTYL TAPE 3/8"

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.

604 McGeachie Drive

Milton, Ontario L9T3Y5 Tel (905) 878-4990 Fax (905) 878-1189

PF 412 BUTYL TAPE 3/8"

Product identifier..... Recommended use and restrictions on ...

Chemical family.....

NFPA rating..... HMIS.....

Health: 0 Fire: 1 Reactivity: 0.

H:0 F:1 R:0.

Automotive.

For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300. 24 hour emergency number:.....

For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION

Not a classified or a controlled product.

Hazard Classification..... Not classified. Hazard Description..... Not classified. Note Product is an article.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS CAS# WT. %

PRODUCT IS AN ARTICLE AND NOT A CHEMICAL

SECTION 04: FIRST-AID MEASURES

Flush for 15 minutes using plenty of water. If irritation persists seek medical attention. Eve contact.....

Skin contact..... Wash skin with soap and water. If irritation persists, seek medical attention.

No specific treatment is necessary since this material is not likely to be hazardous by Inhalation.....

inhalation.

Ingestion..... Ingestion is unlikely. Contact a physician if unusual reaction is noted.

May cause mild skin irritation. May cause slight eye irritation. Most important symptoms and effects,

whether acute or delayed Additional information..... In the event of an incident involving this product ensure that medical authorities are

provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing

media

Specific hazards arising from the hazardous product, such as the nature of

any hazardous combustion products Special protective equipment and precautions for fire-fighters

Carbon dioxide, dry chemical, foam. Treat as a petroleum fire.

Oxides of carbon (CO, CO2). Hydrocarbons. Toxic fumes.

Firefighter should be equipped with self-contained breathing apparatus and full protective

clothing to protect against potentially toxic and irritating fumes.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Wear recommended protective equipment. Pick up solids and put in a dust bin. Keep in a Leak/spill.....

suitable, closed container for disposal.

SECTION 07: HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Handle in accordance with good industrial Precautions for safe handling..... hygiene and safety practices. Employees should wash hands and face before eating or

drinking.

Conditions for safe storage, including any Store in a cool, dry and well ventilated area. Protect containers from physical damage. Do incompatibilities not store above 49C.



PRODUCT: PF 412 BUTYL TAPE 3/8"

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS TWA STEL PEL STEL REL	
-----------------------------------	--

None required under normal use. Avoid breathing vapours. Respiratory/type.....

Where contact with this material is possible, eye protection is recommended. May cause Eye/type.....

eye irritation after repeated or prolonged contact. Gloves/ type.....

Use of proper hygiene practices in the workplace is recommended. May cause skin

irritation after repeated or prolonged contact.

Clothing/type..... Wear long sleeves and trousers to prevent dermal exposure. May cause skin irritation after

repeated or prolonged contact.

Safety boots per local regulations. Educate and train employees on the safe use and handling of the product. Employees Footwear/type..... Other/type.....

should wash their hands and face before eating, drinking, or using tobacco products.

Good general ventilation should be sufficient to control airborne levels.

Appropriate engineering controls.....

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Black mastic, soft solid. Black. Colour..... Odour..... Faint. Characteristic odour. Odour threshold (ppm)..... Not applicable. Vapour pressure (mm Hg)..... Not applicable. Vapour density (air=1)..... Not applicable. Not applicable. pH..... Relative Density (Specific Gravity)..... ~1.3.

Melting / Freezing point (deg C)..... Not applicable. Solubility..... Not applicable. Initial boiling point / boiling range (deg C). Not applicable.

Evaporation rate..... Not applicable. Flash point (deg C), method..... > 232 COC. Auto ignition temperature (deg C)..... Not applicable. Upper flammable limit (% vol)...... Lower flammable limit (% vol)..... Not applicable. No Data.

Partition coefficient — n-octanol/water..... No data. VOC (less water)..... Non volatile. Viscosity..... No data.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....

Stable at normal temperatures and pressures. Avoid heat, sparks and flames. Hazardous polymerization will not occur. Reactivity

Possibility of hazardous reactions..... Will not occur under normal temperature and pressure.

Conditions to avoid, including static Incompatible with strong solvents.

discharge, shock or vibration

Hazardous decomposition products...... Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

Route of exposure..... Not expected to pose any hazards.

Effects of acute exposure..... May cause slight eye and slight skin irritation.

Effects of chronic exposure..... Prolonged or repeated contact may cause eye and skin irritation.

Carbon black has been shown to cause cancer in laboratory animals. The relevance of this Carcinogenicity of material..... finding to humans is uncertain. It is listed as a carcinogen by the International Agency for

Research on Cancer (IARC). . Quartz (Crystalline Silica) is listed by IARC in Group 1 as a

carcinogen.

Reproductive effects..... None.

SECTION 12: ECOLOGICAL INFORMATION

Persistence and degradability..... Not available.



PRODUCT: PF 412 BUTYL TAPE 3/8"

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal . and methods of disposal, including any contaminated packaging

California Proposition 65.....

Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

Not regulated.
Not regulated.
Not regulated.
Not regulated.
No.

SECTION 15: REGULATORY INFORMATION

***! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer. (Carbon black - airborne, unbound particles of respirable size). (Silica, crystalline (airborne particles of respirable size). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not

relate to its use in combination with any other material or in any other process.

Review Date: 2022-11-30. Date of the latest revision of the safety 2018-05-10

data sheet

