



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 425 BUTYL TAPE BULK 1/8" X 1/4" X 15'

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 425 BUTYL TAPE BULK 1/8" X 1/4" X 15'

Recommended use and restrictions on .. Automotive.
use

Chemical family..... Article.

NFPA rating..... Health: 0 Fire: 1 Reactivity: 0.

HMIS..... H:0 F:1 R:0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION

Signal Word..... Not a classified or a controlled product.

Hazard Classification..... Not classified.

Hazard Description..... Not classified.

Note Product is an article.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|----------------------------|-------|-------|
|----------------------------|-------|-------|

PRODUCT IS AN ARTICLE AND NOT A CHEMICAL

SECTION 04: FIRST-AID MEASURES

Eye contact..... Flush for 15 minutes using plenty of water. If irritation persists seek medical attention.

Skin contact..... Wash skin with soap and water. If irritation persists, seek medical attention.

Inhalation..... No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

Ingestion..... Ingestion is unlikely. Contact a physician if unusual reaction is noted.

Most important symptoms and effects, May cause mild skin irritation. May cause slight eye irritation.
whether acute or delayed

Additional information..... In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing Carbon dioxide, dry chemical, foam. Treat as a petroleum fire.
media

Specific hazards arising from the Oxides of carbon (CO, CO2). Hydrocarbons. Toxic fumes.
hazardous product, such as the nature of
any hazardous combustion products

Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective
precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Wear recommended protective equipment. Pick up solids and put in a dust bin. Keep in a
suitable, closed container for disposal.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Handle in accordance with good industrial
hygiene and safety practices. Employees should wash hands and face before eating or
drinking.

Conditions for safe storage, including any Store in a cool, dry and well ventilated area. Protect containers from physical damage. Do
incompatibilities not store above 49C.

PRODUCT: PF 425 BUTYL TAPE BULK 1/8" X 1/4" X 15'

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|---------------------------------------|-----|-------------------|-----|------------------|-----|---|
| Respiratory/type..... | | | | | | None required under normal use. Avoid breathing vapours. |
| Eye/type..... | | | | | | Where contact with this material is possible, eye protection is recommended. May cause eye irritation after repeated or prolonged contact. |
| Gloves/ type..... | | | | | | Use of proper hygiene practices in the workplace is recommended. May cause skin irritation after repeated or prolonged contact. |
| Clothing/type..... | | | | | | Wear long sleeves and trousers to prevent dermal exposure. May cause skin irritation after repeated or prolonged contact. |
| Footwear/type..... | | | | | | Safety boots per local regulations. |
| Other/type..... | | | | | | Educate and train employees on the safe use and handling of the product. Employees should wash their hands and face before eating, drinking, or using tobacco products. |
| Appropriate engineering controls..... | | | | | | Good general ventilation should be sufficient to control airborne levels. |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|------------------------------|
| Appearance/Physical state..... | Black mastic, soft solid. |
| Colour..... | Black. |
| Odour..... | Faint. Characteristic odour. |
| Odour threshold (ppm)..... | Not applicable. |
| Vapour pressure (mm Hg)..... | Not applicable. |
| Vapour density (air=1)..... | Not applicable. |
| pH..... | Not applicable. |
| Relative Density (Specific Gravity)..... | ~1.3. |
| Melting / Freezing point (deg C)..... | Not applicable. |
| Solubility..... | Not applicable. |
| Initial boiling point / boiling range (deg C)..... | Not applicable. |
| Evaporation rate..... | Not applicable. |
| Flash point (deg C), method..... | > 232 COC. |
| Auto ignition temperature (deg C)..... | Not applicable. |
| Upper flammable limit (% vol)..... | Not applicable. |
| Lower flammable limit (% vol)..... | No Data. |
| Partition coefficient — n-octanol/water..... | No data. |
| VOC (less water)..... | Non volatile. |
| Viscosity..... | No data. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Hazardous polymerization will not occur. |
| Possibility of hazardous reactions..... | Will not occur under normal temperature and pressure. |
| Conditions to avoid, including static | Incompatible with strong solvents. |
| discharge, shock or vibration | |
| Hazardous decomposition products..... | Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|----------------------------------|------|------|
| Route of exposure..... | | |
| Effects of acute exposure..... | | |
| Effects of chronic exposure..... | | |
| Carcinogenicity of material..... | | |
| Reproductive effects..... | | |

Not expected to pose any hazards.
 May cause slight eye and slight skin irritation.
 Prolonged or repeated contact may cause eye and skin irritation.
 Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by the International Agency for Research on Cancer (IARC). Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen.
 None.

SECTION 12: ECOLOGICAL INFORMATION

Persistence and degradability..... Not available.

PRODUCT: PF 425 BUTYL TAPE BULK 1/8" X 1/4" X 15'

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | Not regulated. |
| DOT Classification (Road)..... | Not regulated. |
| IATA Classification (Air)..... | Not regulated. |
| IMDG Classification (Marine)..... | Not regulated. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|---|
| CEPA status..... | This is an article and not subject to the DSL. |
| SARA Title III Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | None. |
| Section 313..... | None. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | None. |
| California Proposition 65..... | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Carbon black - airborne, unbound particles of respirable size). (Silica, crystalline (airborne particles of respirable size). For more information, go to www.P65Warnings.ca.gov . |

SECTION 16: OTHER INFORMATION

| | |
|---|---|
| Prepared by: | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com . |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:..... | 2022-11-30. |
| Date of the latest revision of the safety data sheet .. | 2018-05-10 |