

A temporary water-washable clear view coating that is applied with regular spray equipment. It levels to a smooth transparent film that will not distort the booth's lighting or the clarity of the windows. To remove, simply wash off or peel off and apply a new Glass Coating. Product is ready to use.

PRODUCT	SIZE
PF 448-1	3.78 L (U.S. Gallon)
PF 448-5	18.9 L (5 U.S. Gallons)

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!
IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Paint booth walls

ADVANTAGES:

- Water-washable

SPRAY GUN AND PRESSURE:

Gun Type	Fluid Tip	Air Pressure
Gravity Feed	1.8 - 2.0 mm	30-35 psi
Suction Feed	1.8 - 2.0 mm	40-50 psi

DIRECTIONS FOR USE:

1. Clean glass to remove any loose dirt or dry overspray.
2. Apply 2-3 coats allowing 15-20 minutes between coats.
3. Clean equipment after use with soap and water.

COVERAGE:	1 gallon depending on surface condition. 200 sq. ft. per gallon.
RECOAT:	Spray application 20 minutes at 21°C (70°F). Paint roller 1 hour at 21°C (70°F).
DRY TIME:	30-40 minutes at 21°C (70°F).
DRY TO USE:	60 minutes

Caution: Coagulation may occur if product is frozen or heated.

TECHNICAL DATA:

	PF 448-1, PF 448-5
Physical State	Liquid

Color:	Clear to milky
Odour:	Slightly acrylic
Solubility :	Miscible
Flash point:	Not applicable
Auto ignition temperature:	Not applicable
VOC:	0.49 lb/usg • 58.71 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.