

Water-based clear Liquid Mask to protect against paint overspray. Effective and economical masking solution. Dries to a firm coating that will not adhere to skin and clothing. Excellent for booth coating. Will dissolve easily when washed with cold water. Use on body panels, door jambs, engine compartments, wheel wells, grills, etc.

PRODUCT	SIZE
PF 450-1	3.78 L (U.S. Gallon)
PF 450-5	18.9 L (5 U.S. Gallons)
PF 450-15	58 L (15 U.S. Gallons)
PF 450-55	205 L (55 U.S. Gallons)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Body panels
- Door jambs
- Engine compartments
- Wheel wells
- Grills, & etc

ADVANTAGES:

- Ready to use
- Transparent
- Easy to apply
- Non-tacky
- Easy removal
- No solvent

SPRAY GUN AND PRESSURE:

Gun Type	Fluid Tip	Air Pressure
Siphon Feed	1.8 - 2.0 mm	40-50 psi
Gravity Feed	1.8 - 2.0 mm	35-45 psi
HVLP	1.8 - 2.0 mm	10 psi

Clean gun and dry thoroughly before storing gun to avoid corrosion of internal parts.

DIRECTIONS FOR USE:

1. Mask off surface to be painted with masking paper.
2. Apply one full wet coat of Liquid Mask on area to be protected.
3. Let dry for 20 to 30 minutes.
4. Remove any Liquid Mask overspray from surface to be painted.

5. Prepare the surface for painting as usual.
6. Apply primer, paint and/or clear and let cure as per manufacturers recommendations.
7. Once painting and buffing process is completed and cured, simply wet vehicle with water, allow to stand for 1-2 minutes before washing.

DRY TIME:	20 to 30 minutes at 65°F-75°F (18°C-24°C)
BAKING:	Liquid Mask can withstand baking temperatures of 150°F (76°C) without losing its effectiveness.

Caution: Do not use on fabric or fabric covered roofs.

TECHNICAL DATA :

	PF 450-1, PF 450-5, PF 450-15, PF 450-55
Physical State	Liquid
Color:	Opaque, translucent
Odour:	Mild
Solubility :	Soluble
Flash point:	>100°C (>212°F) Does not support combustion
Auto ignition temperature:	Not applicable
VOC:	40 g/L • 0.33 lbs/usg

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.