



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 456 ULTRA FAST DRY

SECTION 01: IDENTIFICATION

Product identifier..... PF 456 ULTRA FAST DRY
 Other means of identification
 Chemical family..... Mixture.
 Recommended use and restrictions on .. Paints. This product should not be used for any other purpose other than the ones
 use described in this section.
 Initial supplier identifier..... Pro Form Products Ltd.
 604 McGeachie Drive
 Milton, Ontario L9T3Y5
 Tel (905) 878-4990 Fax (905) 878-1189
 24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
 IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
 ** For medical emergencies contact your local poison control centre **.
 -
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F:4 R: 0.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye
 Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category
 3. (narcotic effects). (respiratory system). Germ Cell Mutagenicity 1. Carcinogenicity —
 Category 2. Reproductive Toxicity — Category 1.
 Signal Word..... DANGER.
 Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an
 allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory
 irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects.
 H351 This product contains ingredients that are suspected of causing cancer. H360 May
 damage fertility or the unborn child.
 Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all
 safety instructions have been read and understood. P210 Keep away from heat, sparks,
 open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240
 Ground and bond container and receiving equipment. P241 Use explosion proof
 equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against
 static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly
 after handling. P271 Use only outdoors or in a well ventilated area. P272 Contaminated
 work clothing should not be allowed out of the workplace. P280 Wear protective gloves and
 eye protection.
 Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 +
 P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse
 thoroughly with water and use safety shower . P302 + P352 - If on skin: wash with plenty of
 water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313
 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes
 rinse cautiously with water for several minutes. Remove contact lenses, if present and easy
 to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get
 medical attention. P308 + P313 If exposed or concerned, get medical advice/attention.
 P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool.
 P405 Store locked up.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
 Note This product mixture has been classified based on its ingredients.

PRODUCT: PF 456 ULTRA FAST DRY**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	10-30
4-Chlorobenzotrifluoride	98-56-6	10-30
n-Butyl Acetate	123-86-4	5-10
Methyl N-Amyl Ketone	110-43-0	5-10
N-Butyl Propionate	590-01-2	5-10
Methyl Isobutyl Ketone	108-10-1	1-5
Dibutyltin Bis (Acetylacetonate)	22673-19-4	0.1-1
Xylene	1330-20-7	0.1-1
Ethylbenzene	100-41-4	0.1-1
Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate	41556-26-7	0.1-1
<<The actual concentration(s) withheld as a trade secret>> .		

SECTION 04: FIRST-AID MEASURES

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Obtain medical attention immediately.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. Wash clothing before reuse.
Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Obtain medical attention.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin and eye irritation. Acetone is a serious eye irritant that can cause reversible damage to the cornea. It is slightly irritating to the skin. Can cause skin sensitization. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Contains ingredients that; Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. This product contains ingredients that may cause cancer.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	Carbon dioxide, dry chemical, foam. Water spray. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Extremely flammable. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO2).
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Vapour forms a flammable / explosive mixture with air between upper and lower flammable limits. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Acetone is a highly flammable liquid. It is easily ignited in the presence of heat, an ignition source such as a naked flame or a spark (including electrostatic discharge). Aqueous solutions of acetone can also ignite. Acetone vapors are heavier than air and can travel a long distance to an ignition source and cause flashback.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Extremely flammable liquid. No action shall be taken involving any personal risk or without suitable training. Take precautions against static discharge. Equipment should be grounded. Use non-sparking tools and equipment to pick up the spilled material. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways.
--	--

PRODUCT: PF 456 ULTRA FAST DRY**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Methods and materials for containment and cleaning up

Leak/spill..... Wear proper protective equipment. Eliminate all sources of ignition. Ventilate area to remove the remaining vapours. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Containers must be grounded and bonded. Do not use near sources of ignition, open flames or sparks. Do not cut, drill, weld or grind on or near the container. Open containers slowly to allow for any pressure build-up to escape. Keep containers closed when not in use. Prevent accumulation of electrostatic charges. Avoid skin and eye contact. Avoid breathing vapours or mist. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities Store in a cool, dry and well ventilated area. Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Acetone	250 ppm TLV CA ON: 500ppm (TWA); 750ppm (STEL)	500 ppm	1,000 ppm	Not established	250 ppm	
4-Chlorobenzotrifluoride	Not established	Not established	Not established	Not established	Not established	Not established
n-Butyl Acetate	50 ppm CA ON: 50ppm (TWA), 150ppm (STEL)	150 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm	
Methyl N-Amyl Ketone	50 ppm ON OEL: 25 ppm; 115 mg/m3 (TWA)	Not established	100 ppm	465 mg/m3 TWA	Not established	
N-Butyl Propionate	Not Established	Not Established	Not Established	Not Established	Not Established	Not Established
Methyl Isobutyl Ketone	50 ppm ON: 20 ppm (TWA), 75 ppm (STEL)	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm	
Dibutyltin Bis (Acetylacetonate)	Not established	Not established	Not established	Not established	Not established	Not established
Xylene	50 ppm CA ON: 100ppm (TWA); 150ppm (STEL)	150 ppm	100 ppm TWA	Not established	Not established	
Ethylbenzene	100 ppm CA ON: 20ppm (TWA)	125 ppm	100 ppm	Not established	100 ppm / STEL 125 ppm	
Bis (1,2,2,6,6-Pentamethyl-4- Piperidyl) Sebacate	Not established	Not established	Not established	Not established	Not established	Not established

Appropriate engineering controls..... Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.

Respiratory/type..... Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator.

Eye/type..... Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists.

Gloves/ type..... Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Contact glove supplier for recommendations.

PRODUCT: PF 456 ULTRA FAST DRY**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Clothing/type..... Wear adequate protective clothes. Wear long sleeves and trousers to prevent dermal exposure.
 Footwear/type..... Safety boots per local regulations.
 Other/type..... Eye wash facility and emergency shower should be in close proximity. Employees should wash their hands and face before eating, drinking, or using tobacco products.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid.
 Colour..... Clear, colourless.
 Odour..... Pungent odour. Fruity odour.
 Odour threshold (ppm)..... Not available.
 pH..... Not available.
 Melting / Freezing point (deg C)..... Not available.
 Initial boiling point / boiling range (deg C). 56°C (133 °F). (acetone).
 Flash point (deg C), method..... -18°C. (estimate; lowest flash point ingredient).
 Evaporation rate..... Not available.
 Flammability (solids and gases)..... Not applicable. Flammable liquid.
 Upper flammable limit (% vol)..... 12.6.
 Lower flammable limit (% vol)..... 1.0.
 Vapour pressure (mm Hg)..... Not available.
 Vapour density (air=1)..... Not available.
 Relative Density (Specific Gravity)..... 0.968.
 Pounds / USG..... 8.08.
 Solubility..... Partially in water.
 Partition coefficient — n-octanol/water..... Not available.
 Auto ignition temperature (deg C)..... > 200°C.
 Decomposition temperature..... Not available.
 Viscosity..... 15 sec Zahn #2.
 % Volatile by volume..... 48.35.
 VOC (less water)..... 2.01 lb/USG; 240.9 g/L.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product is stable; hazardous polymerization will not occur.
 Chemical stability..... Stable at normal temperatures and pressures.
 Possibility of hazardous reactions..... Hazardous polymerization will not occur.
 Conditions to avoid, including static Avoid heat, spark, open flames. Electrostatic charge.
 discharge, shock or vibration
 Incompatible materials..... Strong acids. Strong bases. Strong oxidizers. Reducing agents. Aldehydes. Acetone may ignite or react violently with strong oxidizing agents, such as chromic acid, chromium trioxide, chromyl chloride, hot nitric acid, potassium permanganate (in an alkaline medium), or peroxides.
 Hazardous decomposition products..... Hazardous decomposition products depend on temperature, air supply, and the presence of other materials. No hazardous decomposition products when stored and handled correctly. See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	50,100 mg/m ³ 8 hours, rat	5,800 mg/kg (rat oral)
4-Chlorobenzotrifluoride	4479 ppm	>6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal)
n-Butyl Acetate	>33 mg/L vapour, 5.2 mg/L (rat) dust/mist	10760 mg/kg (rat, oral) 14112 mg/kg (rabbit, dermal)
Methyl N-Amyl Ketone	Not Available	1,670 mg/kg rat oral 12,600 mg/kg rabbit dermal
N-Butyl Propionate	>23.7 mg/L 6hr.	>5000 mg/kg (oral, rat)
Methyl Isobutyl Ketone	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal
Dibutyltin Bis (Acetylacetonate)	Not Available	1864 mg/kg (oral, rat)
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Ethylbenzene	No data	3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal

PRODUCT: PF 456 ULTRA FAST DRY**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate	Not Available	2369-3920 mg/kg (oral rat), >2000 mg/kg (dermal rabbit)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Symptoms related to the physical, chemical and toxicological characteristics		
Effects of acute exposure.....	Causes skin irritation. Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Irritating to mucous membranes and upper respiratory tract. Excessive inhalation of this product may cause dizziness.	
Effects of chronic exposure.....	Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Sensitizing capability of material.....	May cause sensitization by skin contact.	
Carcinogenicity of material.....	Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B). Ethylbenzene is classified as an A3 known animal carcinogen.	
Reproductive effects.....	Dibutyltin Bis (Acetylacetonate):. May cause genetic defects. Reported to be a reproductive toxin.	
Specific Target Organ Toxicity	May cause drowsiness or dizziness. May cause respiratory irritation.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	Product data not available.
Persistence and degradability.....	Product data not available.
Bioaccumulative potential.....	Product data not available.
Mobility in soil.....	Product data not available.
Other adverse effects.....	Do not allow to enter waters, waste water or soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Do not heat or cut empty containers with electric or gas torch.
---	--

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
DOT Classification (Road).....	UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
IATA Classification (Air).....	UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	Potential marine pollutant.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories	Immediate health, delayed health, fire hazard.
Section 313.....	Methyl Isobutyl Ketone. Xylene.
EPA hazardous air pollutants (HAPS) 40CFR63	Ethylbenzene. Methyl Isobutyl Ketone. Toluene. Xylene.
California Proposition 65.....	*** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Methyl Isobutyl Ketone (D)). (Toluene). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Methyl Isobutyl Ketone (C)). For more information, go to www.P65Warnings.ca.gov .

PRODUCT: PF 456 ULTRA FAST DRY

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... **DISCLAIMER:** All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety .. 2021-01-14
 data sheet