



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 465 PREMIUM RESERVE 4:1

SECTION 01: IDENTIFICATION

Product identifier..... PF 465 PREMIUM RESERVE 4:1
 Other means of identification
 Chemical family..... Mixture.
 Recommended use and restrictions on .. Clearcoat.
 use
 Initial supplier identifier..... Pro Form Products Ltd.
 604 McGeachie Drive
 Milton, Ontario L9T3Y5
 Tel (905) 878-4990 Fax (905) 878-1189
 24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
 IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
 ** For medical emergencies contact your local poison control centre **.
 -
 NFPA rating..... Health: 1 Fire: 4 Reactivity: 0.
 HMIS..... H: 1 F: 4 R: 0.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system).
 Signal Word..... DANGER.
 Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
 Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.
 Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.
 Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
 Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
4-Chlorobenzotrifluoride	98-56-6	10-30
Acetone	67-64-1	10-30
Butyl Acetate	123-86-4	10-30

PRODUCT: PF 465 PREMIUM RESERVE 4:1**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate 41556-26-7 0.1-1
 <<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Ingestion..... If swallowed, do not induce vomiting. Give large quantity of water. Call a physician immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs.

Skin contact..... Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. If irritation persists, seek medical attention.

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Consult a physician if irritation continues.

Most important symptoms and effects, Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. whether acute or delayed Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Can cause skin sensitization. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause respiratory irritation.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing "Alcohol" foam, CO₂, dry chemical. Do not use water in a jet.
 media

Specific hazards arising from the Extremely flammable. Thermal decomposition products are toxic. May include:. Oxides of hazardous product, such as the nature of carbon (CO, CO₂). Hydrocarbon fumes and smoke.
 any hazardous combustion products

Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours.

Unusual fire / explosion hazards..... Extremely flammable. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Acetone is a highly flammable liquid. It is easily ignited in the presence of heat, an ignition source such as a naked flame or a spark (including electrostatic discharge). Aqueous solutions of acetone can also ignite. Acetone vapors are heavier than air and can travel a long distance to an ignition source and cause flashback.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective Extremely flammable liquid. No action shall be taken involving any personal risk or without equipment and emergency procedures suitable training. Equipment should be grounded. Take precautions against static discharge. Use non-sparking tools and equipment to pick up the spilled material. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways.

Methods and materials for containment and cleaning up

Leak/spill..... Eliminate all sources of ignition. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Pick up and place in a tightly-sealed container duly identified. Use an appropriate technique to prevent any environmental contaminations. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

PRODUCT: PF 465 PREMIUM RESERVE 4:1**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle and open container with care. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks, and open flames. Store in a cool, dry and well ventilated area. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV		OSHA PEL		NIOSH REL
	TWA	STEL	PEL	STEL	
4-Chlorobenzotrifluoride	Not established	Not established	Not established	Not established	Not established
Acetone	250 ppm TLV ON: 500ppm (TWA); 750ppm (STEL)	500 ppm	1,000 ppm	Not established	250 ppm
Butyl Acetate	150 ppm	200 ppm	150 ppm	200 ppm vacated	150 ppm - STEL 200 ppm
Bis (1,2,2,6,6-Pentamethyl-4- Piperidyl) Sebacate	Not established	Not established	Not established	Not established	Not established
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.				
Personal Protective Equipment Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Eye/type.....	Chemical safety goggles and full faceshield if a splash hazard exists.				
Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Contact glove supplier for recommendations.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Eye wash facility and emergency shower should be in close proximity. Employees should wash their hands and face before eating, drinking, or using tobacco products.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid.

Colour..... Clear, colourless.

Odour..... Characteristic odour.

Odour threshold (ppm)..... Not available.

pH..... Not available.

Melting / Freezing point (deg C)..... < -23 C.

Initial boiling point / boiling range (deg C)..... > 56 °C.

Flash point (deg C), method..... -18°C. (estimate; lowest flash point ingredient).

Evaporation rate..... Not available.

Flammability (solids and gases)..... Not applicable. Flammable liquid.

Upper flammable limit (% vol)..... 12.6.

Lower flammable limit (% vol)..... 0.9.

Vapour pressure (mm Hg)..... Not available.

Vapour density (air=1)..... >1.

Relative Density (Specific Gravity)..... 1.062.

Pounds / USG..... 8.86.

Solubility..... Not available.

Partition coefficient — n-octanol/water..... Not available.

Auto ignition temperature (deg C)..... Not available.

Decomposition temperature..... Not available.

Viscosity..... 15 sec Zahn #2 .

VOC (less water)..... 1.30 lbs/USG; 155.8 g/L.

PRODUCT: PF 465 PREMIUM RESERVE 4:1**SECTION 10: STABILITY AND REACTIVITY**

Reactivity	Product is stable; hazardous polymerization will not occur.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static discharge, shock or vibration.....	Avoid heat, spark, open flames. Electrostatic charge.
Incompatible materials.....	Strong acids. Strong bases. Strong oxidizers. Aldehydes. Ammonia. Peroxides. Reducing agents. Acetone may ignite or react violently with strong oxidizing agents, such as chromic acid, chromium trioxide, chromyl chloride, hot nitric acid, potassium permanganate (in an alkaline medium), or peroxides.
Hazardous decomposition products.....	No hazardous decomposition products when stored and handled correctly. See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
4-Chlorobenzotrifluoride	4479 ppm	>6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal)
Acetone	50,100 mg/m ³ 8 hours, rat	5,800 mg/kg (rat oral)
Butyl Acetate	390 ppm (4 hr)	10768 mg/kg oral rat 17600 mg/kg dermal rabbit
Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate	Not Available	2369-3920 mg/kg (oral rat), >2000 mg/kg (dermal rabbit)
Route of exposure.....	Eye contact. Skin contact. Skin absorption. Inhalation.	
Symptoms related to the physical, chemical and toxicological characteristics		
Effects of acute exposure.....	May cause severe eye irritation. May damage eyes. Causes skin irritation. Persons previously sensitized can experience an allergic reaction with symptoms of reddening, itching, swelling and rash. May be absorbed by the skin. Inhalation of high vapour may cause central nervous system effects, dizziness, headache, nausea, or loss of coordination.	
Effects of chronic exposure.....	Chronic exposure to organic solvent vapours have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Carcinogenicity of material.....	The components of this product are not listed by IARC, NTP or regulated as a carcinogen by OSHA.	
Sensitizing capability of material.....	May cause sensitization by skin contact.	
Reproductive effects.....	Acetone has been shown to cause reproductive effects in rats by ingestion and inhalation.	
Specific Target Organ Toxicity	May cause drowsiness or dizziness. May cause respiratory irritation.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	Product data not available.
Persistence and degradability.....	Product data not available.
Bioaccumulative potential.....	Product data not available.
Mobility in soil.....	Product data not available.
Other adverse effects.....	Do not allow to enter waters, waste water or soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Do not heat or cut empty containers with electric or gas torch. Empty containers must be handled with care due to product residue.
---------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
DOT Classification (Road).....	UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
IATA Classification (Air).....	UN1263 - PAINT - Class 3 - Packing Group II. Do not ship by air without checking appropriate IATA regulations. Limited Quantity.
IMDG Classification (Marine).....	UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.

PRODUCT: PF 465 PREMIUM RESERVE 4:1

SECTION 14: TRANSPORT INFORMATION

Marine Pollutant..... Potential marine pollutant.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... None above De minimus % limit.
 EPA hazardous air pollutants (HAPS) Toluene.
 40CFR63
 California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Toluene). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... **DISCLAIMER:** All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety .. 2021-01-15
 data sheet