



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY**

### SECTION 01: IDENTIFICATION

Product identifier..... PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY  
Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189  
24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);  
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.  
\*\* For medical emergencies contact your local poison control centre \*\*.  
Recommended use and restrictions on use .. Paints. This product should not be used for any other purpose other than the ones  
described in this section. for industrial use only-keep out of reach of children .  
Chemical family..... Mixture.  
Hazard rating  
NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.  
HMIS..... H: 2 F: 3 R: 0.

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.  
Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritant 2. Specific Target Organ Toxicity — Single Exposure — Category 3. Specific Target Organ Toxicity — Repeated Exposure — Category 1.  
Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to the liver and kidneys through prolonged or repeated exposure.  
Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.  
Response ..... P302 + P352 - If on skin: wash with plenty of water. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P321 - For specific treatment see section 4 on this SDS. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P314 - Get medical advice/attention if you feel unwell. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish.  
Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool.  
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

**PRODUCT: PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY****SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Talc	14807-96-6	15-25
Titanium Dioxide	13463-67-7	5-10
Xylene	1330-20-7	5-10
Propylene Glycol Methyl Ether	107-98-2	1-5
Acetone	67-64-1	3-7
Ethyl 3-Ethoxypropionate	763-69-9	1-5
Butyl Alcohol	71-36-3	1-5
Carbon Black	1333-86-4	0.1-1

**SECTION 04: FIRST-AID MEASURES**

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO <sub>2</sub> , dry chemical. In cases of larger fires, water spray should be used.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO <sub>2</sub> ). Oxides of nitrogen.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

**PRODUCT: PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	ACGIH TLV		PEL	OSHA PEL		NIOSH
	TWA	STEL		STEL	REL	
Talc	2 mg/m3 CA ON: 2mg/kg (TWA)	Not established	2 mg/m3 TWA	Not established	Not established	Not established
Titanium Dioxide	10 mg/m3 CA ON: 10 mg/m3 (TWA)	Not established	15 mg/m3	Not established	Not established	Not established
Xylene	50 ppm CA ON: 100ppm (TWA); 150ppm (STEL)	150 ppm	100 ppm TWA	Not established	Not established	Not established
Propylene Glycol Methyl Ether	100 ppm	150 ppm	Not established	Not established	100 ppm	
Acetone	250 ppm TLV CA ON: 500ppm (TWA); 750ppm (STEL)	500 ppm	1,000 ppm	Not established	250 ppm	
Ethyl 3-Ethoxypropionate	Not established	Not established	Not established	Not established	Not established	Not established
Butyl Alcohol	20 ppm CA ON: 20 ppm (TWA)	Not established	100 ppm	Not established	50 ppm skin	
Carbon Black	3 mg/m3 CA ON: 3 mg/m3 (Inhalable) TWA	Not established	3.5 mg/m3	Not established	3.5 mg/m3	
Eye/type.....	Liquid chemical goggles.					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Gloves/ type.....	Chemical resistant gloves.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available.					
Appropriate engineering controls.....	Local exhaust at points of emission.					

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Auto ignition temperature (deg C).....	> 343°C .
Initial boiling point / boiling range (deg C).	97°C.
Partition coefficient — n-octanol/water.....	Not available.
Colour.....	Gray.
Evaporation rate.....	Not available.
Flash point (deg C), method.....	-18°C.
Melting / Freezing point (deg C).....	Not available.
Lower flammable limit (% vol).....	1.2.
Odour.....	Solvent odour.
Odour threshold (ppm).....	Not available.
pH.....	Not applicable.
Appearance/Physical state.....	Liquid.
Relative Density (Specific Gravity).....	10.65 lb/USG - 1.278.
Solubility.....	Slightly soluble in water.
Upper flammable limit (% vol).....	12.0.
Vapour density (air=1).....	>1.
Vapour pressure (mm Hg).....	Not available.
Viscosity.....	7400 cPs Zahn #2 21 sec.
VOC (less water).....	215.7 g/L - 1.8 Lb/USG.

**SECTION 10: STABILITY AND REACTIVITY**

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity .....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Conditions to avoid, including static discharge, shock or vibration .....	Keep away from heat. Incompatible with strong oxidizers. Amines. Strong bases. Strong acids.
Hazardous decomposition products.....	Dense black smoke. Oxides of nitrogen. Oxides of carbon (CO,CO2).
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.

**PRODUCT: PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY****SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Talc	Not available	Not available
Titanium Dioxide	>6.8 mg/L (4 hr)	> 10,000 mg/kg (rat, oral) > 10,000 mg/kg (rabbit, dermal)
Xylene	6350 ppm 4 hours rat	>3523 mg/kg rat oral
Propylene Glycol Methyl Ether	54.6 mg/L rat	36,000 mg/kg rat oral
Acetone	50,100 mg/m <sup>3</sup> 8 hours, rat	5,800 mg/kg (rat oral)
Ethyl 3-Ethoxypropionate	>998 ppm 6 hours	4,309 mg/kg rat oral 4,080 mg/kg rabbit dermal
Butyl Alcohol	8,000 ppm 4 hours	790 mg/kg rat oral 3,400 mg/kg rabbit dermal
Carbon Black	Not available	>10,000 mg/kg oral rat 3,000 mg/kg dermal rabbit
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Breathing this material may be harmful. Can be irritating to eyes and skin. Can cause dizziness and headaches upon ingestion.	
Effects of chronic exposure.....	Prolonged or repeated exposure may lead to allergic skin reactions. Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material.....	IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies. IARC has classified Titanium Dioxide as a group 2B carcinogen. This product contains non-asbestiform Talc, which is classified as a Group 3 (not classifiable as to carcinogenicity to humans) by IARC .	
Reproductive effects.....	High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known.	

**SECTION 12: ECOLOGICAL INFORMATION**

Environmental..... Do not allow to enter waters, waste water or soil.  
Persistence and degradability..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging This material and its container must be disposed of as hazardous waste. Avoid release to the environment.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.  
IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II.  
IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E.  
Marine Pollutant..... No.  
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**SECTION 15: REGULATORY INFORMATION**

CEPA status..... On Domestic Substances List (DSL).  
TSCA inventory status..... All components are listed.  
OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.  
SARA Title III  
Section 302 - extremely hazardous ..... None.  
substances  
Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.  
Section 313..... Butyl alcohol. Xylene.  
EPA hazardous air pollutants (HAPS) ..... Xylene.  
40CFR63  
California Proposition 65..... This product contains Carbon Black known to the State of California to cause cancer. California is in the process of listing Titanium Dioxide to Proposition 65 as a known carcinogen.

**PRODUCT: PF 495-1 2K HIGH SOLIDS EPOXY PRIMER/SEALER GRAY****SECTION 16: OTHER INFORMATION**

Prepared by: ..... REGULATORY AFFAIRS.  
Telephone number:..... (800) 387-7981.  
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Review Date:..... 2021-11-05.  
Date of the latest revision of the safety .. 2016-04-12  
data sheet