

A rubberized and asphalt coating for sealing, hiding repairs, rustproofing and sound deadening. Excellent adhesion to bare or painted metals and plastics. It remains tacky and cannot be painted.

PRODUCT	SIZE	COLOR
PF 500	560 g (19.75 oz)	Black
PF 561	439 g (15.50 oz)	Black

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**

**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

**NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.**

#### SUITABLE SUBSTRATES:

- Metals
- Plastics
- House gutters
- Fence posts
- Trees after pruning

#### ADVANTAGES:

- Resists abrasion
- Remains flexible
- High solids

#### DIRECTIONS FOR USE:

1. Shake can for 1 minute after mixing ball moves freely. NOTE: Insufficient mixing may cause permanent plugging of the sprayhead.
2. Spray approximately 25 to 30 cm (10 to 12 inches) from surface. Distance will determine texture.
3. To assure that entire contents will be dispensed, always have the dot on can rim facing toward surface to be sprayed.
4. Apply a medium and even coat.
5. When finished, turn can upside down and spray about 3 seconds to clean out spray head. Dry to touch and ready to drive off in 60 minutes.

#### TECHNICAL DATA:

	PF 500	PF 561
Physical State	Aerosol	
Color:	Black	
Odour:	Hydrocarbon odour	
Solubility :	Slightly soluble in water	
Flash point:	23°C (73.4°F)(liquid)	

<b>Auto ignition temperature:</b>	> 232°C (> 450°F)
<b>VOC:</b>	36.85% by weight

#### **PRECAUTIONARY INFORMATION**

Refer to product label and Safety Data Sheet for health and safety information before using this product.

#### **SAFETY CONSIDERATION**

Safety Data Sheets are available at [www.proformproducts.com](http://www.proformproducts.com) or upon request at [info@proformproducts.com](mailto:info@proformproducts.com). These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

#### **TECHNICAL INFORMATION**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

#### **PRODUCT USE**

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

#### **WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY**

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.