



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)

Recommended use and restrictions on .. Paints.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 2 F: 4 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosols — Category 1. Gases Under Pressure: Liquefied Gas. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. Carcinogenicity — Category 1. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H350 This product contains ingredients that may cause cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P332 + P313 - If skin irritation occurs get medical attention or advice. P308 + P313 If exposed or concerned, get medical advice/attention.

Storage..... P233 Keep container tightly closed. P403 Store in a well ventilated area. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

PRODUCT: PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|------------------------------------|------------|-------|
| Asphalt | 8052-42-4 | 10-30 |
| Xylene | 1330-20-7 | 7-13 |
| Mineral Spirits (Stoddard solvent) | 8052-41-3 | 5-10 |
| Hydrocarbon Resin | 64742-16-1 | 5-10 |
| Propane | 74-98-6 | 5-10 |
| Isobutane | 75-28-5 | 3-7 |
| Ethylene Glycol | 107-21-1 | 1-5 |
| Crystalline Silica | 14808-60-7 | 1-5 |
| Carbon Black | 1333-86-4 | 0.1-1 |

SECTION 04: FIRST-AID MEASURES

| | |
|--|---|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. This product contains ingredients that may cause cancer. This product contains ingredients that are suspected of damaging fertility or the unborn child. Harmful if swallowed, in contact with skin or if inhaled. |
| Additional information..... | The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable and unsuitable extinguishing media | "Alcohol" foam, CO ₂ , dry chemical. Do not use water in a jet. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO ₂). Hydrocarbon fumes and smoke. |
| Special protective equipment and precautions for fire-fighters | Extremely flammable aerosol. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-----------------|---|
| Leak/spill..... | Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel or pump to drum or salvage tank. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|---|

SECTION 07: HANDLING AND STORAGE

| | |
|------------------------------------|---|
| Precautions for safe handling..... | Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
|------------------------------------|---|

PRODUCT: PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)**SECTION 07: HANDLING AND STORAGE**

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use. Do not store above 50 deg C.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|------------------------------------|--|-------------------|-------------------------------|-------------------|--------------------|
| Asphalt | 0.5 mg/cu m (Inhalable fraction) 8hr | Not established | Not established | Not established | 5 mg/m3 15 minutes |
| Xylene | 50 ppm CA ON: 100ppm (TWA); 150ppm (STEL) | 150 ppm | 100 ppm TWA | Not established | Not established |
| Mineral Spirits (Stoddard solvent) | 100 ppm CA ON: 100 ppm (TWA) | Not established | 100ppm, 525 mg/m ³ | Not established | Not established |
| Hydrocarbon Resin | Not established | Not established | Not established | Not established | Not established |
| Propane | 1,000 ppm | Not established | 1,000 ppm | Not established | 1,000 ppm |
| Isobutane | Not established | Not established | Not established | Not established | 800 ppm |
| Ethylene Glycol | 50 ppm | 100 mg/m3 Ceiling | 50 ppm Ceiling | 125 mg/m3 Ceiling | Not Established |
| Crystalline Silica | 0.025 mg/m3 CA ON: 0.025 mg/m3 Respirable | Not established | 0.1 mg/m3 TWA | Not established | 0.05 mg/m3 |
| Carbon Black | 3 mg/m3 CA ON: 3 mg/m3 (Inhalable) TWA | Not established | 3.5 mg/m3 | Not established | 3.5 mg/m3 |

Personal Protective Equipment

| | |
|---------------------------------------|---|
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. |
| Eye/type..... | Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists. |
| Gloves/ type..... | Chemical resistant gloves. |
| Clothing/type..... | Wear adequate protective clothes. |
| Footwear/type..... | Safety boots per local regulations. |
| Other/type..... | Emergency showers and eye wash stations should be available. |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--------------------------------------|
| Appearance/Physical state..... | Aerosol. |
| Colour | |
| Odour..... | Hydrocarbon odour. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | 85-95 psig @ 20°C . |
| Vapour density (air=1)..... | >1. |
| pH..... | Not applicable. |
| Relative Density (Specific Gravity)..... | 1.212. (Aerosol) . 1.332. (Liquid) . |
| Melting / Freezing point (deg C)..... | -40°C. (liquid). |
| Solubility..... | Slightly soluble in water. |
| Initial boiling point / boiling range (deg C). | 136. |
| Evaporation rate..... | <1. |
| Flash point (deg C), method..... | 23. (liquid). |
| Auto ignition temperature (deg C)..... | > 232. |
| Upper flammable limit (% vol)..... | 7. (liquid). |
| Lower flammable limit (% vol)..... | 0.9. (liquid). |
| Partition coefficient — n-octanol/water..... | Not available. |
| % Volatile by volume..... | Not available. |
| VOC (less water)..... | 3.09 lbs/USG. |
| Viscosity..... | 6100 cPs., #4 @20 RPM. (liquid). |

PRODUCT: PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)**SECTION 10: STABILITY AND REACTIVITY**

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |
| Conditions to avoid, including static | Keep away from heat. Incompatible with strong oxidizers. |
| discharge, shock or vibration | |
| Hazardous decomposition products..... | See hazardous combustion products section 5. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|------------------------------------|----------------------------|--|
| Asphalt | >94.4 mg/cu m 4.5hr rat | >5000 mg/kg rat oral >2000 mg/kg rabbit dermal |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Mineral Spirits (Stoddard solvent) | 5500 ppm (4 hrs) | 5000 mg/kg (oral, rat) |
| Hydrocarbon Resin | No Data | 50,000 mg/kg (oral, rat) |
| Propane | >1,464 mg/L 15 minutes rat | Not available |
| Isobutane | 52 mg/L 1 hour mouse | Not available |
| Ethylene Glycol | Not Available | 4,700 mg/kg (Rat Oral). 10,600 mg/kg (dermal, rat) |
| Crystalline Silica | Not available | >22,500 mg/kg (oral rat) |
| Carbon Black | Not available | >10,000 mg/kg (oral rat) 3,000 mg/kg (dermal rabbit) |

| | |
|--------------------------------------|--|
| Route of exposure..... | Eye contact. Skin contact. Inhalation. |
| Effects of acute exposure..... | The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. |
| Skin contact..... | Can cause moderate irritation, defatting and dermatitis. |
| Skin absorption..... | Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation. |
| Eye contact..... | Can cause redness, irritation, tissue destruction. |
| Inhalation (acute)..... | Solvent vapours may be irritating to the eyes, nose and throat, resulting in redness, burning and itching of eyes, dryness of the throat and tightness in the chest. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects. |
| Inhalation (chronic)..... | Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation. |
| Ingestion..... | Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed. |
| Carcinogenicity of material..... | Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies. |
| Reproductive effects..... | High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. |
| Specific Target Organ Toxicity | Causes damage to organs. May cause respiratory irritation. |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|--|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. |
|---|--|

PRODUCT: PF 500 NON PAINTABLE RUBBERIZED UNDERCOAT (BLACK)**SECTION 14: TRANSPORT INFORMATION**

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre. |
| DOT Classification (Road)..... | UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons). |
| IATA Classification (Air)..... | UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity. Do not ship by air without checking appropriate IATA regulations. |
| IMDG Classification (Marine)..... | UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG regulations for limited quantity exemptions. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|---|
| CEPA status..... | On Domestic Substances List (DSL). |
| TSCA inventory status..... | All components are listed. |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health, fire hazard. |
| Section 313..... | Xylene. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | Xylene. |
| California Proposition 65..... | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Ethylene glycol (ingested)). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Carbon black - airborne, unbound particles of respirable size). (Silica, crystalline (airborne particles of respirable size). (Ethyl benzene). For more information, go to www.P65Warnings.ca.gov . |

SECTION 16: OTHER INFORMATION

| | |
|---|---|
| Prepared by: | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com . |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process. |
| Review Date:..... | 2022-11-30. |
| Date of the latest revision of the safety data sheet .. | 2018-06-27 |