

Formulate to remove mold release agents, wax, grease, silicone, tar, bugs, adhesive from back of tape, and other contaminants from painted and unpainted plastic or metal surfaces. Includes anti stat additive. Reduces charge of static spark.

PRODUCT**SIZE****PF 525**

425 g (15 oz)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES

- Painted and unpainted plastic
- Metal

ADVANTAGES

- Removes solvent soluble contaminants from painted and unpainted plastic and metal
- Easy to use. Just spray on and wipe off
- Contains no petroleum products. Petroleum based cleaners can leave an oily film on the surface and cause adhesion problems.
- Reduces charge of static spark
- Product does not contain mineral spirits
- Safe on all plastics (except polycarbonate)
- Does not leave any residue

DIRECTIONS FOR USE:

1. Wash surface with soap and water.
2. Spray heavy wet coat of cleaner on surface.
3. Wipe in one direction with a clean lint-free cloth before cleaner evaporates.
4. Let dry thoroughly before proceeding.
5. It may be necessary to repeat these steps a second time on heavily contaminated surfaces.

Note: It is important to test the compatibility of this product with your paint system. Use proper precautionary measures for handling and follow all proper local disposal procedures regulation. DO NOT USE ON POLYCARBONATE.

TECHNICAL DATA:

| | |
|-----------------------|----------------------|
| | PF 525 |
| Physical State | Aerosol |
| Color: | Clear to pale yellow |

| | |
|-----------------------------------|-----------------------------------|
| Odour: | Aromatic |
| Solubility : | Negligible |
| Flash point: | 25°C (77°F) (estimate for liquid) |
| Auto ignition temperature: | 432°C (810°F) |

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.